Cubical Categories

Tanguy Massacrier and Georg Struth

November 9, 2026

Abstract

This AFP entry formalises cubical ω-categories and cubical ω-categories with connections in the style of single-set categories. Cubical categories, and the cubical sets on which they are based, have their origins and main applications in algebraic topology. Applications in computer science include homotopy type theory, higher-dimensional automata in concurrency theory and higher-dimensional rewriting. The single-set axiomatisation, introduced in these components and a companion paper, allows a formalisation based on Isabelle's type classes.

Contents

1 Introductory Remarks **1**

2 Indexed Catoids **2**
2.1 Indexed catoids and categories 2

3 Cubical Categories **4**
3.1 Semi-cubical ω-categories 4
3.2 Type classes for cubical ω-categories 8

4 Cubical Categories with Connections **28**

5 Cubical $(\omega, 0)$-Categories with Connections **39**

1 Introductory Remarks

Based on a formalisation of catoids and single-set categories in the AFP [2] we develop single-set axiomatisations for cubical ω-categories with and without connections. A detailed explanation of the single-set approach, the classical approach to cubical ω-categories and the proof of equivalence of the single-set and the classical approach can be found in a companion article [1]. Isabelle, with its high degree of proof automation, has been instrumental for developing the single-set axioms introduced in this article.

2 Indexed Catoids

theory *ICatoids*
  imports *Catoids.Catoid*

begin

All categories considered in this component are single-set categories.

no-notation *src* (‹σ›)

notation *True* (‹*tt*›)
notation *False* (‹*ff*›)

abbreviation *Fix* :: ('*a* ⇒ '*a*) ⇒ '*a set* **where**
  Fix f ≡ {*x*. *f x* = *x*}

First we lift locality to powersets.

lemma (**in** *local-catoid*) *locality-lifting*: (*X* ⋆ *Y* ≠ {}) = (*Tgt X* ∩ *Src Y* ≠ {})
proof−
  have (*X* ⋆ *Y* ≠ {}) = (∃ *x y*. *x* ∈ *X* ∧ *y* ∈ *Y* ∧ *x* ⊙ *y* ≠ {})
    by (*metis* (*mono-tags*, *lifting*) *all-not-in-conv conv-exp2*)
  also have ... = (∃ *x y*. *x* ∈ *X* ∧ *y* ∈ *Y* ∧ *tgt x* = *src y*)
    using *local.st-local* **by** *auto*
  also have ... = (*Tgt X* ∩ *Src Y* ≠ {})
    by *blast*
  finally show *?thesis*.
qed

The following lemma about functional catoids is useful in proofs.

lemma (**in** *functional-catoid*) *pcomp-def-var4*: Δ *x y* ⟹ *x* ⊙ *y* = {*x* ⊗ *y*}
  using *local.pcomp-def-var3* **by** *blast*

2.1 Indexed catoids and categories

class *face-map-op* =
  fixes *fmap* :: *nat* ⇒ *bool* ⇒ '*a* ⇒ '*a* (‹∂›)

begin

abbreviation *Face* :: *nat* ⇒ *bool* ⇒ '*a set* ⇒ '*a set* (‹∂∂›) **where**
  ∂∂ *i* α ≡ *image* (∂ *i* α)

abbreviation *face-fix* :: *nat* ⇒ '*a set* **where**
  face-fix i ≡ *Fix* (∂ *i ff*)

abbreviation *fFx i x* ≡ (∂ *i ff x* = *x*)

abbreviation *FFx i X* ≡ (∀ *x* ∈ *X*. *fFx i x*)

end

class *icomp-op* =
  fixes *icomp* :: *'a* ⇒ *nat* ⇒ *'a* ⇒ *'a set* (‹-⊙_-›[*70*,*70*,*70*] *70*)

class *imultisemigroup* = *icomp-op* +
  assumes *iassoc*: (⋃ *v* ∈ *y* ⊙$_i$ *z*. *x* ⊙$_i$ *v*) = (⋃ *v* ∈ *x* ⊙$_i$ *y*. *v* ⊙$_i$ *z*)

begin

sublocale *ims*: *multisemigroup* λ*x y*. *x* ⊙$_i$ *y*
  by *unfold-locales* (*simp add*: *local.iassoc*)

abbreviation *DD* ≡ *ims*.Δ

abbreviation *iconv* :: *'a set* ⇒ *nat* ⇒ *'a set* ⇒ *'a set* (‹-⋆_-›[*70*,*70*,*70*] *70*) **where**
  X ⋆$_i$ *Y* ≡ *ims.conv i X Y*

end

class *icatoid* = *imultisemigroup* + *face-map-op* +
  assumes *iDst*: *DD i x y* ⟹ ∂ *i tt x* = ∂ *i ff y*
  and *is-absorb* [*simp*]: (∂ *i ff x*) ⊙$_i$ *x* = {*x*}
  and *it-absorb* [*simp*]: *x* ⊙$_i$ (∂ *i tt x*) = {*x*}

begin

Every indexed catoid is a catoid.

sublocale *icid*: *catoid* λ*x y*. *x* ⊙$_i$ *y* ∂ *i ff* ∂ *i tt*
  by *unfold-locales* (*simp-all add*: *iDst*)

lemma *lFace-Src*: ∂∂ *i ff* = *icid.Src i*
  by *simp*

lemma *uFace-Tgt*: ∂∂ *i tt* = *icid.Tgt i*
  by *simp*

lemma *face-fix-sfix*: *face-fix* = *icid.sfix*
  by *force*

lemma *face-fix-tfix*: *face-fix* = *icid.tfix*
  using *icid.stopp.stfix-set* **by** *presburger*

lemma *face-fix-prop* [*simp*]: *x* ∈ *face-fix i* = (∂ *i* α *x* = *x*)
  by (*smt* (*verit*, *del-insts*) *icid.stopp.st-fix mem-Collect-eq*)

lemma *fFx-prop*: *fFx i x* = (∂ *i* α *x* = *x*)
  by (*metis icid.st-eq1 icid.st-eq2*)

end

class *icategory* = *icatoid* +
  assumes *locality*: $\partial\ i\ tt\ x = \partial\ i\ ff\ y \Longrightarrow DD\ i\ x\ y$
  and *functionality*: $z \in x \odot_i y \Longrightarrow z' \in x \odot_i y \Longrightarrow z = z'$

begin

Every indexed category is a (single-set) category.

sublocale *icat*: *single-set-category* $\lambda x\ y.\ x \odot_i y\ \partial\ i\ ff\ \partial\ i\ tt$
  apply *unfold-locales*
    apply (*simp add*: *local.functionality*)
  apply (*metis dual-order.eq-iff icid.src-local-cond icid.st-locality-locality local.locality*)
  by (*metis icid.st-locality-locality local.iDst local.locality order-refl*)

abbreviation *ipcomp* :: $'a \Rightarrow nat \Rightarrow 'a \Rightarrow 'a$ ($\langle$-⊗_-$\rangle$[70,70,70]70) **where**
  $x \otimes_i y \equiv icat.pcomp\ i\ x\ y$

lemma *iconv-prop*: $X \star_i Y = \{x \otimes_i y \mid x\ y.\ x \in X \wedge y \in Y \wedge DD\ i\ x\ y\}$
  by (*rule antisym*) (*clarsimp simp*: *ims.conv-def*, *metis local.icat.pcomp-def-var*)+

abbreviation *dim-bound* $k\ x \equiv (\forall i.\ k \leq i \longrightarrow fFx\ i\ x)$

abbreviation *fin-dim* $x \equiv (\exists k.\ dim\text{-}bound\ k\ x)$

end

end

3 Cubical Categories

theory *CubicalCategories*
  imports *ICatoids*

begin

All categories considered in this component are single-set categories.

3.1 Semi-cubical ω-categories

We first define a class for cubical ω-categories without symmetries.

class *semi-cubical-omega-category* = *icategory* +
  assumes *face-comm*: $i \neq j \Longrightarrow \partial\ i\ \alpha \circ \partial\ j\ \beta = \partial\ j\ \beta \circ \partial\ i\ \alpha$
  and *face-func*: $i \neq j \Longrightarrow DD\ j\ x\ y \Longrightarrow \partial\ i\ \alpha\ (x \otimes_j y) = \partial\ i\ \alpha\ x \otimes_j \partial\ i\ \alpha\ y$
  and *interchange*: $i \neq j \Longrightarrow DD\ i\ w\ x \Longrightarrow DD\ i\ y\ z \Longrightarrow DD\ j\ w\ y \Longrightarrow DD\ j\ x\ z$
    $\Longrightarrow (w \otimes_i x) \otimes_j (y \otimes_i z) = (w \otimes_j y) \otimes_i (x \otimes_j z)$
  and *fin-fix*: $\exists k. \forall i.\ k \leq i \longrightarrow fFx\ i\ x$

begin

lemma *pcomp-face-func-DD*: $i \neq j \Longrightarrow DD\ j\ x\ y \Longrightarrow DD\ j\ (\partial\ i\ \alpha\ x)\ (\partial\ i\ \alpha\ y)$
by (*metis comp-apply icat.st-local local.face-comm*)

lemma *comp-face-func*: $i \neq j \Longrightarrow (\partial\partial\ i\ \alpha)\ (x \odot_j y) \subseteq \partial\ i\ \alpha\ x \odot_j \partial\ i\ \alpha\ y$
using *local.icat.pcomp-def-var local.icat.pcomp-def-var4 local.face-func pcomp-face-func-DD*
by *fastforce*

lemma *interchange-var*:
assumes $i \neq j$
and $(w \odot_i x) \star_j (y \odot_i z) \neq \{\}$
and $(w \odot_j y) \star_i (x \odot_j z) \neq \{\}$
shows $(w \odot_i x) \star_j (y \odot_i z) = (w \odot_j y) \star_i (x \odot_j z)$
proof−
have *h1*: *DD i w x*
using *assms*(*2*) *local.ims.conv-def* **by** *force*
have *h2*: *DD i y z*
using *assms*(*2*) *multimagma.conv-distl* **by** *force*
have *h3*: *DD j w y*
using *assms*(*3*) *multimagma.conv-def* **by** *force*
have *h4*: *DD j x z*
using *assms*(*3*) *local.icid.stopp.conv-def* **by** *force*
have $(w \odot_i x) \star_j (y \odot_i z) = \{w \otimes_i x\} \star_j \{y \otimes_i z\}$
using *h1 h2 local.icat.pcomp-def-var4* **by** *force*
also have $\ldots = \{(w \otimes_i x) \otimes_j (y \otimes_i z)\}$
using *assms*(*2*) *calculation local.icat.pcomp-def-var4* **by** *force*
also have $\ldots = \{(w \otimes_j y) \otimes_i (x \otimes_j z)\}$
by (*simp add*: *assms*(*1*) *h1 h2 h3 h4 local.interchange*)
also have $\ldots = \{w \otimes_j y\} \star_i \{x \otimes_j z\}$
by (*metis assms*(*3*) *h3 h4 local.icat.pcomp-def-var4 multimagma.conv-atom*)
also have $\ldots = (w \odot_j y) \star_i (x \odot_j z)$
using *h3 h4 local.icat.pcomp-def-var4* **by** *force*
finally show *?thesis*.
qed

lemma *interchange-var2*:
assumes $i \neq j$
and $(\bigcup a \in w \odot_i x.\ \bigcup b \in y \odot_i z.\ a \odot_j b) \neq \{\}$
and $(\bigcup c \in w \odot_j y.\ \bigcup d \in x \odot_j z.\ c \odot_i d) \neq \{\}$
shows $(\bigcup a \in w \odot_i x.\ \bigcup b \in y \odot_i z.\ a \odot_j b) = (\bigcup c \in w \odot_j y.\ \bigcup d \in x \odot_j z.\ c \odot_i d)$
proof−
have $\{(w \otimes_i x) \otimes_j (y \otimes_i z)\} = \{(w \otimes_j y) \otimes_i (x \otimes_j z)\}$
using *assms*(*1*) *assms*(*2*) *assms*(*3*) *local.interchange* **by** *fastforce*
thus *?thesis*
by (*metis assms*(*1*) *assms*(*2*) *assms*(*3*) *interchange-var multimagma.conv-def*)
qed

lemma *face-compat*: $\partial\ i\ \alpha \circ \partial\ i\ \beta\ = \partial\ i\ \beta$
by (*metis* (*full-types*, *lifting*) *ext comp-def*[*of* $\partial\ i\ tt\ \partial\ i\ tt$] *comp-def*[*of* $\partial\ i\ tt\ \partial\ i\ ff$]
comp-def[*of* $\partial\ i\ ff\ \partial\ i\ tt$] *comp-def*[*of* $\partial\ i\ ff\ \partial\ i\ ff$] *icid.ts-compat*[*of i*]
local.icid.stopp.ts-compat[*of i*])

lemma *face-compat-var* [*simp*]: $\partial\ i\ \alpha\ (\partial\ i\ \beta\ x) = \partial\ i\ \beta\ x$
by (*metis* (*full-types*) *icid.ts-compat local.icid.stopp.ts-compat*)

lemma *face-comm-var*: $i \neq j \Longrightarrow \partial\ i\ \alpha\ (\partial\ j\ \beta\ x) = \partial\ j\ \beta\ (\partial\ i\ \alpha\ x)$
by (*meson comp-eq-dest local.face-comm*)

lemma *face-comm-lift*: $i \neq j \Longrightarrow \partial\partial\ i\ \alpha\ (\partial\partial\ j\ \beta\ X) = \partial\partial\ j\ \beta\ (\partial\partial\ i\ \alpha\ X)$
by (*simp add*: *image-comp local.face-comm*)

lemma *face-func-lift*: $i \neq j \Longrightarrow (\partial\partial\ i\ \alpha)\ (X \star_j Y) \subseteq \partial\partial\ i\ \alpha\ X \star_j \partial\partial\ \ i\ \alpha\ Y$
using *ims.conv-def comp-face-func dual-order.refl image-subset-iff* **by** *fastforce*

lemma *pcomp-lface*: $DD\ i\ x\ y \Longrightarrow \partial\ i\ ff\ (x \otimes_i y) = \partial\ i\ ff\ x$
by (*simp add*: *icat.st-local local.icat.sscatml.locall-var*)

lemma *pcomp-uface*: $DD\ i\ x\ y \Longrightarrow \partial\ i\ tt\ (x \otimes_i y) = \partial\ i\ tt\ y$
using *icat.st-local local.icat.sscatml.localr-var* **by** *force*

lemma *interchange-DD1*:
assumes $i \neq j$
and $DD\ i\ w\ x$
and $DD\ i\ y\ z$
and $DD\ j\ w\ y$
and $DD\ j\ x\ z$
shows $DD\ j\ (w \otimes_i x)\ (y \otimes_i z)$
proof−
have *a*: $\partial\ j\ tt\ (w \otimes_i x) = \partial\ j\ tt\ w \otimes_i \partial\ j\ tt\ x$
using *assms*(*1*) *assms*(*2*) *face-func* **by** *simp*
also have $\ldots\ = \partial\ j\ ff\ y \otimes_i \partial\ j\ ff\ z$
using *assms*(*4*) *assms*(*5*) *local.iDst* **by** *simp*
also have $\ldots = \partial\ j\ ff\ (y \otimes_i z)$
using *assms*(*1*) *assms*(*3*) *face-func* **by** *simp*
finally show *?thesis*
using *local.locality* **by** *simp*
qed

lemma *interchange-DD2*:
assumes $i \neq j$
and $DD\ i\ w\ x$
and $DD\ i\ y\ z$
and $DD\ j\ w\ y$
and $DD\ j\ x\ z$
shows $DD\ i\ (w \otimes_j y)\ (x \otimes_j z)$

using *assms interchange-DD1* **by** *simp*

lemma *face-idem1*: $\partial\ i\ \alpha\ x = \partial\ i\ \beta\ y \Longrightarrow \partial\ i\ \alpha\ x \odot_i \partial\ i\ \beta\ y = \{\partial\ i\ \alpha\ x\}$
by (*metis face-compat-var local.it-absorb*)

lemma *face-pidem1*: $\partial\ i\ \alpha\ x = \partial\ i\ \beta\ y \Longrightarrow \partial\ i\ \alpha\ x \otimes_i \partial\ i\ \beta\ y = \partial\ i\ \alpha\ x$
by (*metis face-compat-var local.icat.sscatml.l0-absorb*)

lemma *face-pidem2*: $\partial\ i\ \alpha\ x \neq \partial\ i\ \beta\ y \Longrightarrow \partial\ i\ \alpha\ x \odot_i \partial\ i\ \beta\ y = \{\}$
using *icat.st-local* **by** *force*

lemma *face-fix-comp-var*: $i \neq j \Longrightarrow \partial\partial\ i\ \alpha\ (\partial\ i\ \alpha\ x \odot_j \partial\ i\ \alpha\ y) = \partial\ i\ \alpha\ x \odot_j \partial\ i\ \alpha\ y$
by (*metis* (*mono-tags*, *lifting*) *comp-face-func empty-is-image face-compat-var local.icat.pcomp-def-var4 subset-singletonD*)

lemma *interchange-lift-aux*: $x \in X \Longrightarrow y \in Y \Longrightarrow DD\ i\ x\ y \Longrightarrow x \otimes_i y \in X \star_i Y$
using *local.icat.pcomp-def-var local.ims.conv-exp2* **by** *blast*

lemma *interchange-lift1*:
assumes $i \neq j$
and $\exists\, w \in W.\ \exists\, x \in X.\ \exists\, y \in Y.\ \exists\, z \in Z.\ DD\ i\ w\ x \wedge DD\ i\ y\ z \wedge DD\ j\ w\ y \wedge DD\ j\ x\ z$
shows $((W \star_i X) \star_j (Y \star_i Z)) \cap ((W \star_j Y) \star_i (X \star_j Z)) \neq \{\}$
proof−
obtain $w\ x\ y\ z$ **where** *h1*: $w \in W \wedge x \in X \wedge y \in Y \wedge z \in Z \wedge DD\ i\ w\ x \wedge DD\ i\ y\ z \wedge DD\ j\ w\ y \wedge DD\ j\ x\ z$
using *assms*(*2*) **by** *blast*
have *h5*: $(w \otimes_i x) \otimes_j (y \otimes_i z) \in (W \star_i X) \star_j (Y \star_i Z)$
using *assms*(*1*) *h1 interchange-lift-aux interchange-DD2* **by** *presburger*
have $(w \otimes_j y) \otimes_i (x \otimes_j z) \in (W \star_j Y) \star_i (X \star_j Z)$
by (*simp add*: *assms*(*1*) *h1 interchange-lift-aux interchange-DD2*)
thus *?thesis*
using *assms*(*1*) *h1 h5 local.interchange* **by** *fastforce*
qed

lemma *interchange-lift2*:
assumes $i \neq j$
and $\forall\, w \in W.\ \forall\, x \in X.\ \forall\, y \in Y.\ \forall\, z \in Z.\ DD\ i\ w\ x \wedge DD\ i\ y\ z \wedge DD\ j\ w\ y \wedge DD\ j\ x\ z$
shows $((W \star_i X) \star_j (Y \star_i Z)) = ((W \star_j Y) \star_i (X \star_j Z))$
proof−
{fix t
have $(t \in (W \star_i X) \star_j (Y \star_i Z)) = (\exists\, w \in W.\ \exists\, x \in X.\ \exists\, y \in Y.\ \exists\, z \in Z.\ DD\ i\ w\ x \wedge DD\ i\ y\ z \wedge DD\ j\ (w \otimes_i x)\ (y \otimes_i z) \wedge t = (w \otimes_i x) \otimes_j (y \otimes_i z))$
unfolding *iconv-prop* **by** *force*
also have $\ldots = (\exists\, w \in W.\ \exists\, x \in X.\ \exists\, y \in Y.\ \exists\, z \in Z.\ DD\ i\ w\ x \wedge DD\ i\ y\ z \wedge DD\ j\ w\ y \wedge DD\ j\ x\ z \wedge t = (w \otimes_i x) \otimes_j (y \otimes_i z))$
using *assms*(*1*) *assms*(*2*) *interchange-DD2* **by** *simp*

also have $\ldots = (\exists\, w \in W.\ \exists\, x \in X.\ \exists\, y \in Y.\ \exists\, z \in Z.\ DD\ j\ w\ y \wedge DD\ j\ x\ z \wedge DD\ j\ w\ y \wedge DD\ j\ x\ z \wedge t = (w \otimes_j y) \otimes_i (x \otimes_j z))$
by (*simp add*: *assms*(1) *assms*(2) *local.interchange*)
also have $\ldots = (\exists\, w \in W.\ \exists\, x \in X.\ \exists\, y \in Y.\ \exists\, z \in Z.\ DD\ j\ w\ y \wedge DD\ j\ x\ z \wedge DD\ i\ (w \otimes_j y)\ (x \otimes_j z) \wedge t = (w \otimes_j y) \otimes_i (x \otimes_j z))$
using *assms*(1) *assms*(2) *interchange-DD1* **by** *simp*
also have $\ldots = (t \in (W \star_j Y) \star_i (X \star_j Z))$
unfolding *iconv-prop* **by** *force*
finally have $(t \in (W \star_i X) \star_j (Y \star_i Z)) = (t \in (W \star_j Y) \star_i (X \star_j Z))$
by *blast*}
thus *?thesis*
by *force*
qed

lemma *double-fix-prop*: $(\partial\ i\ \alpha\ (\partial\ j\ \beta\ x) = x) = (fFx\ i\ x \wedge fFx\ j\ x)$
by (*metis face-comm-var face-compat-var*)

end

3.2 Type classes for cubical ω-categories

abbreviation *diffSup* :: *nat* ⇒ *nat* ⇒ *nat* ⇒ *bool* **where**
diffSup i j k ≡ $(i - j \geq k \vee j - i \geq k)$

class *symmetry-ops* =
fixes *symmetry* :: *nat* ⇒ *'a* ⇒ *'a* (‹σ›)
and *inv-symmetry* :: *nat* ⇒ *'a* ⇒ *'a* (‹ϑ›)

begin

abbreviation $\sigma\sigma\ i \equiv image\ (\sigma\ i)$

abbreviation $\vartheta\vartheta\ i \equiv image\ (\vartheta\ i)$

symcomp i j composes the symmetry maps from index i to index i+j-1.

primrec *symcomp* :: *nat* ⇒ *nat* ⇒ *'a* ⇒ *'a* (‹Σ›) **where**
$\Sigma\ i\ 0\ x = x$
| $\Sigma\ i\ (Suc\ j)\ x = \sigma\ (i + j)\ (\Sigma\ i\ j\ x)$

inv-symcomp i j composes the inverse symmetries from i+j-1 to i.

primrec *inv-symcomp* :: *nat* ⇒ *nat* ⇒ *'a* ⇒ *'a* (‹Θ›) **where**
$\Theta\ i\ 0\ x = x$
| $\Theta\ i\ (Suc\ j)\ x = \Theta\ i\ j\ (\vartheta\ (i + j)\ x)$

end

Next we define a class for cubical ω-categories.

class *cubical-omega-category* = *semi-cubical-omega-category* + *symmetry-ops* +
assumes *sym-type*: $\sigma\sigma\ i\ (face\text{-}fix\ i) \subseteq face\text{-}fix\ (i + 1)$

and *inv-sym-type*: $\vartheta\vartheta\ i\ (\mathit{face\text{-}fix}\ (i+1)) \subseteq \mathit{face\text{-}fix}\ i$
and *sym-inv-sym*: $\mathit{fFx}\ (i+1)\ x \Longrightarrow \sigma\ i\ (\vartheta\ i\ x) = x$
and *inv-sym-sym*: $\mathit{fFx}\ i\ x \Longrightarrow \vartheta\ i\ (\sigma\ i\ x) = x$
and *sym-face1*: $\mathit{fFx}\ i\ x \Longrightarrow \partial\ i\ \alpha\ (\sigma\ i\ x) = \sigma\ i\ (\partial\ (i+1)\ \alpha\ x)$
and *sym-face2*: $i \neq j \Longrightarrow i \neq j+1 \Longrightarrow \mathit{fFx}\ j\ x \Longrightarrow \partial\ i\ \alpha\ (\sigma\ j\ x) = \sigma\ j\ (\partial\ i\ \alpha\ x)$
and *sym-func*: $i \neq j \Longrightarrow \mathit{fFx}\ i\ x \Longrightarrow \mathit{fFx}\ i\ y \Longrightarrow \mathit{DD}\ j\ x\ y \Longrightarrow$
$\sigma\ i\ (x \otimes_j y) = (\mathit{if}\ j = i+1\ \mathit{then}\ \sigma\ i\ x \otimes_i \sigma\ i\ y\ \mathit{else}\ \sigma\ i\ x \otimes_j \sigma\ i\ y)$
and *sym-fix*: $\mathit{fFx}\ i\ x \Longrightarrow \mathit{fFx}\ (i+1)\ x \Longrightarrow \sigma\ i\ x = x$
and *sym-sym-braid*: $\mathit{diffSup}\ i\ j\ 2 \Longrightarrow \mathit{fFx}\ i\ x \Longrightarrow \mathit{fFx}\ j\ x \Longrightarrow \sigma\ i\ (\sigma\ j\ x) = \sigma\ j\ (\sigma\ i\ x)$

begin

First we prove variants of the axioms.

lemma *sym-type-var*: $\mathit{fFx}\ i\ x \Longrightarrow \mathit{fFx}\ (i+1)\ (\sigma\ i\ x)$
by (*meson image-subset-iff local.face-fix-prop local.sym-type*)

lemma *sym-type-var1* [*simp*]: $\partial\ (i+1)\ \alpha\ (\sigma\ i\ (\partial\ i\ \alpha\ x)) = \sigma\ i\ (\partial\ i\ \alpha\ x)$
by (*metis local.face-compat-var sym-type-var*)

lemma *sym-type-var2* [*simp*]: $\partial\ (i+1)\ \alpha \circ \sigma\ i \circ \partial\ i\ \alpha = \sigma\ i \circ \partial\ i\ \alpha$
unfolding *comp-def fun-eq-iff* **using** *sym-type-var1* **by** *simp*

lemma *sym-type-var-lift-var* [*simp*]: $\partial\partial\ (i+1)\ \alpha\ (\sigma\sigma\ i\ (\partial\partial\ i\ \alpha\ X)) = \sigma\sigma\ i\ (\partial\partial\ i\ \alpha\ X)$
by (*metis image-comp sym-type-var2*)

lemma *sym-type-var-lift* [*simp*]:
assumes *FFx i X*
shows $\partial\partial\ (i+1)\ \alpha\ (\sigma\sigma\ i\ X) = \sigma\sigma\ i\ X$
proof−
have $\partial\partial\ (i+1)\ \alpha\ (\sigma\sigma\ i\ X) = \{\partial\ (i+1)\ \alpha\ (\sigma\ i\ x)\ |x.\ x \in X\}$
by *blast*
also have $\ldots = \{\sigma\ i\ x\ |x.\ x \in X\}$
by (*metis assms local.fFx-prop sym-type-var*)
also have $\ldots = \sigma\sigma\ i\ X$
by (*simp add*: *setcompr-eq-image*)
finally show *?thesis*.
qed

lemma *inv-sym-type-var*: $\mathit{fFx}\ (i+1)\ x \Longrightarrow \mathit{fFx}\ i\ (\vartheta\ i\ x)$
by (*meson image-subset-iff local.face-fix-prop local.inv-sym-type*)

lemma *inv-sym-type-var1* [*simp*]: $\partial\ i\ \alpha\ (\vartheta\ i\ (\partial\ (i+1)\ \alpha\ x)) = \vartheta\ i\ (\partial\ (i+1)\ \alpha\ x)$
by (*metis inv-sym-type-var local.face-compat-var*)

lemma *inv-sym-type-var2* [*simp*]: $\partial\ i\ \alpha \circ \vartheta\ i \circ \partial\ (i+1)\ \alpha = \vartheta\ i \circ \partial\ (i+1)\ \alpha$

unfolding *comp-def fun-eq-iff* **using** *inv-sym-type-var1* **by** *simp*

lemma *inv-sym-type-lift-var* [*simp*]: $\partial\partial\ i\ \alpha\ (\vartheta\vartheta\ i\ (\partial\partial\ (i + 1)\ \alpha\ X)) = \vartheta\vartheta\ i\ (\partial\partial\ (i + 1)\ \alpha\ X)$
by (*metis image-comp inv-sym-type-var2*)

lemma *inv-sym-type-lift*:
assumes *FFx* $(i + 1)\ X$
shows $\partial\partial\ i\ \alpha\ (\vartheta\vartheta\ i\ X) = \vartheta\vartheta\ i\ X$
by (*smt* (*verit*, *best*) *assms image-cong image-ident inv-sym-type-lift-var local.icid.stopp.ST-compat*)

lemma *sym-inv-sym-var1* [*simp*]: $\sigma\ i\ (\vartheta\ i\ (\partial\ (i + 1)\ \alpha\ x)) = \partial\ (i + 1)\ \alpha\ x$
by (*simp add*: *local.sym-inv-sym*)

lemma *sym-inv-sym-var2* [*simp*]: $\sigma\ i \circ \vartheta\ i \circ \partial\ (i + 1)\ \alpha = \partial\ (i + 1)\ \alpha$
unfolding *comp-def fun-eq-iff* **using** *sym-inv-sym-var1* **by** *simp*

lemma *sym-inv-sym-lift-var*: $\sigma\sigma\ i\ (\vartheta\vartheta\ i\ (\partial\partial\ (i + 1)\ \alpha\ X)) = \partial\partial\ (i + 1)\ \alpha\ X$
by (*metis image-comp sym-inv-sym-var2*)

lemma *sym-inv-sym-lift*:
assumes *FFx* $(i + 1)\ X$
shows $\sigma\sigma\ i\ (\vartheta\vartheta\ i\ X) = X$
proof−
have $\sigma\sigma\ i\ (\vartheta\vartheta\ i\ X) = \{\sigma\ i\ (\vartheta\ i\ x)\ |x.\ x \in X\}$
by *blast*
thus *?thesis*
using *assms local.sym-inv-sym* **by** *force*
qed

lemma *inv-sym-sym-var1* [*simp*]: $\vartheta\ i\ (\sigma\ i\ (\partial\ i\ \alpha\ x)) = \partial\ i\ \alpha\ x$
by (*simp add*: *local.inv-sym-sym*)

lemma *inv-sym-sym-var2* [*simp*]: $\vartheta\ i \circ \sigma\ i \circ \partial\ i\ \alpha = \partial\ i\ \alpha$
unfolding *comp-def fun-eq-iff* **by** *simp*

lemma *inv-sym-sym-lift-var* [*simp*]: $\vartheta\vartheta\ i\ (\sigma\sigma\ i\ (\partial\partial\ i\ \alpha\ X)) = \partial\partial\ i\ \alpha\ X$
by (*simp add*: *image-comp*)

lemma *inv-sym-sym-lift*:
assumes *FFx i X*
shows $\vartheta\vartheta\ i\ (\sigma\sigma\ i\ X) = X$
by (*metis assms image-cong image-ident inv-sym-sym-lift-var*)

lemma *sym-fix-var1* [*simp*]: $\sigma\ i\ (\partial\ i\ \alpha\ (\partial\ (i + 1)\ \beta\ x)) = \partial\ i\ \alpha\ (\partial\ (i + 1)\ \beta\ x)$
by (*simp add*: *local.face-comm-var local.sym-fix*)

lemma *sym-fix-var2* [*simp*]: $\sigma\ i \circ \partial\ i\ \alpha \circ \partial\ (i + 1)\ \beta = \partial\ i\ \alpha \circ \partial\ (i + 1)\ \beta$

unfolding *comp-def fun-eq-iff* **using** *sym-fix-var1* **by** *simp*

lemma *sym-fix-lift-var*: $\sigma\sigma\ i\ (\partial\partial\ i\ \alpha\ (\partial\partial\ (i+1)\ \beta\ X)) = \partial\partial\ i\ \alpha\ (\partial\partial\ (i+1)\ \beta\ X)$
by (*metis image-comp sym-fix-var2*)

lemma *sym-fix-lift*:
assumes *FFx i X*
and *FFx* $(i+1)$ *X*
shows $\sigma\sigma\ i\ X = X$
using *assms local.sym-fix* **by** *simp*

lemma *sym-face1-var1*: $\partial\ i\ \alpha\ (\sigma\ i\ (\partial\ i\ \beta\ x)) = \sigma\ i\ (\partial\ (i+1)\ \alpha\ (\partial\ i\ \beta\ x))$
by (*simp add*: *local.sym-face1*)

lemma *sym-face1-var2*: $\partial\ i\ \alpha \circ \sigma\ i \circ \partial\ i\ \beta\ = \sigma\ i \circ \partial\ (i+1)\ \alpha \circ \partial\ i\ \beta$
by (*simp add*: *comp-def local.sym-face1*)

lemma *sym-face1-lift-var*: $\partial\partial\ i\ \alpha\ (\sigma\sigma\ i\ (\partial\partial\ i\ \beta\ X)) = \sigma\sigma\ i\ (\partial\partial\ (i+1)\ \alpha\ (\partial\partial\ i\ \beta\ X))$
by (*metis image-comp sym-face1-var2*)

lemma *sym-face1-lift*:
assumes *FFx i X*
shows $\partial\partial\ i\ \alpha\ (\sigma\sigma\ i\ X) = \sigma\sigma\ i\ (\partial\partial\ (i+1)\ \alpha\ X)$
by (*metis* (*lifting*) *ext assms inv-sym-sym-lift inv-sym-type-lift-var sym-face1-lift-var sym-type-var-lift*)

lemma *sym-face2-var1*:
assumes $i \neq j$
and $i \neq j+1$
shows $\partial\ i\ \alpha\ (\sigma\ j\ (\partial\ j\ \beta\ x)) = \sigma\ j\ (\partial\ i\ \alpha\ (\partial\ j\ \beta\ x))$
using *assms local.sym-face2* **by** *simp*

lemma *sym-face2-var2*:
assumes $i \neq j$
and $i \neq j+1$
shows $\partial\ i\ \alpha \circ \sigma\ j \circ \partial\ j\ \beta = \sigma\ j \circ \partial\ i\ \alpha \circ \partial\ j\ \beta$
unfolding *comp-def fun-eq-iff* **using** *assms sym-face2-var1* **by** *simp*

lemma *sym-face2-lift-var*:
assumes $i \neq j$
and $i \neq j+1$
shows $\partial\partial\ i\ \alpha\ (\sigma\sigma\ j\ (\partial\partial\ j\ \beta\ X)) = \sigma\sigma\ j\ (\partial\partial\ i\ \alpha\ (\partial\partial\ j\ \beta\ X))$
by (*metis assms image-comp sym-face2-var2*)

lemma *sym-face2-lift*:
assumes $i \neq j$
and $i \neq j+1$

and *FFx j X*
shows $\partial\partial\ i\ \alpha\ (\sigma\sigma\ j\ X) = \sigma\sigma\ j\ (\partial\partial\ i\ \alpha\ X)$
by (*smt* (*z3*) *assms image-cong image-image sym-face2-var1*)

lemma *sym-sym-braid-var1*:
assumes *diffSup i j 2*
shows $\sigma\ i\ (\sigma\ j\ (\partial\ i\ \alpha\ (\partial\ j\ \beta\ x))) = \sigma\ j\ (\sigma\ i\ (\partial\ i\ \alpha\ (\partial\ j\ \beta\ x)))$
using *assms local.face-comm-var local.sym-sym-braid* **by** *force*

lemma *sym-sym-braid-var2*:
assumes *diffSup i j 2*
shows $\sigma\ i \circ \sigma\ j \circ \partial\ i\ \alpha \circ \partial\ j\ \beta = \sigma\ j \circ \sigma\ i \circ \partial\ i\ \alpha \circ \partial\ j\ \beta$
using *assms sym-sym-braid-var1* **by** *fastforce*

lemma *sym-sym-braid-lift-var*:
assumes *diffSup i j 2*
shows $\sigma\sigma\ i\ (\sigma\sigma\ j\ (\partial\partial\ i\ \alpha\ (\partial\partial\ j\ \beta\ X))) = \sigma\sigma\ j\ (\sigma\sigma\ i\ (\partial\partial\ i\ \alpha\ (\partial\partial\ j\ \beta\ X)))$
proof−
have $\sigma\sigma\ i\ (\sigma\sigma\ j\ (\partial\partial\ i\ \alpha\ (\partial\partial\ j\ \beta\ X))) = \{\sigma\ i\ (\sigma\ j\ (\partial\ i\ \alpha\ (\partial\ j\ \beta\ x)))\ |x.\ x \in X\}$
by *blast*
also have $\ldots = \{\sigma\ j\ (\sigma\ i\ (\partial\ i\ \alpha\ (\partial\ j\ \beta\ x)))\ |x.\ x \in X\}$
by (*metis* (*full-types*, *opaque-lifting*) *assms sym-sym-braid-var1*)
finally show *?thesis*
by (*simp add*: *Setcompr-eq-image image-image*)
qed

lemma *sym-sym-braid-lift*:
assumes *diffSup i j 2*
and *FFx i X*
and *FFx j X*
shows $\sigma\sigma\ i\ (\sigma\sigma\ j\ X) = \sigma\sigma\ j\ (\sigma\sigma\ i\ X)$
by (*smt* (*verit*, *best*) *assms*(*1*,*2*,*3*) *comp-apply image-comp image-cong local.sym-sym-braid*)

lemma *sym-func2*:
assumes *fFx i x*
and *fFx i y*
and *DD* $(i + 1)\ x\ y$
shows $\sigma\ i\ (x \otimes_{(i+1)} y) = \sigma\ i\ x \otimes_i \sigma\ i\ y$
using *assms local.sym-func* **by** *simp*

lemma *sym-func3*:
assumes $i \neq j$
and $j \neq i + 1$
and *fFx i x*
and *fFx i y*
and *DD j x y*
shows $\sigma\ i\ (x \otimes_j y) = \sigma\ i\ x \otimes_j \sigma\ i\ y$
using *assms local.sym-func* **by** *simp*

lemma *sym-func2-var1*:
assumes $DD\ (i + 1)\ (\partial\ i\ \alpha\ x)\ (\partial\ i\ \beta\ y)$
shows $\sigma\ i\ (\partial\ i\ \alpha\ x \otimes_{(i+1)} \partial\ i\ \beta\ y) = \sigma\ i\ (\partial\ i\ \alpha\ x) \otimes_i \sigma\ i\ (\partial\ i\ \beta\ y)$
using *assms local.face-compat-var local.sym-func2* **by** *simp*

lemma *sym-func3-var1*:
assumes $i \neq j$
and $j \neq i + 1$
and $DD\ j\ (\partial\ i\ \alpha\ x)\ (\partial\ i\ \beta\ y)$
shows $\sigma\ i\ (\partial\ i\ \alpha\ x \otimes_j \partial\ i\ \beta\ y) = \sigma\ i\ (\partial\ i\ \alpha\ x) \otimes_j \sigma\ i\ (\partial\ i\ \beta\ y)$
using *assms local.face-compat-var local.sym-func3* **by** *simp*

lemma *sym-func2-DD*:
assumes *fFx i x*
and *fFx i y*
shows $DD\ (i + 1)\ x\ y = DD\ i\ (\sigma\ i\ x)\ (\sigma\ i\ y)$
by (*metis assms icat.st-local local.face-comm-var local.sym-face1 sym-fix-var1*)

lemma *func2-var2*: $\sigma\sigma\ i\ (\partial\ i\ \alpha\ x \odot_{(i+1)} \partial\ i\ \beta\ y) = \sigma\ i\ (\partial\ i\ \alpha\ x) \odot_i \sigma\ i\ (\partial\ i\ \beta\ y)$
proof (*cases* $DD\ (i + 1)\ (\partial\ i\ \alpha\ x)\ (\partial\ i\ \beta\ y)$)
case *True*
have $\sigma\sigma\ i\ (\partial\ i\ \alpha\ x \odot_{(i+1)} \partial\ i\ \beta\ y) = \sigma\sigma\ i\ \{\partial\ i\ \alpha\ x \otimes_{(i+1)} \partial\ i\ \beta\ y\}$
using *True local.icat.pcomp-def-var4* **by** *simp*
also have $\ldots = \{\sigma\ i\ (\partial\ i\ \alpha\ x \otimes_{(i+1)} \partial\ i\ \beta\ y)\}$
by *simp*
also have $\ldots = \{\sigma\ i\ (\partial\ i\ \alpha\ x) \otimes_i \sigma\ i\ (\partial\ i\ \beta\ y)\}$
using *True sym-func2-var1* **by** *simp*
also have $\ldots = \sigma\ i\ (\partial\ i\ \alpha\ x) \odot_i \sigma\ i\ (\partial\ i\ \beta\ y)$
using *True local.icat.pcomp-def-var4 sym-func2-DD* **by** *simp*
finally show *?thesis*.
next
case *False*
thus *?thesis*
using *local.sym-func2-DD* **by** *simp*
qed

lemma *sym-func2-lift-var1*: $\sigma\sigma\ i\ (\partial\partial\ i\ \alpha\ X \star_{(i+1)} \partial\partial\ i\ \beta\ Y) = \sigma\sigma\ i\ (\partial\partial\ i\ \alpha\ X) \star_i \sigma\sigma\ i\ (\partial\partial\ i\ \beta\ Y)$
proof−
have $\sigma\sigma\ i\ (\partial\partial\ i\ \alpha\ X \star_{(i+1)} \partial\partial\ i\ \beta\ Y) = \sigma\sigma\ i\ \{x \otimes_{(i+1)} y\ |x\ y.\ x \in \partial\partial\ i\ \alpha\ X \wedge y \in \partial\partial\ i\ \beta\ Y \wedge DD\ (i + 1)\ x\ y\}$
using *local.iconv-prop* **by** *presburger*
also have $\ldots = \{\sigma\ i\ (\partial\ i\ \alpha\ x \otimes_{(i+1)} \partial\ i\ \beta\ y)\ |x\ y.\ x \in X \wedge y \in Y \wedge DD\ (i + 1)\ (\partial\ i\ \alpha\ x)\ (\partial\ i\ \beta\ y)\}$
by *blast*
also have $\ldots = \{\sigma\ i\ (\partial\ i\ \alpha\ x) \otimes_i \sigma\ i\ (\partial\ i\ \beta\ y)\ |x\ y.\ x \in X \wedge y \in Y \wedge DD\ i\ (\sigma\ i\ (\partial\ i\ \alpha\ x))\ (\sigma\ i\ (\partial\ i\ \beta\ y))\}$

using *func2-var2 sym-func2-var1* **by** *fastforce*
also have $\ldots = \{x \otimes_i y \mid x\ y.\ x \in \sigma\sigma\ i\ (\partial\partial\ i\ \alpha\ X) \wedge y \in \sigma\sigma\ i\ (\partial\partial\ i\ \beta\ Y) \wedge DD\ i\ x\ y\}$
by *blast*
also have $\ldots = \sigma\sigma\ i\ (\partial\partial\ i\ \alpha\ X) \star_i \sigma\sigma\ i\ (\partial\partial\ i\ \beta\ Y)$
using *local.iconv-prop* **by** *presburger*
finally show *?thesis*.
qed

lemma *sym-func2-lift*:
assumes *FFx i X*
and *FFx i Y*
shows $\sigma\sigma\ i\ (X \star_{(i+1)} Y) = \sigma\sigma\ i\ X \star_i \sigma\sigma\ i\ Y$
proof−
have $\sigma\sigma\ i\ (X \star_{(i+1)} Y) = \sigma\sigma\ i\ (\partial\partial\ i\ tt\ X \star_{(i+1)} \partial\partial\ i\ tt\ Y)$
by (*smt* (*verit*) *assms image-cong image-ident local.icid.stopp.ST-compat*)
also have $\ldots = \sigma\sigma\ i\ (\partial\partial\ i\ tt\ X) \star_i \sigma\sigma\ i\ (\partial\partial\ i\ tt\ Y)$
using *sym-func2-lift-var1* **by** *simp*
also have $\ldots = \sigma\sigma\ i\ X \star_i \sigma\sigma\ i\ Y$
using *assms icid.st-eq1* **by** *simp*
finally show *?thesis*.
qed

lemma *func3-var1*:
assumes $i \neq j$
and $j \neq i + 1$
shows $\sigma\sigma\ i\ (\partial\ i\ \alpha\ x \odot_j \partial\ i\ \beta\ y) = \sigma\ i\ (\partial\ i\ \alpha\ x) \odot_j \sigma\ i\ (\partial\ i\ \beta\ y)$
proof (*cases DD j* $(\partial\ i\ \alpha\ x)$ $(\partial\ i\ \beta\ y)$)
case *True*
have $\sigma\sigma\ i\ (\partial\ i\ \alpha\ x \odot_j \partial\ i\ \beta\ y) = \sigma\sigma\ i\ \{\partial\ i\ \alpha\ x \otimes_j \partial\ i\ \beta\ y\}$
using *True local.icat.pcomp-def-var4* **by** *simp*
also have $\ldots = \{\sigma\ i\ (\partial\ i\ \alpha\ x \otimes_j \partial\ i\ \beta\ y)\}$
by *simp*
also have $\ldots = \{\sigma\ i\ (\partial\ i\ \alpha\ x) \otimes_j \sigma\ i\ (\partial\ i\ \beta\ y)\}$
using *True assms sym-func3-var1* **by** *simp*
also have $\ldots = \sigma\ i\ (\partial\ i\ \alpha\ x) \odot_j \sigma\ i\ (\partial\ i\ \beta\ y)$
using *True assms icat.st-local local.icat.pcomp-def-var4 sym-face2-var1* **by** *simp*
finally show *?thesis*.
next
case *False*
thus *?thesis*
by (*metis assms empty-is-image icat.st-local inv-sym-sym-var1 local.face-comm-var sym-face2-var1*)
qed

lemma *sym-func3-lift-var1*:
assumes $i \neq j$
and $j \neq i + 1$
shows $\sigma\sigma\ i\ (\partial\partial\ i\ \alpha\ X \star_j \partial\partial\ i\ \beta\ Y) = \sigma\sigma\ i\ (\partial\partial\ i\ \alpha\ X) \star_j \sigma\sigma\ i\ (\partial\partial\ i\ \beta\ Y)$

proof−
have $\sigma\sigma\ i\ (\partial\partial\ i\ \alpha\ X \star_j \partial\partial\ i\ \beta\ Y) = \sigma\sigma\ i\ \{x \otimes_j y\ |x\ y.\ x \in \partial\partial\ i\ \alpha\ X \wedge y \in \partial\partial\ i\ \beta\ Y \wedge DD\ j\ x\ y\}$
using *local.iconv-prop* **by** *presburger*
also have $\ldots = \{\sigma\ i\ (\partial\ i\ \alpha\ x \otimes_j \partial\ i\ \beta\ y)\ |x\ y.\ x \in X \wedge y \in Y \wedge DD\ j\ (\partial\ i\ \alpha\ x)\ (\partial\ i\ \beta\ y)\}$
by *force*
also have $\ldots = \{\sigma\ i\ (\partial\ i\ \alpha\ x) \otimes_j \sigma\ i\ (\partial\ i\ \beta\ y)\ |x\ y.\ x \in X \wedge y \in Y \wedge DD\ j\ (\sigma\ i\ (\partial\ i\ \alpha\ x))\ (\sigma\ i\ (\partial\ i\ \beta\ y))\}$
using *assms func3-var1 sym-func3-var1* **by** *fastforce*
also have $\ldots = \{x \otimes_j y\ |x\ y.\ x \in \sigma\sigma\ i\ (\partial\partial\ i\ \alpha\ X) \wedge y \in \sigma\sigma\ i\ (\partial\partial\ i\ \beta\ Y) \wedge DD\ j\ x\ y\}$
by *force*
also have $\ldots = \sigma\sigma\ i\ (\partial\partial\ i\ \alpha\ X) \star_j \sigma\sigma\ i\ (\partial\partial\ i\ \beta\ Y)$
using *local.iconv-prop* **by** *presburger*
finally show *?thesis*.
qed

lemma *sym-func3-lift*:
assumes $i \neq j$
and $j \neq i + 1$
and *FFx i X*
and *FFx i Y*
shows $\sigma\sigma\ i\ (X \star_j Y) = \sigma\sigma\ i\ X \star_j \sigma\sigma\ i\ Y$
proof−
have $\sigma\sigma\ i\ (X \star_j Y) = \sigma\sigma\ i\ (\partial\partial\ i\ tt\ X \star_j \partial\partial\ i\ tt\ Y)$
by (*smt* (*verit*) *assms*(*3*) *assms*(*4*) *image-cong image-ident local.icid.stopp.ST-compat*)
also have $\ldots = \sigma\sigma\ i\ (\partial\partial\ i\ tt\ X) \star_j \sigma\sigma\ i\ (\partial\partial\ i\ tt\ Y)$
using *assms*(*1*) *assms*(*2*) *sym-func3-lift-var1* **by** *presburger*
also have $\ldots = \sigma\sigma\ i\ X \star_j \sigma\sigma\ i\ Y$
using *assms*(*3*) *assms*(*4*) *icid.st-eq1* **by** *simp*
finally show *?thesis*.
qed

lemma *sym-func3-var2*: $i \neq j \Longrightarrow \sigma\sigma\ i\ (\partial\ i\ \alpha\ x \odot_j \partial\ i\ \beta\ y) = (\textit{if } j = i + 1 \textit{ then } \sigma\ i\ (\partial\ i\ \alpha\ x) \odot_i \sigma\ i\ (\partial\ i\ \beta\ y) \textit{ else } \sigma\ i\ (\partial\ i\ \alpha\ x) \odot_j \sigma\ i\ (\partial\ i\ \beta\ y))$
using *func2-var2 func3-var1* **by** *simp*

Symmetries and inverse symmetries form a bijective pair on suitable fixpoints of the face maps.

lemma *sym-inj*: *inj-on* $(\sigma\ i)$ (*face-fix i*)
by (*smt* (*verit*, *del-insts*) *CollectD inj-onI local.inv-sym-sym*)

lemma *sym-inj-var*:
assumes *fFx i x*
and *fFx i y*
and $\sigma\ i\ x = \sigma\ i\ y$
shows $x = y$
by (*metis assms inv-sym-sym-var1*)

lemma *inv-sym-inj*: *inj-on* (ϑ *i*) (*face-fix* (*i* + *1*))
by (*smt* (*verit*, *del-insts*) *CollectD inj-onI local.sym-inv-sym*)

lemma *inv-sym-inj-var*:
assumes *fFx* (*i* + *1*) *x*
and *fFx* (*i* + *1*) *y*
and ϑ *i x* = ϑ *i y*
shows *x* = *y*
by (*metis assms local.sym-inv-sym*)

lemma *surj-sym*: *image* (σ *i*) (*face-fix i*) = *face-fix* (*i* + *1*)
by (*safe*, *metis sym-type-var1*, *smt* (*verit*, *del-insts*) *imageI inv-sym-type-var1 mem-Collect-eq sym-inv-sym-var1*)

lemma *surj-inv-sym*: *image* (ϑ *i*) (*face-fix* (*i* + *1*)) = *face-fix i*
by (*safe*, *metis inv-sym-type-var1*, *smt* (*verit*, *del-insts*) *imageI inv-sym-sym-var1 mem-Collect-eq sym-type-var1*)

lemma *sym-adj*:
assumes *fFx i x*
and *fFx* (*i* + *1*) *y*
shows (σ *i x* = *y*) = (*x* = ϑ *i y*)
using *assms local.inv-sym-sym local.sym-inv-sym* **by** *force*

Next we list properties for inverse symmetries corresponding to the axioms.

lemma *inv-sym*:
assumes *fFx i x*
and *fFx* (*i* + *1*) *x*
shows ϑ *i x* = *x*
proof−
have *x* = σ *i x*
using *assms local.sym-fix* **by** *simp*
thus *?thesis*
using *assms sym-adj* **by** *force*
qed

lemma *inv-sym-face2*:
assumes *i* ≠ *j*
and *i* ≠ *j* + *1*
and *fFx* (*j* + *1*) *x*
shows ∂ *i* α (ϑ *j x*) = ϑ *j* (∂ *i* α *x*)
proof−
have σ *j* (∂ *i* α (ϑ *j x*)) = σ *j* (∂ *i* α (∂ *j ff* (ϑ *j x*)))
using *assms*(*3*) *inv-sym-type-var* **by** *simp*
also have ... = ∂ *i* α (σ *j* (∂ *j* α (ϑ *j x*)))
by (*metis assms inv-sym-type-var local.fFx-prop sym-face2-var1*)
also have ... = ∂ *i* α (σ *j* (ϑ *j x*))
using *assms calculation inv-sym-type-var local.sym-face2* **by** *presburger*

also have $\ldots = \partial\ i\ \alpha\ (\partial\ (j + 1)\ \alpha\ x)$
by (*metis assms*(*3*) *local.face-compat-var sym-inv-sym-var1*)
finally have $\sigma\ j\ (\partial\ i\ \alpha\ (\vartheta\ j\ x)) = \partial\ i\ \alpha\ (\partial\ (j + 1)\ \alpha\ x)$**.**
thus *?thesis*
by (*metis assms*(*3*) *inv-sym-type-var local.fFx-prop local.face-comm-var local.inv-sym-sym*)
qed

lemma *sym-braid*:
assumes *fFx i x*
and *fFx* $(i + 1)$ *x*
shows $\sigma\ i\ (\sigma\ (i + 1)\ (\sigma\ i\ x)) = \sigma\ (i + 1)\ (\sigma\ i\ (\sigma\ (i + 1)\ x))$
using *assms local.sym-face2 local.sym-fix sym-type-var* **by** *simp*

lemma *inv-sym-braid*:
assumes *fFx* $(i + 1)$ *x*
and *fFx* $(i + 2)$ *x*
shows $\vartheta\ i\ (\vartheta\ (i + 1)\ (\vartheta\ i\ x)) = \vartheta\ (i + 1)\ (\vartheta\ i\ (\vartheta\ (i + 1)\ x))$
using *assms inv-sym inv-sym-face2 inv-sym-type-var* **by** *simp*

lemma *sym-inv-sym-braid*:
assumes *diffSup i j 2*
and *fFx* $(j + 1)$ *x*
and *fFx i x*
shows $\sigma\ i\ (\vartheta\ j\ x) = \vartheta\ j\ (\sigma\ i\ x)$
by (*metis* (*no-types*, *lifting*) *ext assms*(*1*,*2*,*3*) *diff-add-0 diff-add-inverse inv-sym-face2 inv-sym-type-var local.inv-sym-sym local.sym-face2 local.sym-inv-sym not-numeral-le-zero numeral-le-one-iff semiring-norm*(*69*) *sym-sym-braid-var1*)

lemma *sym-func1*:
assumes *fFx i x*
and *fFx i y*
and *DD i x y*
shows $\sigma\ i\ (x \otimes_i y) = \sigma\ i\ x \otimes_{(i + 1)} \sigma\ i\ y$
by (*metis assms icid.ts-compat local.iDst local.icat.sscatml.l0-absorb sym-type-var1*)

lemma *sym-func1-var1*: $\sigma\sigma\ i\ (\partial\ i\ \alpha\ x \odot_i \partial\ i\ \beta\ y) = \sigma\ i\ (\partial\ i\ \alpha\ x) \odot_{(i + 1)} \sigma\ i\ (\partial\ i\ \beta\ y)$
by (*metis icid.t-idem image-empty image-insert inv-sym-sym-var1 local.face-compat-var local.icid.stopp.Dst sym-type-var1*)

lemma *inv-sym-func2-var1*: $\vartheta\vartheta\ i\ (\partial\ (i + 1)\ \alpha\ x \odot_i \partial\ (i + 1)\ \beta\ y) = \vartheta\ i\ (\partial\ (i + 1)\ \alpha\ x) \odot_{(i + 1)} \vartheta\ i\ (\partial\ (i + 1)\ \beta\ y)$
proof−
have $\sigma\sigma\ i\ (\vartheta\ i\ (\partial\ (i + 1)\ \alpha\ x) \odot_{(i + 1)} \vartheta\ i\ (\partial\ (i + 1)\ \beta\ y)) = \partial\ (i + 1)\ \alpha\ x \odot_i \partial\ (i + 1)\ \beta\ y$
by (*metis func2-var2 inv-sym-type-var1 sym-inv-sym-var1*)
hence $\sigma\sigma\ i\ (\partial\partial\ i\ ff\ (\vartheta\ i\ (\partial\ (i + 1)\ \alpha\ x) \odot_{(i + 1)} \vartheta\ i\ (\partial\ (i + 1)\ \beta\ y))) = \partial\partial$

$(i + 1)$ *ff* $(\partial\ (i + 1)\ \alpha\ x \odot_i \partial\ (i + 1)\ \beta\ y)$
by (*smt* (*verit*) *diff-add-0 diff-add-inverse inv-sym-type-var1 local.face-fix-comp-var local.icid.stopp.ts-compat numerals*(1) *zero-neq-numeral*)
hence *∂∂ i ff* $(\vartheta\ i\ (\partial\ (i + 1)\ \alpha\ x) \odot_{(i + 1)} \vartheta\ i\ (\partial\ (i + 1)\ \beta\ y)) = \vartheta\vartheta\ i\ (\partial\partial\ (i + 1)$ *ff* $(\partial\ (i + 1)\ \alpha\ x \odot_i \partial\ (i + 1)\ \beta\ y))$
by (*metis inv-sym-sym-lift-var*)
thus *?thesis*
by (*metis add-cancel-right-right dual-order.eq-iff inv-sym-type-var1 local.face-compat-var local.face-fix-comp-var not-one-le-zero*)
qed

lemma *inv-sym-func3-var1*: $\vartheta\vartheta\ i\ ((\partial\ (i + 1)\ \alpha\ x) \odot_{(i + 1)} (\partial\ (i + 1)\ \beta\ y)) = \vartheta\ i\ (\partial\ (i + 1)\ \alpha\ x) \odot_i \vartheta\ i\ (\partial\ (i + 1)\ \beta\ y)$
by (*smt* (*z3*) *empty-is-image image-insert inv-sym-type-var1 local.face-idem1 local.face-pidem2 sym-inv-sym-var1*)

lemma *inv-sym-func-var1*:
assumes $i \neq j$
and $j \neq i + 1$
shows $\vartheta\vartheta\ i\ ((\partial\ (i + 1)\ \alpha\ x) \odot_j (\partial\ (i + 1)\ \beta\ y)) = \vartheta\ i\ (\partial\ (i + 1)\ \alpha\ x) \odot_j \vartheta\ i\ (\partial\ (i + 1)\ \beta\ y)$
by (*smt* (*z3*) *assms*(1) *assms*(2) *inv-sym-sym-lift-var inv-sym-type-var1 local.face-fix-comp-var local.icid.stopp.ts-compat sym-func3-var2 sym-inv-sym-var1*)

lemma *inv-sym-func2*:
assumes *fFx* $(i + 1)\ x$
and *fFx* $(i + 1)\ y$
and *DD i x y*
shows $\vartheta\ i\ (x \otimes_i y) = \vartheta\ i\ x \otimes_{(i + 1)} \vartheta\ i\ y$
proof−
have $\{\vartheta\ i\ (x \otimes_i y)\} = \vartheta\vartheta\ i\ (x \odot_i y)$
using *assms*(3) *local.icat.pcomp-def-var4* **by** *fastforce*
also have $\ldots = \vartheta\ i\ x \odot_{(i + 1)} \vartheta\ i\ y$
by (*metis assms*(1) *assms*(2) *inv-sym-func2-var1*)
also have $\ldots = \{\vartheta\ i\ x \otimes_{(i + 1)} \vartheta\ i\ y\}$
by (*metis calculation insert-not-empty local.icat.pcomp-def-var4*)
finally show *?thesis*
by *simp*
qed

lemma *inv-sym-func3*:
assumes *fFx* $(i + 1)\ x$
and *fFx* $(i + 1)\ y$
and *DD* $(i + 1)\ x\ y$
shows $\vartheta\ i\ (x \otimes_{(i + 1)} y) = \vartheta\ i\ x \otimes_i \vartheta\ i\ y$
by (*metis assms icat.st-local icid.st-fix inv-sym-type-var1 local.icat.sscatml.l0-absorb*)

lemma *inv-sym-func*:

assumes $i \neq j$
and $j \neq i + 1$
and *fFx* $(i + 1)$ x
and *fFx* $(i + 1)$ y
and *DD* j x y
shows $\vartheta\ i\ (x \otimes_j y) = \vartheta\ i\ x \otimes_j \vartheta\ i\ y$
proof−
have $\{\vartheta\ i\ (x \otimes_j y)\} = \vartheta\vartheta\ i\ (x \odot_j y)$
using *assms*(5) *local.icat.pcomp-def-var4* **by** *fastforce*
also have $\ldots = \vartheta\ i\ x \odot_j \vartheta\ i\ y$
by (*metis assms*(1) *assms*(2) *assms*(3) *assms*(4) *inv-sym-func-var1*)
also have $\ldots = \{\vartheta\ i\ x \otimes_j \vartheta\ i\ y\}$
by (*metis calculation insert-not-empty local.icat.pcomp-def-var4*)
finally show *?thesis*
by *simp*
qed

The following properties are related to faces and braids.

lemma *sym-face3*:
assumes *fFx* i x
shows $\partial\ (i + 1)\ \alpha\ (\sigma\ i\ x) = \sigma\ i\ (\partial\ i\ \alpha\ x)$
by (*metis assms local.fFx-prop sym-type-var1*)

lemma *sym-face3-var1*: $\partial\ (i + 1)\ \alpha\ (\sigma\ i\ (\partial\ i\ \beta\ x)) = \sigma\ i\ (\partial\ i\ \alpha\ (\partial\ i\ \beta\ x))$
proof−
have $\partial\ (i + 1)\ \alpha\ (\sigma\ i\ (\partial\ i\ \beta\ x)) = \partial\ (i + 1)\ \alpha\ (\sigma\ i\ (\partial\ i\ \alpha\ (\partial\ i\ \beta\ x)))$
by *simp*
also have $\ldots = \sigma\ i\ (\partial\ i\ \alpha\ (\partial\ i\ \beta\ x))$
using *local.sym-type-var1* **by** *fastforce*
also have $\ldots = \sigma\ i\ (\partial\ i\ \beta\ x)$
by *simp*
thus *?thesis*
using *calculation* **by** *simp*
qed

lemma *sym-face3-simp* [*simp*]:
assumes *fFx* i x
shows $\partial\ (i + 1)\ \alpha\ (\sigma\ i\ x) = \sigma\ i\ x$
by (*metis assms local.fFx-prop sym-face3*)

lemma *sym-face3-simp-var1* [*simp*]: $\partial\ (i + 1)\ \alpha\ (\sigma\ i\ (\partial\ i\ \beta\ x)) = \sigma\ i\ (\partial\ i\ \beta\ x)$
using *sym-face3* **by** *simp*

lemma *inv-sym-face3*:
assumes *fFx* $(i + 1)$ x
shows $\partial\ i\ \alpha\ (\vartheta\ i\ x) = \vartheta\ i\ (\partial\ (i + 1)\ \alpha\ x)$
by (*metis assms inv-sym-type-var1 local.face-compat-var*)

lemma *inv-sym-face3-var1*: $\partial\ i\ \alpha\ (\vartheta\ i\ (\partial\ (i + 1)\ \beta\ x)) = \vartheta\ i\ (\partial\ (i + 1)\ \alpha\ (\partial\ (i$

$+ 1)\ \beta\ x))$
by (*metis inv-sym-type-var1 local.face-compat-var*)

lemma *inv-sym-face3-simp*:
assumes *fFx* $(i + 1)\ x$
shows $\partial\ i\ \alpha\ (\vartheta\ i\ x) = \vartheta\ i\ x$
using *assms inv-sym-type-var local.fFx-prop* **by** *force*

lemma *inv-sym-face3-simp-var1* [*simp*]: $\partial\ i\ \alpha\ (\vartheta\ i\ (\partial\ (i + 1)\ \beta\ x)) = \vartheta\ i\ (\partial\ (i + 1)\ \beta\ x)$
using *inv-sym-face3 local.face-compat-var* **by** *simp*

lemma *inv-sym-face1*:
assumes *fFx* $(i + 1)\ x$
shows $\partial\ (i + 1)\ \alpha\ (\vartheta\ i\ x) = \vartheta\ i\ (\partial\ i\ \alpha\ x)$
by (*metis assms inv-sym-face3-simp inv-sym-sym-var1 local.face-comm-var local.sym-inv-sym sym-face1-var1*)

lemma *inv-sym-face1-var1*: $\partial\ (i + 1)\ \alpha\ (\vartheta\ i\ (\partial\ (i + 1)\ \beta\ x)) = \vartheta\ i\ (\partial\ i\ \alpha\ (\partial\ (i + 1)\ \beta\ x))$
using *inv-sym-face1 local.face-compat-var* **by** *simp*

lemma *inv-sym-sym-braid*:
assumes *diffSup i j 2*
and *fFx j x*
and *fFx* $(i + 1)\ x$
shows $\vartheta\ i\ (\sigma\ j\ x) = \sigma\ j\ (\vartheta\ i\ x)$
using *assms sym-inv-sym-braid* **by** *force*

lemma *inv-sym-sym-braid-var1*: *diffSup i j 2* $\Longrightarrow \vartheta\ i\ (\sigma\ j\ (\partial\ (i + 1)\ \alpha\ (\partial\ j\ \beta\ x))) = \sigma\ j\ (\vartheta\ i\ (\partial\ (i + 1)\ \alpha\ (\partial\ j\ \beta\ x)))$
using *local.face-comm-var local.sym-inv-sym-braid* **by** *force*

lemma *inv-sym-inv-sym-braid*:
assumes *diffSup i j 2*
and *fFx* $(i + 1)\ x$
and *fFx* $(j + 1)\ x$
shows $\vartheta\ i\ (\vartheta\ j\ x) = \vartheta\ j\ (\vartheta\ i\ x)$
by (*metis Suc-eq-plus1 add-right-cancel assms inv-sym-face2 inv-sym-face3 inv-sym-sym-braid-var1 local.inv-sym-sym local.sym-inv-sym nat-le-linear not-less-eq-eq*)

lemma *inv-sym-inv-sym-braid-var1*: *diffSup i j 2* $\Longrightarrow \vartheta\ i\ (\vartheta\ j\ (\partial\ (i + 1)\ \alpha\ (\partial\ (j + 1)\ \beta\ x))) = \vartheta\ j\ (\vartheta\ i\ (\partial\ (i + 1)\ \alpha\ (\partial\ (j + 1)\ \beta\ x)))$
using *inv-sym-inv-sym-braid local.face-comm-var* **by** *force*

The following properties are related to symcomp and inv-symcomp.

lemma *symcomp-type-var*:
assumes *fFx i x*
shows *fFx* $(i + j)\ (\Sigma\ i\ j\ x)$ **using** ‹*fFx i x*›

apply (*induct j*)
using *sym-face3* **by** *simp-all*

lemma *symcomp-type*: *image* (Σ *i j*) (*face-fix i*) $\subseteq$ *face-fix* (*i* + *j*)
using *symcomp-type-var* **by** *force*

lemma *symcomp-type-var1* [*simp*]: ∂ (*i* + *j*) α (Σ *i j* (∂ *i* β *x*)) = Σ *i j* (∂ *i* β *x*)
by (*metis local.face-compat-var symcomp-type-var*)

lemma *inv-symcomp-type-var*:
assumes *fFx* (*i* + *j*) *x*
shows *fFx i* (Θ *i j x*) **using** ‹*fFx* (*i* + *j*) *x*›
by (*induct j arbitrary*: *x*, *simp-all add*: *inv-sym-type-var*)

lemma *inv-symcomp-type*: *image* (Θ *i j*) (*face-fix* (*i* + *j*)) $\subseteq$ *face-fix i*
using *inv-symcomp-type-var* **by** *force*

lemma *inv-symcomp-type-var1* [*simp*]: ∂ *i* α (Θ *i j* (∂ (*i* + *j*) β *x*)) = Θ *i j* (∂ (*i* + *j*) β *x*)
by (*meson inv-symcomp-type-var local.fFx-prop local.face-compat-var*)

lemma *symcomp-inv-symcomp*:
assumes *fFx* (*i* + *j*) *x*
shows Σ *i j* (Θ *i j x*) = *x* **using** ‹*fFx* (*i* + *j*) *x*›
by (*induct j arbitrary*: *i x*, *simp-all add*: *inv-sym-type-var local.sym-inv-sym*)

lemma *inv-symcomp-symcomp*:
assumes *fFx i x*
shows Θ *i j* (Σ *i j x*) = *x* **using** ‹*fFx i x*›
by (*induct j arbitrary*: *i x*, *simp-all add*: *local.inv-sym-sym symcomp-type-var*)

lemma *symcomp-adj*:
assumes *fFx i x*
and *fFx* (*i* + *j*) *y*
shows (Σ *i j x* = *y*) = (*x* = Θ *i j y*)
using *assms inv-symcomp-symcomp symcomp-inv-symcomp* **by** *force*

lemma *decomp-symcomp1*:
assumes *k* $\leq$ *j*
and *fFx i x*
shows Σ *i j x* = Σ (*i* + *k*) (*j* − *k*) (Σ *i k x*) **using** ‹*k* $\leq$ *j*›
apply (*induct j*)
using *Suc-diff-le le-Suc-eq* **by** *force*+

lemma *decomp-symcomp2*:
assumes *1* $\leq$ *k*
and *k* $\leq$ *j*
and *fFx i x*
shows Σ *i j x* = Σ (*i* + *k*) (*j* − *k*) (σ (*i* + *k* − *1*) (Σ *i* (*k* − *1*) *x*))

by (*metis Nat.add-diff-assoc add-diff-cancel-left′ assms decomp-symcomp1 local.symcomp.simps*(*2*) *plus-1-eq-Suc*)

lemma *decomp-symcomp3*:
assumes $i \leq l$
and $l + 1 \leq i + j$
and *fFx i x*
shows $\Sigma\ i\ j\ x = \Sigma\ (l + 1)\ (i + j - l - 1)\ (\sigma\ l\ (\Sigma\ i\ (l - i)\ x))$
by (*smt* (*verit*, *del-insts*) *add.commute add-le-cancel-left assms decomp-symcomp2 diff-add-inverse2 diff-diff-left le-add1 le-add-diff-inverse*)

lemma *symcomp-face2*:
assumes $l < i \vee i + j < l$
and *fFx i x*
shows $\partial\ l\ \alpha\ (\Sigma\ i\ j\ x) = \Sigma\ i\ j\ (\partial\ l\ \alpha\ x)$ **using** ‹$l < i \vee i + j < l$›
proof (*induct j*)
case *0*
show *?case*
by *simp*
next
case (*Suc j*)
have $\partial\ l\ \alpha\ (\Sigma\ i\ (Suc\ j)\ x) = \partial\ l\ \alpha\ (\sigma\ (i + j)\ (\Sigma\ i\ j\ x))$
by *simp*
also have $\ldots = \sigma\ (i + j)\ (\partial\ l\ \alpha\ (\Sigma\ i\ j\ x))$
using *Suc.prems add.commute assms*(*2*) *local.sym-face2 symcomp-type-var* **by** *auto*
also have $\ldots = \sigma\ (i + j)\ (\Sigma\ i\ j\ (\partial\ l\ \alpha\ x))$
using *Suc.hyps Suc.prems* **by** *fastforce*
also have $\ldots = (\Sigma\ i\ (Suc\ j)\ (\partial\ l\ \alpha\ x))$
by *simp*
finally show *?case*.
qed

lemma *symcomp-face3*: *fFx i x* $\Longrightarrow \partial\ (i + j)\ \alpha\ (\Sigma\ i\ j\ x) = \Sigma\ i\ j\ (\partial\ i\ \alpha\ x)$
by (*metis local.face-compat-var symcomp-type-var1*)

lemma *symcomp-face1*:
assumes $i \leq l$
and $l < i + j$
and *fFx i x*
shows $\partial\ l\ \alpha\ (\Sigma\ i\ j\ x) = \Sigma\ i\ j\ (\partial\ (l + 1)\ \alpha\ x)$
proof−
have $\partial\ l\ \alpha\ (\Sigma\ i\ j\ x) = \partial\ l\ \alpha\ (\Sigma\ (l + 1)\ (i + j - l - 1)\ (\sigma\ l\ (\Sigma\ i\ (l - i)\ x)))$
using *Suc-eq-plus1 Suc-leI assms*(*1*) *assms*(*2*) *assms*(*3*) *decomp-symcomp3* **by** *presburger*
also have $\ldots = \Sigma\ (l + 1)\ (i + j - l - 1)\ (\partial\ l\ \alpha\ (\sigma\ l\ (\Sigma\ i\ (l - i)\ x)))$
by (*metis assms*(*1*) *assms*(*3*) *less-add-one ordered-cancel-comm-monoid-diff-class.add-diff-inverse sym-type-var symcomp-face2 symcomp-face3*)
also have $\ldots = \Sigma\ (l + 1)\ (i + j - l - 1)\ (\sigma\ l\ (\partial\ (l + 1)\ \alpha\ (\Sigma\ i\ (l - i)\ x)))$

by (*metis assms*(*1*) *assms*(*3*) *local.sym-face1 ordered-cancel-comm-monoid-diff-class.add-diff-inverse symcomp-face3*)
also have $\ldots = \Sigma\ (l + 1)\ (i + j - l - 1)\ (\sigma\ l\ (\Sigma\ i\ (l - i)\ (\partial\ (l + 1)\ \alpha\ x)))$
by (*simp add*: *assms*(*1*) *assms*(*3*) *symcomp-face2*)
also have $\ldots = \Sigma\ i\ j\ (\partial\ (l + 1)\ \alpha\ x)$
by (*metis Suc-eq-plus1 Suc-leI assms*(*1*) *assms*(*2*) *assms*(*3*) *decomp-symcomp3 local.fFx-prop local.face-comm-var*)
finally show *?thesis*.
qed

lemma *inv-symcomp-face2*:
assumes $l < i \vee i + j < l$
and *fFx* $(i + j)\ x$
shows $\partial\ l\ \alpha\ (\Theta\ i\ j\ x) = \Theta\ i\ j\ (\partial\ l\ \alpha\ x)$ **using** ‹$l < i \vee i + j < l$› ‹*fFx* $(i + j)$ x›
proof (*induct j arbitrary*: x)
case *0*
show *?case*
using *local.inv-sym-face2* **by** *force*
next
case (*Suc j*)
have $\partial\ l\ \alpha\ (\Theta\ i\ (Suc\ j)\ x) = \Theta\ i\ j\ (\partial\ l\ \alpha\ (\vartheta\ (i + j)\ x))$
using *Suc.hyps Suc.prems*(*1*) *Suc.prems*(*2*) *inv-sym-type-var* **by** *force*
also have $\ldots = \Theta\ i\ j\ (\vartheta\ (i + j)\ (\partial\ l\ \alpha\ x))$
using *Suc.prems inv-sym-face2* **by** *force*
also have $\ldots = (\Theta\ i\ (Suc\ j)\ (\partial\ l\ \alpha\ x))$
by *simp*
finally show *?case*.
qed

lemma *inv-symcomp-face3*: *fFx* $(i + j)\ x \Longrightarrow \partial\ i\ \alpha\ (\Theta\ i\ j\ x) = \Theta\ i\ j\ (\partial\ (i + j)\ \alpha\ x)$
by (*metis inv-symcomp-type-var1 local.face-compat-var*)

lemma *inv-symcomp-face1*:
assumes $i < l$
and $l \leq i + j$
and *fFx* $(i + j)\ x$
shows $\partial\ l\ \alpha\ (\Theta\ i\ j\ x) = \Theta\ i\ j\ (\partial\ (l - 1)\ \alpha\ x)$
proof−
have $(\partial\ (l - 1)\ \alpha\ (\Sigma\ i\ j\ (\Theta\ i\ j\ x)) = \partial\ (l - 1)\ \alpha\ x)$
using *assms*(*3*) *symcomp-inv-symcomp* **by** *force*
hence $(\Sigma\ i\ j\ (\partial\ l\ \alpha\ (\Theta\ i\ j\ x)) = \partial\ (l - 1)\ \alpha\ x)$
using *assms inv-symcomp-type-var symcomp-face1* **by** *auto*
thus *?thesis*
by (*metis assms*(*1*) *assms*(*3*) *inv-symcomp-symcomp inv-symcomp-type-var local.face-comm-var nat-neq-iff*)
qed

lemma *symcomp-comp1*:
assumes *fFx i x*
and *fFx i y*
and *DD i x y*
shows $\Sigma\ i\ j\ (x \otimes_i y) = \Sigma\ i\ j\ x \otimes_{(i+j)} \Sigma\ i\ j\ y$
by (*induct j*, *simp*, *metis assms local.face-compat-var local.iDst local.icat.sscatml.r0-absorb symcomp-type-var1*)

lemma *symcomp-comp2*:
assumes $k < i$
and *fFx i x*
and *fFx i y*
and *DD k x y*
shows $\Sigma\ i\ j\ (x \otimes_k y) = \Sigma\ i\ j\ x \otimes_k \Sigma\ i\ j\ y$
proof (*induct j*)
case *0*
show *?case*
by *simp*
next
case (*Suc j*)
have $\Sigma\ i\ (Suc\ j)\ (x \otimes_k y) = \sigma\ (i+j)\ ((\Sigma\ i\ j\ x) \otimes_k (\Sigma\ i\ j\ y))$
by (*simp add*: *Suc*)
also have $\ldots = \sigma\ (i+j)\ (\Sigma\ i\ j\ x) \otimes_k \sigma\ (i+j)\ (\Sigma\ i\ j\ y)$
apply (*rule sym-func3*)
using *assms(1) assms(2) assms(3) symcomp-type-var* **apply** *presburger+*
using *assms local.iDst local.locality symcomp-face2* **by** *presburger*
finally show *?case*
by *simp*
qed

lemma *symcomp-comp3*:
assumes $i + j < k$
and *fFx i x*
and *fFx i y*
and *DD k x y*
shows $\Sigma\ i\ j\ (x \otimes_k y) = \Sigma\ i\ j\ x \otimes_k \Sigma\ i\ j\ y$ **using** $\langle k > i + j \rangle$
proof (*induct j*)
case *0*
show *?case*
by *simp*
next
case (*Suc j*)
have $\Sigma\ i\ (Suc\ j)\ (x \otimes_k y) = \sigma\ (i+j)\ ((\Sigma\ i\ j\ x) \otimes_k (\Sigma\ i\ j\ y))$
using *Suc.hyps Suc.prems* **by** *force*
also have $\ldots = \sigma\ (i+j)\ (\Sigma\ i\ j\ x) \otimes_k \sigma\ (i+j)\ (\Sigma\ i\ j\ y)$
apply (*rule sym-func3*)
using *Suc.prems* **apply** *linarith+*
using *assms(2) assms(3) symcomp-type-var* **apply** *presburger+*
using *Suc.prems assms(2) assms(3) assms(4) local.icid.ts-msg.st-locality-locality*

symcomp-face2 **by** *simp*
finally show *?case*
by *simp*
qed

lemma *fix-comp*:
assumes $i \neq j$
and *fFx i x*
and *fFx i y*
and *DD j x y*
shows *fFx i* $(x \otimes_j y)$
using *face-func assms* **by** *simp*

lemma *symcomp-comp4*:
assumes $i < k$
and $k \leq i + j$
and *fFx i x*
and *fFx i y*
and *DD k x y*
shows $\Sigma\ i\ j\ (x \otimes_k y) = \Sigma\ i\ j\ x \otimes_{(k\ -\ 1)} \Sigma\ i\ j\ y$
using ‹$k \leq i + j$› ‹*fFx i x*› ‹*fFx i y*› ‹*DD k x y*›
proof (*induct j arbitrary*: *x y*)
case *0*
thus *?case*
using *assms*(*1*) **by** *linarith*
next
case (*Suc j*)
have *a*: *fFx i* $(x \otimes_k y)$
using *Suc.prems*(*2*) *Suc.prems*(*3*) *Suc.prems*(*4*) *assms*(*1*) *fix-comp* **by** *force*
have *b*: *fFx* $(k\ -\ 1)$ $(\Sigma\ i\ (k\ -\ 1\ -\ i)\ x)$
using *Suc.prems*(*2*) *assms*(*1*) *less-imp-Suc-add symcomp-type-var* **by** *fastforce*
have *c*: *fFx* $(k\ -\ 1)$ $(\Sigma\ i\ (k\ -\ 1\ -\ i)\ y)$
using *Suc.prems*(*3*) *assms*(*1*) *less-imp-Suc-add symcomp-type-var* **by** *fastforce*
have *d*: *DD k* $(\Sigma\ i\ (k\ -\ 1\ -\ i)\ x)$ $(\Sigma\ i\ (k\ -\ 1\ -\ i)\ y)$
by (*metis Suc.prems*(*2*) *Suc.prems*(*3*) *Suc.prems*(*4*) *add-diff-cancel-left' assms*(*1*) *lessI less-imp-Suc-add local.iDst local.locality plus-1-eq-Suc symcomp-face2*)
have $\Sigma\ i\ (Suc\ j)\ (x \otimes_k y) = \Sigma\ k\ (i + j + 1 - k)\ (\sigma\ (k\ -\ 1)\ (\Sigma\ i\ (k\ -\ 1\ -\ i)\ (x \otimes_k y)))$
by (*smt* (*verit*) *Suc.prems*(*1*) *Suc-eq-plus1 a add-Suc-right add-le-imp-le-diff assms*(*1*) *decomp-symcomp3 diff-diff-left le-add-diff-inverse2 less-eq-Suc-le plus-1-eq-Suc*)
also have $\ldots = \Sigma\ k\ (i + j + 1 - k)\ (\sigma\ (k\ -\ 1)\ (\Sigma\ i\ (k\ -\ 1\ -\ i)\ x \otimes_k \Sigma\ i\ (k\ -\ 1\ -\ i)\ y))$
using *Suc.prems*(*2*) *Suc.prems*(*3*) *Suc.prems*(*4*) *assms*(*1*) *symcomp-comp3* **by** *force*
also have $\ldots = \Sigma\ k\ (i + j + 1 - k)\ (\sigma\ (k\ -\ 1)\ (\Sigma\ i\ (k\ -\ 1\ -\ i)\ x \otimes_{((k\ -\ 1)\ +\ 1)} \Sigma\ i\ (k\ -\ 1\ -\ i)\ y))$
using *assms*(*1*) **by** *auto*
also have $\ldots = \Sigma\ k\ (i + j + 1 - k)\ (\sigma\ (k\ -\ 1)\ (\Sigma\ i\ (k\ -\ 1\ -\ i)\ x) \otimes_{(k\ -\ 1)} \sigma\ (k\ -\ 1)\ (\Sigma\ i\ (k\ -\ 1\ -\ i)\ y))$

using *assms(1) b c d less-iff-Suc-add sym-func2* **by** *fastforce*
also have $\ldots = \Sigma\ k\ (i + j + 1 - k)\ (\sigma\ (k - 1)\ (\Sigma\ i\ (k - 1 - i)\ x)) \otimes_{(k - 1)} \Sigma\ k\ (i + j + 1 - k)\ (\sigma\ (k - 1)\ (\Sigma\ i\ (k - 1 - i)\ y))$
apply (*rule symcomp-comp2*)
using *assms(1) b sym-face3* **apply** *fastforce+*
apply (*metis assms(1) c le-add1 le-add-diff-inverse2 less-imp-Suc-add plus-1-eq-Suc sym-face3*)
by (*metis assms(1) b c d le-add1 le-add-diff-inverse2 less-imp-Suc-add plus-1-eq-Suc sym-func2-DD*)
also have $\ldots = \Sigma\ k\ (i + j + 1 - k)\ (\Sigma\ i\ (k - i)\ x) \otimes_{(k - 1)} \Sigma\ k\ (i + j + 1 - k)\ (\Sigma\ i\ (k - i)\ y)$
using *assms(1) less-imp-Suc-add* **by** *fastforce*
also have $\ldots = (\Sigma\ i\ (j + 1)\ x) \otimes_{(k - 1)} \Sigma\ k\ (i + j + 1 - k)\ (\Sigma\ i\ (k - i)\ y)$
by (*smt* (*verit*, *ccfv-SIG*) *Nat.diff-diff-eq Suc.prems(1) Suc.prems(2) add.comm-neutral add-left-mono assms(1) decomp-symcomp1 diff-add-inverse diff-le-mono group-cancel.add2 linordered-semidom-class.add-diff-inverse order-less-imp-le order-less-imp-not-less plus-1-eq-Suc zero-less-Suc*)
also have $\ldots = (\Sigma\ i\ (j + 1)\ x) \otimes_{(k - 1)} (\Sigma\ i\ (j + 1)\ y)$
by (*smt* (*verit*, *ccfv-SIG*) *Nat.add-0-right Nat.diff-diff-eq Suc.prems(1) Suc.prems(3) add-Suc add-Suc-shift add-diff-inverse-nat add-mono-thms-linordered-semiring(2) assms(1) decomp-symcomp1 diff-add-inverse diff-le-mono nless-le order.asym plus-1-eq-Suc trans-less-add2 zero-less-one*)
finally show *?case*
by *simp*
qed

lemma *symcomp-comp*:
assumes *fFx i x*
and *fFx i y*
and *DD k x y*
shows $\Sigma\ i\ j\ (x \otimes_k y) = (\mathit{if}\ k = i\ \mathit{then}\ \Sigma\ i\ j\ x \otimes_{(i + j)} \Sigma\ i\ j\ y\ \mathit{else}\ (\mathit{if}\ (i < k \wedge k \leq i + j)\ \mathit{then}\ \Sigma\ i\ j\ x \otimes_{(k - 1)} \Sigma\ i\ j\ y\ \mathit{else}\ \Sigma\ i\ j\ x \otimes_k \Sigma\ i\ j\ y))$
by (*metis assms linorder-not-le not-less-iff-gr-or-eq symcomp-comp1 symcomp-comp2 symcomp-comp3 symcomp-comp4*)

lemma *inv-symcomp-comp1*:
assumes *fFx* $(i + j)$ *x*
and *fFx* $(i + j)$ *y*
and *DD* $(i + j)$ *x y*
shows $\Theta\ i\ j\ (x \otimes_{(i + j)} y) = \Theta\ i\ j\ x \otimes_i \Theta\ i\ j\ y$
by (*metis assms inv-symcomp-type-var local.fFx-prop local.iDst local.icat.sscatml.l0-absorb*)

lemma *inv-symcomp-comp2*:
assumes $k < i$
and *fFx* $(i + j)$ *x*
and *fFx* $(i + j)$ *y*
and *DD k x y*

shows $\Theta\ i\ j\ (x \otimes_k y) = \Theta\ i\ j\ x \otimes_k \Theta\ i\ j\ y$
proof−
have *a*: *DD k* ($\Theta\ i\ j\ x$) ($\Theta\ i\ j\ y$)
using *assms inv-symcomp-face2 local.iDst local.locality* **by** *presburger*
have $x \otimes_k y = \Sigma\ i\ j\ (\Theta\ i\ j\ x) \otimes_k \Sigma\ i\ j\ (\Theta\ i\ j\ y)$
by (*simp add*: *assms*(*2*) *assms*(*3*) *symcomp-inv-symcomp*)
hence $x \otimes_k y = \Sigma\ i\ j\ ((\Theta\ i\ j\ x) \otimes_k (\Theta\ i\ j\ y))$
using *a assms*(*1*) *assms*(*2*) *assms*(*3*) *inv-symcomp-type-var symcomp-comp2*
by *presburger*
thus *?thesis*
using *a assms*(*1*) *assms*(*2*) *assms*(*3*) *fix-comp inv-symcomp-face3 inv-symcomp-symcomp*
by *simp*
qed

lemma *inv-symcomp-comp3*:
assumes $i + j < k$
and *fFx* ($i + j$) *x*
and *fFx* ($i + j$) *y*
and *DD k x y*
shows $\Theta\ i\ j\ (x \otimes_k y) = \Theta\ i\ j\ x \otimes_k \Theta\ i\ j\ y$
proof−
have *h*: *DD k* ($\Theta\ i\ j\ x$) ($\Theta\ i\ j\ y$)
using *assms inv-symcomp-face2 local.iDst local.locality* **by** *presburger*
have $x \otimes_k y = \Sigma\ i\ j\ (\Theta\ i\ j\ x) \otimes_k \Sigma\ i\ j\ (\Theta\ i\ j\ y)$
by (*simp add*: *assms*(*2*) *assms*(*3*) *symcomp-inv-symcomp*)
hence $x \otimes_k y = \Sigma\ i\ j\ ((\Theta\ i\ j\ x) \otimes_k (\Theta\ i\ j\ y))$
using *assms*(*1*) *assms*(*2*) *assms*(*3*) *h inv-symcomp-face3 symcomp-comp3* **by** *simp*
thus *?thesis*
using *assms*(*1*) *assms*(*2*) *assms*(*3*) *fix-comp h inv-symcomp-face3 inv-symcomp-symcomp*
by *simp*
qed

lemma *inv-symcomp-comp4*:
assumes $i \leq k$
and $k < i + j$
and *fFx* ($i + j$) *x*
and *fFx* ($i + j$) *y*
and *DD k x y*
shows $\Theta\ i\ j\ (x \otimes_k y) = \Theta\ i\ j\ x \otimes_{(k\ +\ 1)} \Theta\ i\ j\ y$
proof−
have *h*: *DD* ($k + 1$) ($\Theta\ i\ j\ x$) ($\Theta\ i\ j\ y$)
using *assms*(*1*) *assms*(*2*) *assms*(*3*) *assms*(*4*) *assms*(*5*) *inv-symcomp-face1 local.icat.sts-msg.st-local* **by** *auto*
have $x \otimes_k y = \Sigma\ i\ j\ (\Theta\ i\ j\ x) \otimes_k \Sigma\ i\ j\ (\Theta\ i\ j\ y)$
by (*simp add*: *assms*(*3*) *assms*(*4*) *symcomp-inv-symcomp*)
hence $x \otimes_k y = \Sigma\ i\ j\ ((\Theta\ i\ j\ x) \otimes_{(k\ +\ 1)} (\Theta\ i\ j\ y))$
apply (*subst symcomp-comp4*)
using *assms h inv-symcomp-type-var* **by** *auto*

thus *?thesis*
by (*metis Suc-eq-plus1 Suc-n-not-le-n assms(1) assms(3) assms(4) fix-comp h inv-symcomp-face3 inv-symcomp-symcomp*)
qed

end

end

4 Cubical Categories with Connections

theory *CubicalCategoriesConnections*
imports *CubicalCategories*

begin

All categories considered in this component are single-set categories.

class *connection-ops* =
fixes *connection* :: *nat* ⇒ *bool* ⇒ 'a ⇒ 'a (‹Γ›)

abbreviation (**in** *connection-ops*) ΓΓ *i α* ≡ *image* (Γ *i α*)

We define a class for cubical ω-categories with connections.

class *cubical-omega-category-connections* = *cubical-omega-category* + *connection-ops* +
assumes *conn-face1*: *fFx j x* ⟹ ∂ *j α* (Γ *j α x*) = *x*
and *conn-face2*: *fFx j x* ⟹ ∂ (*j* + *1*) *α* (Γ *j α x*) = *σ j x*
and *conn-face3*: *i* ≠ *j* ⟹ *i* ≠ *j* + *1* ⟹ *fFx j x* ⟹ ∂ *i α* (Γ *j β x*) = Γ *j β* (∂ *i α x*)
and *conn-corner1*: *fFx i x* ⟹ *fFx i y* ⟹ *DD* (*i* + *1*) *x y* ⟹ Γ *i tt* (*x* ⊗$_{(i + 1)}$ *y*) = (Γ *i tt x* ⊗$_{(i + 1)}$ *σ i x*) ⊗$_i$ (*x* ⊗$_{(i + 1)}$ Γ *i tt y*)
and *conn-corner2*: *fFx i x* ⟹ *fFx i y* ⟹ *DD* (*i* + *1*) *x y* ⟹ Γ *i ff* (*x* ⊗$_{(i + 1)}$ *y*) = (Γ *i ff x* ⊗$_{(i + 1)}$ *y*) ⊗$_i$ (*σ i y* ⊗$_{(i + 1)}$ Γ *i ff y*)
and *conn-corner3*: *j* ≠ *i* ∧ *j* ≠ *i* + *1* ⟹ *fFx i x* ⟹ *fFx i y* ⟹ *DD j x y* ⟹ Γ *i α* (*x* ⊗$_j$ *y*) = Γ *i α x* ⊗$_j$ Γ *i α y*
and *conn-fix*: *fFx i x* ⟹ *fFx* (*i* + *1*) *x* ⟹ Γ *i α x* = *x*
and *conn-zigzag1*: *fFx i x* ⟹ Γ *i tt x* ⊗$_{(i + 1)}$ Γ *i ff x* = *x*
and *conn-zigzag2*: *fFx i x* ⟹ Γ *i tt x* ⊗$_i$ Γ *i ff x* = *σ i x*
and *conn-conn-braid*: *diffSup i j 2* ⟹ *fFx j x* ⟹ *fFx i x* ⟹ Γ *i α* (Γ *j β x*) = Γ *j β* (Γ *i α x*)
and *conn-shift*: *fFx i x* ⟹ *fFx* (*i* + *1*) *x* ⟹ *σ* (*i* + *1*) (*σ i* (Γ (*i* + *1*) *α x*)) = Γ *i α* (*σ* (*i* + *1*) *x*)

begin

lemma *conn-face4*: *fFx j x* ⟹ ∂ *j α* (Γ *j* (¬*α*) *x*) = ∂ (*j* + *1*) *α x*
by (*smt* (*z3*) *local.conn-face1 local.conn-zigzag2 local.face-comm-var local.locality local.pcomp-lface local.pcomp-uface local.sym-face1 local.sym-fix-var1*)

lemma *conn-face1-lift*: $FFx\ j\ X \Longrightarrow \partial\partial\ j\ \alpha\ (\Gamma\Gamma\ j\ \alpha\ X) = X$
by (*auto simp add*: *image-iff local.conn-face1*)

lemma *conn-face4-lift*: $FFx\ j\ X \Longrightarrow \partial\partial\ j\ \alpha\ (\Gamma\Gamma\ j\ (\neg\alpha)\ X) = \partial\partial\ (j + 1)\ \alpha\ X$
apply *safe*
apply (*simp add*: *local.conn-face4*)
by (*metis image-eqI local.conn-face4*)

lemma *conn-face2-lift*: $FFx\ j\ X \Longrightarrow \partial\partial\ (j + 1)\ \alpha\ (\Gamma\Gamma\ j\ \alpha\ X) = \sigma\sigma\ j\ X$
by (*smt* (*z3*) *comp-apply image-comp image-cong local.conn-face2*)

lemma *conn-face3-lift*: $i \neq j \Longrightarrow i \neq j + 1 \Longrightarrow FFx\ j\ X \Longrightarrow \partial\partial\ i\ \alpha\ (\Gamma\Gamma\ j\ \beta\ X)$
$= \Gamma\Gamma\ j\ \beta\ (\partial\partial\ i\ \alpha\ X)$
by (*smt* (*z3*) *image-cong image-image local.conn-face3*)

lemma *conn-fix-lift*: $FFx\ i\ X \Longrightarrow FFx\ (i + 1)\ X \Longrightarrow \Gamma\Gamma\ i\ \alpha\ X = X$
by (*simp add*: *local.conn-fix*)

lemma *conn-conn-braid-lift*:
assumes *diffSup i j 2*
and *FFx j X*
and *FFx i X*
shows $\Gamma\Gamma\ i\ \alpha\ (\Gamma\Gamma\ j\ \beta\ X) = \Gamma\Gamma\ j\ \beta\ (\Gamma\Gamma\ i\ \alpha\ X)$
by (*smt* (*z3*) *assms image-cong image-image local.conn-conn-braid*)

lemma *conn-sym-braid*:
assumes *diffSup i j 2*
and *fFx i x*
and *fFx j x*
shows $\Gamma\ i\ \alpha\ (\sigma\ j\ x) = \sigma\ j\ (\Gamma\ i\ \alpha\ x)$
by (*smt* (*z3*) *assms add-diff-cancel-left' cancel-comm-monoid-add-class.diff-cancel diff-is-0-eq' icat.st-local le-add1 local.conn-conn-braid local.conn-corner3 local.conn-face1 local.conn-face3 local.conn-zigzag2 numeral-le-one-iff rel-simps*(*28*) *semiring-norm*(*69*))

lemma *conn-zigzag1-var* [*simp*]: $\Gamma\ i\ tt\ (\partial\ i\ \alpha\ x)\ \odot_{(i + 1)}\ \Gamma\ i\ ff\ (\partial\ i\ \alpha\ x) = \{\partial\ i\ \alpha\ x\}$
proof (*cases DD* $(i + 1)$ $(\Gamma\ i\ tt\ (\partial\ i\ \alpha\ x))$ $(\Gamma\ i\ ff\ (\partial\ i\ \alpha\ x))$)
case *True*
hence $\Gamma\ i\ tt\ (\partial\ i\ \alpha\ x)\ \odot_{(i + 1)}\ \Gamma\ i\ ff\ (\partial\ i\ \alpha\ x) = \{\Gamma\ i\ tt\ (\partial\ i\ \alpha\ x)\ \otimes_{(i + 1)}\ \Gamma\ i\ ff\ (\partial\ i\ \alpha\ x)\}$
by (*metis True local.icat.pcomp-def-var4*)
also have $\ldots = \{\partial\ i\ \alpha\ x\}$
using *local.conn-zigzag1* **by** *simp*
finally show *?thesis*.
next
case *False*
thus *?thesis*
using *local.conn-face2 local.locality* **by** *simp*

qed

lemma *conn-zigzag1-lift*:
assumes *FFx i X*
shows $\Gamma\Gamma\ i\ tt\ X \star_{(i+1)} \Gamma\Gamma\ i\ ff\ X = X$
proof−
have $\Gamma\Gamma\ i\ tt\ X \star_{(i+1)} \Gamma\Gamma\ i\ ff\ X = \{\Gamma\ i\ tt\ x \otimes_{(i+1)} \Gamma\ i\ ff\ y \mid x\ y.\ x \in X \wedge y \in X \wedge DD\ (i+1)\ (\Gamma\ i\ tt\ x)\ (\Gamma\ i\ ff\ y)\}$
unfolding *local.iconv-prop* **by** *force*
also have $\ldots = \{\Gamma\ i\ tt\ x \otimes_{(i+1)} \Gamma\ i\ ff\ y \mid x\ y.\ x \in X \wedge y \in X \wedge \partial\ (i+1)\ tt\ (\Gamma\ i\ tt\ x) = \partial\ (i+1)\ ff\ (\Gamma\ i\ ff\ y)\}$
using *icat.st-local* **by** *presburger*
also have $\ldots = \{\Gamma\ i\ tt\ x \otimes_{(i+1)} \Gamma\ i\ ff\ y \mid x\ y.\ x \in X \wedge y \in X \wedge \sigma\ i\ x = \sigma\ i\ y\}$
by (*metis* (*no-types*, *lifting*) *assms local.conn-face2*)
also have $\ldots = \{\Gamma\ i\ tt\ x \otimes_{(i+1)} \Gamma\ i\ ff\ x \mid x.\ x \in X\}$
using *assms local.sym-inj-var* **by** *blast*
also have $\ldots = \{\Gamma\ i\ tt\ (\partial\ i\ tt\ x) \otimes_{(i+1)} \Gamma\ i\ ff\ (\partial\ i\ tt\ x) \mid x.\ x \in X\}$
by (*metis* (*full-types*) *assms icid.ts-compat*)
also have $\ldots = \{\partial\ i\ tt\ x \mid x.\ x \in X\}$
using *local.conn-zigzag1 local.face-compat-var* **by** *presburger*
also have $\ldots = X$
by (*smt* (*verit*, *del-insts*) *Collect-cong Collect-mem-eq assms local.icid.stopp.st-fix*)
finally show *?thesis*.
qed

lemma *conn-zigzag2-var*: $\Gamma\ i\ tt\ (\partial\ i\ \alpha\ x) \odot_i \Gamma\ i\ ff\ (\partial\ i\ \alpha\ x) = \{\sigma\ i\ (\partial\ i\ \alpha\ x)\}$
proof (*cases DD i* ($\Gamma\ i\ tt\ (\partial\ i\ \alpha\ x)$) ($\Gamma\ i\ ff\ (\partial\ i\ \alpha\ x)$))
case *True*
hence $\Gamma\ i\ tt\ (\partial\ i\ \alpha\ x) \odot_i \Gamma\ i\ ff\ (\partial\ i\ \alpha\ x) = \{\Gamma\ i\ tt\ (\partial\ i\ \alpha\ x) \otimes_i \Gamma\ i\ ff\ (\partial\ i\ \alpha\ x)\}$
by (*metis True local.icat.pcomp-def-var4*)
also have $\ldots = \{\sigma\ i\ (\partial\ i\ \alpha\ x)\}$
using *local.conn-zigzag2* **by** *simp*
finally show *?thesis*.
next
case *False*
thus *?thesis*
by (*simp add*: *local.conn-face1 local.locality*)
qed

lemma *conn-zigzag2-lift*:
assumes *FFx i X*
shows $\Gamma\Gamma\ i\ tt\ X \star_i \Gamma\Gamma\ i\ ff\ X = \sigma\sigma\ i\ X$
proof−
have $\Gamma\Gamma\ i\ tt\ X \star_i \Gamma\Gamma\ i\ ff\ X = \{\Gamma\ i\ tt\ x \otimes_i \Gamma\ i\ ff\ y \mid x\ y.\ x \in X \wedge y \in X \wedge DD\ i\ (\Gamma\ i\ tt\ x)\ (\Gamma\ i\ ff\ y)\}$
unfolding *local.iconv-prop* **by** *force*
also have $\ldots = \{\Gamma\ i\ tt\ x \otimes_i \Gamma\ i\ ff\ y \mid x\ y.\ x \in X \wedge y \in X \wedge \partial\ i\ tt\ (\Gamma\ i\ tt\ x) =$

$\partial\ i\ ff\ (\Gamma\ i\ ff\ y)\}$
using *icat.st-local* **by** *presburger*
also have $\ldots = \{\Gamma\ i\ tt\ x \otimes_i \Gamma\ i\ ff\ x \mid x.\ x \in X\}$
by (*metis* (*full-types*) *assms local.conn-face1*)
also have $\ldots = \{\Gamma\ i\ tt\ (\partial\ i\ tt\ x) \otimes_i \Gamma\ i\ ff\ (\partial\ i\ tt\ x) \mid x.\ x \in X\}$
by (*metis* (*full-types*) *assms icid.ts-compat*)
also have $\ldots = \{\sigma\ i\ x \mid x.\ x \in X\}$
by (*metis assms icid.ts-compat local.conn-zigzag2*)
also have $\ldots = \sigma\sigma\ i\ X$
by *force*
finally show *?thesis*.
qed

lemma *conn-sym-braid-lift*: *diffSup i j 2* $\Longrightarrow$ *FFx i X* $\Longrightarrow$ *FFx j X* $\Longrightarrow$ $\Gamma\Gamma\ i\ \alpha\ (\sigma\sigma\ j\ X) = \sigma\sigma\ j\ (\Gamma\Gamma\ i\ \alpha\ X)$
by (*smt* (*z3*) *image-cong image-image local.conn-sym-braid*)

lemma *conn-corner1-DD*:
assumes *fFx i x*
and *fFx i y*
and *DD* $(i + 1)\ x\ y$
shows *DD i* $(\Gamma\ i\ tt\ x \otimes_{(i + 1)} \sigma\ i\ x)\ (x \otimes_{(i + 1)} \Gamma\ i\ tt\ y)$
proof−
have *h1*: *DD* $(i + 1)\ (\Gamma\ i\ tt\ x)\ (\sigma\ i\ x)$
using *assms(1) local.conn-face2 local.locality local.sym-type-var* **by** *simp*
have *h2*: *DD* $(i + 1)\ x\ (\Gamma\ i\ tt\ y)$
by (*metis assms(2) assms(3) conn-zigzag1-var icat.st-local icid.src-comp-aux singleton-iff*)
have *h3*: $\partial\ i\ tt\ (\Gamma\ i\ tt\ x \otimes_{(i + 1)} \sigma\ i\ x) = x$
by (*metis assms(1) local.conn-face1 local.conn-face2 local.icat.sscatml.r0-absorb*)
have $\partial\ i\ ff\ (x \otimes_{(i + 1)} \Gamma\ i\ tt\ y) = \partial\ i\ ff\ x \otimes_{(i + 1)} \partial\ i\ ff\ (\Gamma\ i\ tt\ y)$
using *h2 local.face-func* **by** *simp*
hence *h4*: $\partial\ i\ ff\ (x \otimes_{(i + 1)} \Gamma\ i\ tt\ y) = x \otimes_{(i + 1)} \partial\ (i + 1)\ ff\ y$
by (*metis* (*full-types*) *assms(1) assms(2) local.conn-face4*)
have $\partial\ i\ tt\ (\Gamma\ i\ tt\ x \otimes_{(i + 1)} \sigma\ i\ x) = \partial\ i\ tt\ (\Gamma\ i\ tt\ x) \otimes_{(i + 1)} \partial\ i\ tt\ (\sigma\ i\ x)$
using *h1 local.face-func* **by** *simp*
also have $\ldots = x \otimes_{(i + 1)} \partial\ (i + 1)\ tt\ x$
using *calculation h3* **by** *simp*
thus *?thesis*
using *assms(3) h3 h4 local.icat.sts-msg.st-local* **by** *simp*
qed

lemma *conn-corner1-var*: $\Gamma\Gamma\ i\ tt\ (\partial\ i\ \alpha\ x \odot_{(i + 1)} \partial\ i\ \beta\ y) = (\Gamma\ i\ tt\ (\partial\ i\ \alpha\ x) \odot_{(i + 1)} \sigma\ i\ (\partial\ i\ \alpha\ x)) \star_i (\partial\ i\ \alpha\ x \odot_{(i + 1)} \Gamma\ i\ tt\ (\partial\ i\ \beta\ y))$
proof (*cases DD* $(i + 1)\ (\partial\ i\ \alpha\ x)\ (\partial\ i\ \beta\ y)$)
case *True*
have *h1*: *DD* $(i + 1)\ (\Gamma\ i\ tt\ (\partial\ i\ \alpha\ x))\ (\sigma\ i\ (\partial\ i\ \alpha\ x))$
by (*metis local.conn-face2 local.face-compat-var local.locality*)

have *h2*: *DD* $(i + 1)$ $(\partial\ i\ \alpha\ x)$ $(\Gamma\ i\ tt\ (\partial\ i\ \beta\ y))$
by (*metis True icid.src-comp-aux insertCI local.conn-zigzag1-var local.iDst local.locality*)
have *h3*: *DD* i $(\Gamma\ i\ tt\ (\partial\ i\ \alpha\ x) \otimes_{(i + 1)} \sigma\ i\ (\partial\ i\ \alpha\ x))$ $(\partial\ i\ \alpha\ x \otimes_{(i + 1)} \Gamma\ i\ tt\ (\partial\ i\ \beta\ y))$
using *True local.conn-corner1-DD local.face-compat-var* **by** *simp*
have $\Gamma\Gamma\ i\ tt\ (\partial\ i\ \alpha\ x \odot_{(i + 1)} \partial\ i\ \beta\ y) = \Gamma\Gamma\ i\ tt\ \{\partial\ i\ \alpha\ x \otimes_{(i + 1)} \partial\ i\ \beta\ y\}$
using *True local.icat.pcomp-def-var4* **by** *simp*
also have $\ldots = \{(\Gamma\ i\ tt\ (\partial\ i\ \alpha\ x) \otimes_{(i + 1)} \sigma\ i\ (\partial\ i\ \alpha\ x)) \otimes_i (\partial\ i\ \alpha\ x \otimes_{(i + 1)} \Gamma\ i\ tt\ (\partial\ i\ \beta\ y))\}$
using *True local.conn-corner1 local.face-compat-var* **by** *simp*
also have $\ldots = \{\Gamma\ i\ tt\ (\partial\ i\ \alpha\ x) \otimes_{(i + 1)} \sigma\ i\ (\partial\ i\ \alpha\ x)\} \star_i \{\partial\ i\ \alpha\ x \otimes_{(i + 1)} \Gamma\ i\ tt\ (\partial\ i\ \beta\ y)\}$
using *h3 local.icat.pcomp-def-var4 local.icid.stopp.conv-atom* **by** *simp*
also have $\ldots = (\Gamma\ i\ tt\ (\partial\ i\ \alpha\ x) \odot_{(i + 1)} \sigma\ i\ (\partial\ i\ \alpha\ x)) \star_i (\partial\ i\ \alpha\ x \odot_{(i + 1)} \Gamma\ i\ tt\ (\partial\ i\ \beta\ y))$
using *h1 h2 local.icat.pcomp-def-var4* **by** *simp*
finally show *?thesis*.
next
case *False*
thus *?thesis*
by (*smt* (*z3*) *Union-empty empty-is-image icat.st-local icid.ts-compat local.conn-face4 local.face-comm-var local.icid.stopp.ts-compat multimagma.conv-distl*)
qed

lemma *conn-corner1-lift-aux*: *fFx i x* $\Longrightarrow \partial\ (i + 1)\ ff\ (\Gamma\ i\ tt\ x) = \partial\ (i + 1)\ ff\ x$
by (*metis conn-zigzag1-var empty-not-insert equals0I icid.src-comp-aux singletonD*)

lemma *conn-corner1-lift*:
assumes *FFx i X*
and *FFx i Y*
shows $\Gamma\Gamma\ i\ tt\ (X \star_{(i + 1)} Y) = (\Gamma\Gamma\ i\ tt\ X \star_{(i + 1)} \sigma\sigma\ i\ X) \star_i (X \star_{(i + 1)} \Gamma\Gamma\ i\ tt\ Y)$
proof−
have *h1*: $\forall\, y \in Y.\ \partial\ (i + 1)\ ff\ (\Gamma\ i\ tt\ y) = \partial\ (i + 1)\ ff\ y$
by (*metis assms*(*2*) *conn-zigzag1-var local.icid.ts-msg.tgt-comp-aux singletonI*)
have *h2* :$\forall\, xa \in X.\ DD\ (i + 1)\ (\Gamma\ i\ tt\ xa)\ (\sigma\ i\ xa) \longrightarrow \partial\ i\ tt\ (\Gamma\ i\ tt\ xa \otimes_{(i + 1)} \sigma\ i\ xa) = \partial\ i\ tt\ (\Gamma\ i\ tt\ xa) \otimes_{(i + 1)} \partial\ i\ tt\ (\sigma\ i\ xa)$
by (*simp add*: *local.face-func*)
have *h3* :$\forall\, xc \in X.\ \forall\, y \in Y.\ DD\ (i + 1)\ xc\ (\Gamma\ i\ tt\ y) \longrightarrow \partial\ i\ ff\ (xc \otimes_{(i + 1)} \Gamma\ i\ tt\ y) = \partial\ i\ ff\ xc \otimes_{(i + 1)} \partial\ i\ ff\ (\Gamma\ i\ tt\ y)$
by (*simp add*: *local.face-func*)
have *h4*: $\forall\, xa \in X.\ \partial\ i\ tt\ (\Gamma\ i\ tt\ xa) \otimes_{(i + 1)} \partial\ i\ tt\ (\sigma\ i\ xa) = xa \otimes_{(i + 1)} \partial\ i\ tt\ (\partial\ (i + 1)\ tt\ xa)$
by (*smt* (*z3*) *assms*(*1*) *local.conn-face1 local.fFx-prop local.face-comm-var local.sym-face1-var1 local.sym-fix-var1*)

have *h5*: $\forall\, xc \in X.\ \forall\, y \in Y.\ \partial\ i\ ff\ xc \otimes_{(i\ +\ 1)} \partial\ i\ ff\ (\Gamma\ i\ tt\ y) = xc \otimes_{(i\ +\ 1)} \partial\ (i\ +\ 1)\ ff\ y$
by (*metis* (*full-types*) *assms*(*1*) *assms*(*2*) *local.conn-face4*)
have *h6*: $\forall\, xc \in X.\ \forall\, y \in Y.\ DD\ (i\ +\ 1)\ xc\ (\partial\ (i\ +\ 1)\ ff\ y) \longrightarrow xc \otimes_{(i\ +\ 1)} \partial\ (i\ +\ 1)\ ff\ y = xc$
by (*metis local.face-compat-var local.icat.sscatml.r0-absorb local.icid.stopp.Dst*)
have *h7*: $\forall\, xa \in X.\ xa \otimes_{(i\ +\ 1)} \partial\ i\ tt\ (\partial\ (i\ +\ 1)\ tt\ xa) = xa$
by (*metis assms*(*1*) *local.face-comm-var local.face-compat-var local.icat.sscatml.r0-absorb*)
have *h8*: $\forall\, x \in X.\ \forall\, y \in Y.\ DD\ (i\ +\ 1)\ x\ y \longrightarrow (\Gamma\ i\ tt\ x \otimes_{(i\ +\ 1)} \sigma\ i\ x) \otimes_i (x \otimes_{(i\ +\ 1)} \Gamma\ i\ tt\ y) = \Gamma\ i\ tt\ (x \otimes_{(i\ +\ 1)} y)$
using *assms*(*1*) *assms*(*2*) *local.conn-corner1* **by** *auto*
have $(\Gamma\Gamma\ i\ tt\ X \star_{(i\ +\ 1)} \sigma\sigma\ i\ X) \star_i (X \star_{(i\ +\ 1)} \Gamma\Gamma\ i\ tt\ Y) = \{(\Gamma\ i\ tt\ xa \otimes_{(i\ +\ 1)} \sigma\ i\ xb) \otimes_i (xc \otimes_{(i\ +\ 1)} \Gamma\ i\ tt\ y) \mid xa\ xb\ xc\ y.\ xa \in X \wedge xb \in X \wedge xc \in X \wedge y \in Y \wedge DD\ (i\ +\ 1)\ (\Gamma\ i\ tt\ xa)\ (\sigma\ i\ xb) \wedge DD\ (i\ +\ 1)\ xc\ (\Gamma\ i\ tt\ y) \wedge DD\ i\ (\Gamma\ i\ tt\ xa \otimes_{(i\ +\ 1)} \sigma\ i\ xb)\ (xc \otimes_{(i\ +\ 1)} \Gamma\ i\ tt\ y)\}$
unfolding *local.iconv-prop* **by** *blast*
also have $\ldots = \{(\Gamma\ i\ tt\ xa \otimes_{(i\ +\ 1)} \sigma\ i\ xb) \otimes_i (xc \otimes_{(i\ +\ 1)} \Gamma\ i\ tt\ y) \mid xa\ xb\ xc\ y.\ xa \in X \wedge xb \in X \wedge xc \in X \wedge y \in Y \wedge \partial\ (i\ +\ 1)\ tt\ (\Gamma\ i\ tt\ xa) = \partial\ (i\ +\ 1)\ ff\ (\sigma\ i\ xb) \wedge \partial\ (i\ +\ 1)\ tt\ xc = \partial\ (i\ +\ 1)\ ff\ (\Gamma\ i\ tt\ y) \wedge \partial\ i\ tt\ (\Gamma\ i\ tt\ xa \otimes_{(i\ +\ 1)} \sigma\ i\ xb) = \partial\ i\ ff\ (xc \otimes_{(i\ +\ 1)} \Gamma\ i\ tt\ y)\}$
using *icat.st-local* **by** *presburger*
also have $\ldots = \{(\Gamma\ i\ tt\ xa \otimes_{(i\ +\ 1)} \sigma\ i\ xb) \otimes_i (xc \otimes_{(i\ +\ 1)} \Gamma\ i\ tt\ y) \mid xa\ xb\ xc\ y.\ xa \in X \wedge xb \in X \wedge xc \in X \wedge y \in Y \wedge xa = xb \wedge \partial\ (i\ +\ 1)\ tt\ xc = \partial\ (i\ +\ 1)\ ff\ (\Gamma\ i\ tt\ y) \wedge \partial\ i\ tt\ (\Gamma\ i\ tt\ xa \otimes_{(i\ +\ 1)} \sigma\ i\ xb) = \partial\ i\ ff\ (xc \otimes_{(i\ +\ 1)} \Gamma\ i\ tt\ y)\}$
by (*smt* (*verit*) *Collect-cong assms*(*1*) *local.conn-face2 local.sym-type-var*)
also have $\ldots = \{(\Gamma\ i\ tt\ xa \otimes_{(i\ +\ 1)} \sigma\ i\ xa) \otimes_i (xc \otimes_{(i\ +\ 1)} \Gamma\ i\ tt\ y) \mid xa\ xc\ y.\ xa \in X \wedge xc \in X \wedge y \in Y \wedge \partial\ (i\ +\ 1)\ tt\ xc = \partial\ (i\ +\ 1)\ ff\ y \wedge \partial\ i\ tt\ (\Gamma\ i\ tt\ xa \otimes_{(i\ +\ 1)} \sigma\ i\ xa) = \partial\ i\ ff\ (xc \otimes_{(i\ +\ 1)} \Gamma\ i\ tt\ y)\}$
by (*smt* (*verit*, *best*) *Collect-cong assms*(*1*) *h1 local.conn-face3 local.locality local.sym-type-var*)
also have $\ldots = \{(\Gamma\ i\ tt\ xa \otimes_{(i\ +\ 1)} \sigma\ i\ xa) \otimes_i (xc \otimes_{(i\ +\ 1)} \Gamma\ i\ tt\ y) \mid xa\ xc\ y.\ xa \in X \wedge xc \in X \wedge y \in Y \wedge \partial\ (i\ +\ 1)\ tt\ xc = \partial\ (i\ +\ 1)\ ff\ y \wedge \partial\ i\ tt\ (\Gamma\ i\ tt\ xa) \otimes_{(i\ +\ 1)} \partial\ i\ tt\ (\sigma\ i\ xa) = \partial\ i\ ff\ xc \otimes_{(i\ +\ 1)} \partial\ i\ ff\ (\Gamma\ i\ tt\ y)\}$
by (*smt* (*verit*, *del-insts*) *h2 h3 Collect-cong assms*(*1*) *h1 icat.st-local local.conn-face2 local.sym-type-var*)
also have $\ldots = \{(\Gamma\ i\ tt\ xa \otimes_{(i\ +\ 1)} \sigma\ i\ xa) \otimes_i (xc \otimes_{(i\ +\ 1)} \Gamma\ i\ tt\ y) \mid xa\ xc\ y.\ xa \in X \wedge xc \in X \wedge y \in Y \wedge \partial\ (i\ +\ 1)\ tt\ xc = \partial\ (i\ +\ 1)\ ff\ y \wedge xa \otimes_{(i\ +\ 1)} \partial\ i\ tt\ (\partial\ (i\ +\ 1)\ tt\ xa) = xc \otimes_{(i\ +\ 1)} \partial\ (i\ +\ 1)\ ff\ y\}$
by (*smt* (*verit*, *del-insts*) *h4 h5 Collect-cong*)
also have $\ldots = \{(\Gamma\ i\ tt\ xa \otimes_{(i\ +\ 1)} \sigma\ i\ xa) \otimes_i (xc \otimes_{(i\ +\ 1)} \Gamma\ i\ tt\ y) \mid xa\ xc\ y.\ xa \in X \wedge xc \in X \wedge y \in Y \wedge \partial\ (i\ +\ 1)\ tt\ xc = \partial\ (i\ +\ 1)\ ff\ y \wedge xa = xc\}$
by (*smt* (*z3*) *h6 h7 Collect-cong assms*(*2*) *icid.st-eq1 local.face-comm-var*)
also have $\ldots = \{\Gamma\ i\ tt\ (x \otimes_{(i\ +\ 1)} y) \mid x\ y.\ x \in X \wedge y \in Y \wedge DD\ (i\ +\ 1)\ x\ y\}$
by (*smt* (*verit*, *ccfv-threshold*) *h8 Collect-cong icat.st-local*)
also have $\ldots = \Gamma\Gamma\ i\ tt\ (X \star_{(i\ +\ 1)} Y)$

unfolding *local.iconv-prop* **by** *force*
finally show *?thesis*
by *simp*
qed

lemma *conn-corner2-DD*:
assumes *fFx i x*
and *fFx i y*
and *DD* $(i + 1)$ *x y*
shows *DD i* $(\Gamma\ i\ ff\ x \otimes_{(i+1)} y)$ $(\sigma\ i\ y \otimes_{(i+1)} \Gamma\ i\ ff\ y)$
proof−
have *h1*: *DD* $(i + 1)$ $(\Gamma\ i\ ff\ x)$ *y*
by (*metis assms*(*1*) *assms*(*3*) *conn-zigzag1-var insertCI local.iDst local.icid.ts-msg.src-comp-aux local.locality*)
have *h2*: $\partial\ i\ ff\ (\sigma\ i\ y \otimes_{(i+1)} \Gamma\ i\ ff\ y) = \partial\ i\ ff\ (\sigma\ i\ y) \otimes_{(i+1)} \partial\ i\ ff\ (\Gamma\ i\ ff\ y)$
using *assms*(*2*) *local.conn-face2 local.face-func local.locality local.sym-face3-simp*
by *auto*
have $\partial\ i\ tt\ (\Gamma\ i\ ff\ x \otimes_{(i+1)} y) = \partial\ i\ tt\ (\Gamma\ i\ ff\ x) \otimes_{(i+1)} \partial\ i\ tt\ y$
using *h1 local.face-func* **by** *simp*
hence *h4*: $\partial\ i\ tt\ (\Gamma\ i\ ff\ x \otimes_{(i+1)} y) = \partial\ (i + 1)\ tt\ x \otimes_{(i+1)} y$
by (*metis* (*full-types*) *assms*(*1*) *assms*(*2*) *icid.st-eq1 local.conn-face4*)
thus *?thesis*
by (*metis h2 assms*(*2*) *assms*(*3*) *local.conn-face1 local.conn-face2 local.face-comm-var local.icid.stopp.Dst local.locality*)
qed

lemma *conn-corner2-var*: $\Gamma\Gamma\ i\ ff\ (\partial\ i\ \alpha\ x \odot_{(i+1)} \partial\ i\ \beta\ y) = (\Gamma\ i\ ff\ (\partial\ i\ \alpha\ x) \odot_{(i+1)} \partial\ i\ \beta\ y) \star_i (\sigma\ i\ (\partial\ i\ \beta\ y) \odot_{(i+1)} \Gamma\ i\ ff\ (\partial\ i\ \beta\ y))$
proof (*cases DD* $(i + 1)$ $(\partial\ i\ \alpha\ x)$ $(\partial\ i\ \beta\ y)$)
case *True*
have *h1*: *DD* $(i + 1)$ $(\Gamma\ i\ ff\ (\partial\ i\ \alpha\ x))$ $(\partial\ i\ \beta\ y)$
by (*metis True insertCI local.conn-zigzag1-var local.iDst local.icid.ts-msg.src-comp-aux local.locality*)
have *h2*: *DD* $(i + 1)$ $(\sigma\ i\ (\partial\ i\ \beta\ y))$ $(\Gamma\ i\ ff\ (\partial\ i\ \beta\ y))$
by (*metis local.conn-face2 local.face-compat-var local.locality*)
have *h3*: *DD i* $(\Gamma\ i\ ff\ (\partial\ i\ \alpha\ x) \otimes_{(i+1)} \partial\ i\ \beta\ y)$ $(\sigma\ i\ (\partial\ i\ \beta\ y) \otimes_{(i+1)} \Gamma\ i\ ff\ (\partial\ i\ \beta\ y))$
using *True local.conn-corner2-DD* **by** *simp*
have $\Gamma\Gamma\ i\ ff\ (\partial\ i\ \alpha\ x \odot_{(i+1)} \partial\ i\ \beta\ y) = \{\Gamma\ i\ ff\ (\partial\ i\ \alpha\ x \otimes_{(i+1)} \partial\ i\ \beta\ y)\}$
by (*metis* (*full-types*) *True local.icat.pcomp-def-var4 image-empty image-insert*)

also have $\ldots = \{(\Gamma\ i\ ff\ (\partial\ i\ \alpha\ x) \otimes_{(i+1)} (\partial\ i\ \beta\ y)) \otimes_i (\sigma\ i\ (\partial\ i\ \beta\ y) \otimes_{(i+1)} \Gamma\ i\ ff\ (\partial\ i\ \beta\ y))\}$
using *True conn-corner2 local.face-compat-var* **by** *simp*
also have $\ldots = \{\Gamma\ i\ ff\ (\partial\ i\ \alpha\ x) \otimes_{(i+1)} (\partial\ i\ \beta\ y)\} \star_i \{\sigma\ i\ (\partial\ i\ \beta\ y) \otimes_{(i+1)} \Gamma\ i\ ff\ (\partial\ i\ \beta\ y)\}$
using *h3 local.icat.pcomp-def-var4 local.icid.stopp.conv-atom* **by** *simp*

also have $\ldots = (\Gamma\ i \mathit{ff}\ (\partial\ i\ \alpha\ x) \odot_{(i+1)} (\partial\ i\ \beta\ y)) \star_i \{\sigma\ i\ (\partial\ i\ \beta\ y) \otimes_{(i+1)} \Gamma\ i \mathit{ff}\ (\partial\ i\ \beta\ y)\}$
by (*metis h1 local.icat.functionality-lem-var local.icat.pcomp-def local.icat.sscatml.r0-absorb local.it-absorb*)
also have $\ldots = (\Gamma\ i \mathit{ff}\ (\partial\ i\ \alpha\ x) \odot_{(i+1)} (\partial\ i\ \beta\ y)) \star_i (\sigma\ i\ (\partial\ i\ \beta\ y) \odot_{(i+1)} \Gamma\ i \mathit{ff}\ (\partial\ i\ \beta\ y))$
using *h2 local.icat.pcomp-def-var4* **by** *simp*
finally show *?thesis*.
next
case *False*
thus *?thesis*
by (*metis UN-empty add-eq-self-zero empty-is-image local.conn-face1 local.face-compat-var local.pcomp-face-func-DD multimagma.conv-def nat-neq-iff zero-less-one*)
qed

lemma *conn-corner2-lift*:
assumes *FFx i X*
and *FFx i Y*
shows $\Gamma\Gamma\ i \mathit{ff}\ (X \star_{(i+1)} Y) = (\Gamma\Gamma\ i \mathit{ff}\ X \star_{(i+1)} Y) \star_i (\sigma\sigma\ i\ Y \star_{(i+1)} \Gamma\Gamma\ i \mathit{ff}\ Y)$
proof−
have *h1* :$\forall\, x \in X.\ \forall\, ya \in Y.\ \partial\ (i+1)\ tt\ x = \partial\ (i+1)\ \mathit{ff}\ ya \longrightarrow \partial\ i\ tt\ (\Gamma\ i \mathit{ff}\ x \otimes_{(i+1)} ya) = \partial\ i\ tt\ (\Gamma\ i \mathit{ff}\ x) \otimes_{(i+1)} \partial\ i\ tt\ ya$
by (*metis local.face-func add.commute add-diff-cancel-right' assms(1) bot-nat-0.extremum-unique cancel-comm-monoid-add-class.diff-cancel conn-zigzag1-var empty-not-insert ex-in-conv icat.st-local local.icid.ts-msg.src-comp-aux not-one-le-zero singletonD*)
have *h2* :$\forall\, yb \in Y.\ DD\ (i+1)\ (\sigma\ i\ yb)\ (\Gamma\ i \mathit{ff}\ yb) \longrightarrow \partial\ i \mathit{ff}\ (\sigma\ i\ yb \otimes_{(i+1)} \Gamma\ i \mathit{ff}\ yb) = \partial\ i \mathit{ff}\ (\sigma\ i\ yb) \otimes_{(i+1)} \partial\ i \mathit{ff}\ (\Gamma\ i \mathit{ff}\ yb)$
by (*simp add*: *local.face-func*)
have *h3*: $\forall\, x \in X.\ \forall\, y \in Y.\ DD\ (i+1)\ x\ y \longrightarrow (\Gamma\ i \mathit{ff}\ x \otimes_{(i+1)} y) \otimes_i (\sigma\ i\ y \otimes_{(i+1)} \Gamma\ i \mathit{ff}\ y) = \Gamma\ i \mathit{ff}\ (x \otimes_{(i+1)} y)$
using *assms local.conn-corner2* **by** *simp*
have *h4*: $\forall\, x \in X.\ \forall\, ya \in Y.\ (\partial\ (i+1)\ tt\ (\Gamma\ i \mathit{ff}\ x) = \partial\ (i+1)\ \mathit{ff}\ ya) = (\partial\ (i+1)\ tt\ x = \partial\ (i+1)\ \mathit{ff}\ ya)$
by (*metis assms(1) conn-zigzag1-var local.icid.ts-msg.src-comp-aux singletonI*)
have *h5*: $\forall\, yb \in Y.\ \forall\, yc \in Y.\ (\partial\ (i+1)\ tt\ (\sigma\ i\ yb) = \partial\ (i+1)\ \mathit{ff}\ (\Gamma\ i \mathit{ff}\ yc)) = (yb = yc)$
by (*metis assms(2) local.conn-face2 local.inv-sym-sym local.sym-face3-simp*)
have *h6*: $\forall\, x \in X.\ \forall\, ya \in Y.\ \forall\, yb \in Y.\ (x \in X \wedge ya \in Y \wedge yb \in Y \wedge \partial\ (i+1)\ tt\ x = \partial\ (i+1)\ \mathit{ff}\ ya \wedge \partial\ i\ tt\ (\Gamma\ i \mathit{ff}\ x \otimes_{(i+1)} ya) = \partial\ i \mathit{ff}\ (\sigma\ i\ yb \otimes_{(i+1)} \Gamma\ i \mathit{ff}\ yb)) = (x \in X \wedge ya \in Y \wedge yb \in Y \wedge \partial\ (i+1)\ tt\ x = \partial\ (i+1)\ \mathit{ff}\ ya \wedge \partial\ i\ tt\ (\Gamma\ i \mathit{ff}\ x) \otimes_{(i+1)} \partial\ i\ tt\ ya = \partial\ i \mathit{ff}\ (\sigma\ i\ yb) \otimes_{(i+1)} \partial\ i \mathit{ff}\ (\Gamma\ i \mathit{ff}\ yb))$
using *h1 h2 h5 icat.st-local* **by** *force*
have $(\Gamma\Gamma\ i \mathit{ff}\ X \star_{(i+1)} Y) \star_i (\sigma\sigma\ i\ Y \star_{(i+1)} \Gamma\Gamma\ i \mathit{ff}\ Y) = \{(\Gamma\ i \mathit{ff}\ x \otimes_{(i+1)} ya) \otimes_i (\sigma\ i\ yb \otimes_{(i+1)} \Gamma\ i \mathit{ff}\ yc) \mid x\ ya\ yb\ yc.\ x \in X \wedge ya \in Y \wedge yb \in Y \wedge yc \in Y \wedge DD\ (i+1)\ (\Gamma\ i \mathit{ff}\ x)\ ya \wedge DD\ (i+1)\ (\sigma\ i\ yb)\ (\Gamma\ i \mathit{ff}\ yc) \wedge DD\ i\ (\Gamma\ i \mathit{ff}\ x \otimes_{(i+1)} ya)\ (\sigma\ i\ yb \otimes_{(i+1)} \Gamma\ i \mathit{ff}\ yc)\}$

unfolding *local.iconv-prop* **by** *fastforce*
also have $\ldots = \{(\Gamma\ i\ ff\ x \otimes_{(i+1)} ya) \otimes_i (\sigma\ i\ yb \otimes_{(i+1)} \Gamma\ i\ ff\ yc) \mid x\ ya\ yb\ yc.\ x \in X \wedge ya \in Y \wedge yb \in Y \wedge yc \in Y \wedge \partial\ (i+1)\ tt\ (\Gamma\ i\ ff\ x) = \partial\ (i+1)\ ff\ ya \wedge \partial\ (i+1)\ tt\ (\sigma\ i\ yb) = \partial\ (i+1)\ ff\ (\Gamma\ i\ ff\ yc) \wedge \partial\ i\ tt\ (\Gamma\ i\ ff\ x \otimes_{(i+1)} ya) = \partial\ i\ ff\ (\sigma\ i\ yb \otimes_{(i+1)} \Gamma\ i\ ff\ yc)\}$
using *icat.st-local* **by** *simp*
also have $\ldots = \{(\Gamma\ i\ ff\ x \otimes_{(i+1)} ya) \otimes_i (\sigma\ i\ yb \otimes_{(i+1)} \Gamma\ i\ ff\ yb) \mid x\ ya\ yb.\ x \in X \wedge ya \in Y \wedge yb \in Y \wedge \partial\ (i+1)\ tt\ x = \partial\ (i+1)\ ff\ ya \wedge \partial\ i\ tt\ (\Gamma\ i\ ff\ x \otimes_{(i+1)} ya) = \partial\ i\ ff\ (\sigma\ i\ yb \otimes_{(i+1)} \Gamma\ i\ ff\ yb)\}$
using *h4 h5* **by** (*smt* (*verit*, *del-insts*) *Collect-cong*)
also have $\ldots = \{(\Gamma\ i\ ff\ x \otimes_{(i+1)} ya) \otimes_i (\sigma\ i\ yb \otimes_{(i+1)} \Gamma\ i\ ff\ yb) \mid x\ ya\ yb.\ x \in X \wedge ya \in Y \wedge yb \in Y \wedge \partial\ (i+1)\ tt\ x = \partial\ (i+1)\ ff\ ya \wedge \partial\ i\ tt\ (\Gamma\ i\ ff\ x) \otimes_{(i+1)} \partial\ i\ tt\ ya = \partial\ i\ ff\ (\sigma\ i\ yb) \otimes_{(i+1)} \partial\ i\ ff\ (\Gamma\ i\ ff\ yb)\}$
using *h6* **by** *fastforce*
also have $\ldots = \{(\Gamma\ i\ ff\ x \otimes_{(i+1)} ya) \otimes_i (\sigma\ i\ yb \otimes_{(i+1)} \Gamma\ i\ ff\ yb) \mid x\ ya\ yb.\ x \in X \wedge ya \in Y \wedge yb \in Y \wedge \partial\ (i+1)\ tt\ x = \partial\ (i+1)\ ff\ ya \wedge \partial\ (i+1)\ tt\ x \otimes_{(i+1)} ya = \partial\ (i+1)\ ff\ yb \otimes_{(i+1)} yb\}$
by (*smt* (*z3*) *Collect-cong assms*(*1*) *assms*(*2*) *icid.st-eq1 local.conn-face1 local.conn-face4 local.conn-face2 local.face-comm-var*)
also have $\ldots = \{(\Gamma\ i\ ff\ x \otimes_{(i+1)} ya) \otimes_i (\sigma\ i\ yb \otimes_{(i+1)} \Gamma\ i\ ff\ yb) \mid x\ ya\ yb.\ x \in X \wedge ya \in Y \wedge yb \in Y \wedge \partial\ (i+1)\ tt\ x = \partial\ (i+1)\ ff\ ya \wedge ya = yb\}$
by *force*
also have $\ldots = \{\Gamma\ i\ ff\ (x \otimes_{(i+1)} y) \mid x\ y.\ x \in X \wedge y \in Y \wedge DD\ (i+1)\ x\ y\}$
by (*smt* (*verit*, *ccfv-threshold*) *h3 Collect-cong icat.st-local*)
also have $\ldots = \Gamma\Gamma\ i\ ff\ (X \star_{(i+1)} Y)$
unfolding *local.iconv-prop* **by** *force*
finally show *?thesis*
by *simp*
qed

lemma *conn-corner3-var*:
assumes $j \neq i \wedge j \neq i + 1$
shows $\Gamma\Gamma\ i\ \alpha\ (\partial\ i\ \beta\ x \odot_j \partial\ i\ \gamma\ y) = \Gamma\ i\ \alpha\ (\partial\ i\ \beta\ x) \odot_j \Gamma\ i\ \alpha\ (\partial\ i\ \gamma\ y)$
by (*smt* (*z3*) *assms empty-is-image image-insert local.conn-corner3 local.conn-face1 local.conn-face3 local.face-compat-var local.iDst local.icat.pcomp-def-var4 local.locality local.pcomp-face-func-DD*)

lemma *conn-corner3-lift*:
assumes $j \neq i$
and $j \neq i + 1$
and *FFx i X*
and *FFx i Y*
shows $\Gamma\Gamma\ i\ \alpha\ (X \star_j Y) = \Gamma\Gamma\ i\ \alpha\ X \star_j \Gamma\Gamma\ i\ \alpha\ Y$
proof−
have *h*: $\forall x \in X.\ \forall y \in Y.\ DD\ j\ (\Gamma\ i\ \alpha\ x)\ (\Gamma\ i\ \alpha\ y) = DD\ j\ x\ y$
by (*metis assms icat.st-local local.conn-face1 local.conn-face3 local.face-comm-var*)
have $\Gamma\Gamma\ i\ \alpha\ X \star_j \Gamma\Gamma\ i\ \alpha\ Y = \{\Gamma\ i\ \alpha\ x \otimes_j \Gamma\ i\ \alpha\ y \mid x\ y.\ x \in X \wedge y \in Y \wedge DD$

$j\ (\Gamma\ i\ \alpha\ x)\ (\Gamma\ i\ \alpha\ y)\}$
unfolding *local.iconv-prop* **by** *force*
also have $\ldots = \{\Gamma\ i\ \alpha\ x \otimes_j \Gamma\ i\ \alpha\ y \mid x\ y.\ x \in X \wedge y \in Y \wedge DD\ j\ x\ y\}$
using h **by** *force*
also have $\ldots = \{\Gamma\ i\ \alpha\ (x \otimes_j y) \mid x\ y.\ x \in X \wedge y \in Y \wedge DD\ j\ x\ y\}$
using *conn-corner3 assms* **by** *fastforce*
also have $\ldots = \Gamma\Gamma\ i\ \alpha\ (X \star_j Y)$
unfolding *local.iconv-prop* **by** *force*
finally show *?thesis*
by *simp*
qed

lemma *conn-face5* [*simp*]: $\partial\ (j + 1)\ \alpha\ (\Gamma\ j\ (\neg\alpha)\ (\partial\ j\ \gamma\ x)) = \partial\ (j + 1)\ \alpha\ (\partial\ j\ \gamma\ x)$
by (*smt* (*verit*, *ccfv-SIG*) *icid.s-absorb-var local.conn-corner1-lift-aux local.conn-zigzag1-var local.face-compat-var local.icid.ts-msg.src-comp-cond local.is-absorb singleton-insert-inj-eq′*)

lemma *conn-inv-sym-braid*:
assumes *diffSup i j 2*
shows $\Gamma\ i\ \alpha\ (\vartheta\ j\ (\partial\ i\ \beta\ (\partial\ (j + 1)\ \gamma\ x))) = \vartheta\ j\ (\Gamma\ i\ \alpha\ (\partial\ i\ \beta\ (\partial\ (j + 1)\ \gamma\ x)))$
by (*smt* (*z3*) *add-diff-cancel-left′ assms diff-add-0 diff-is-0-eq′ local.conn-face3 local.conn-sym-braid local.face-comm-var local.face-compat-var local.inv-sym-face2 local.inv-sym-sym-var1 local.inv-sym-type-var local.sym-inv-sym nat-1-add-1 nle-le rel-simps*(*28*))

lemma *conn-corner4*: $\Gamma\Gamma\ i\ tt\ (\partial\ i\ \alpha\ x \odot_{(i + 1)} \partial\ i\ \beta\ y) = (\Gamma\ i\ tt\ (\partial\ i\ \alpha\ x) \odot_i \partial\ i\ \alpha\ x) \star_{(i + 1)} (\sigma\ i\ (\partial\ i\ \alpha\ x) \odot_i \Gamma\ i\ tt\ (\partial\ i\ \beta\ y))$
proof (*cases DD* $(i + 1)\ (\partial\ i\ \alpha\ x)\ (\partial\ i\ \beta\ y)$)
case *True*
have *h1*: $\partial\partial\ (i+1)\ tt\ (\Gamma\ i\ tt\ (\partial\ i\ \alpha\ x) \odot_i \partial\ i\ \alpha\ x) = \{\sigma\ i\ (\partial\ i\ \alpha\ x)\}$
by (*metis image-empty image-insert local.conn-face1 local.conn-face2 local.face-compat-var local.it-absorb*)
have $\partial\ (i+1)\ tt\ (\partial\ i\ \alpha\ x) = \partial\ (i+1)\ ff\ (\partial\ i\ \beta\ y)$
using *True local.iDst* **by** *simp*
hence *h2*: $\partial\partial\ (i+1)\ ff\ (\sigma\ i\ (\partial\ i\ \alpha\ x) \odot_i \Gamma\ i\ tt\ (\partial\ i\ \beta\ y)) = \{\sigma\ i\ (\partial\ i\ \alpha\ x)\}$
by (*smt* (*z3*) *add-eq-self-zero conn-face4 conn-face5 icat.st-local image-is-empty local.comp-face-func local.conn-face2 local.face-comm-var local.face-compat-var local.it-absorb subset-singletonD zero-neq-one*)
hence $\partial\partial\ (i+1)\ tt\ (\Gamma\ i\ tt\ (\partial\ i\ \alpha\ x) \odot_i \partial\ i\ \alpha\ x) \cap \partial\partial\ (i+1)\ ff\ (\sigma\ i\ (\partial\ i\ \alpha\ x) \odot_i \Gamma\ i\ tt\ (\partial\ i\ \beta\ y)) \neq \{\}$
using *h1* **by** *simp*
thus *?thesis*
by (*smt* (*z3*) *True add-cancel-right-right dual-order.eq-iff empty-is-image h1 h2 icat.locality-lifting local.conn-corner1-var local.icat.pcomp-def-var4 local.interchange-var multimagma.conv-atom not-one-le-zero*)
next
case *False*
thus *?thesis*
by (*smt* (*z3*) *Union-empty add-eq-self-zero dual-order.eq-iff icat.st-local im-*

age-empty local.conn-face4 local.conn-face2 local.face-comm-var local.face-compat-var multimagma.conv-distl not-one-le-zero)
qed

lemma *conn-corner5*: $\Gamma\Gamma\ i\ ff\ (\partial\ i\ \alpha\ x\ \odot_{(i\ +\ 1)}\ \partial\ i\ \beta\ y) = (\Gamma\ i\ ff\ (\partial\ i\ \alpha\ x)\ \odot_i\ \sigma\ i\ (\partial\ i\ \beta\ y))\ \star_{(i\ +\ 1)}\ (\partial\ i\ \beta\ y\ \odot_i\ \Gamma\ i\ ff\ (\partial\ i\ \beta\ y))$
proof (*cases DD* $(i\ +\ 1)\ (\partial\ i\ \alpha\ x)\ (\partial\ i\ \beta\ y)$)
case *True*
have *h1*: $\partial\partial\ (i{+}1)\ ff\ (\partial\ i\ \beta\ y\ \odot_i\ \Gamma\ i\ ff\ (\partial\ i\ \beta\ y)) = \{\sigma\ i\ (\partial\ i\ \beta\ y)\}$
by (*metis image-empty image-insert local.conn-face1 local.conn-face2 local.face-compat-var local.is-absorb*)
have $\partial\ (i{+}1)\ tt\ (\partial\ i\ \alpha\ x) = \partial\ (i{+}1)\ ff\ (\partial\ i\ \beta\ y)$
using *True local.iDst* **by** *simp*
hence *h2*: $\partial\partial\ (i{+}1)\ tt\ (\Gamma\ i\ ff\ (\partial\ i\ \alpha\ x)\ \odot_i\ \sigma\ i\ (\partial\ i\ \beta\ y)) = \{\sigma\ i\ (\partial\ i\ \beta\ y)\}$
by (*smt* (*z3*) *conn-face4 conn-face5 h1 icat.st-local image-insert image-is-empty local.comp-face-func local.conn-face2 local.face-comm-var local.face-compat-var local.icat.functionality-lem-var local.it-absorb subset-singletonD*)
hence $\partial\partial\ (i{+}1)\ ff\ (\partial\ i\ \beta\ y\ \odot_i\ \Gamma\ i\ ff\ (\partial\ i\ \beta\ y)) \cap \partial\partial\ (i{+}1)\ tt\ (\Gamma\ i\ ff\ (\partial\ i\ \alpha\ x)\ \odot_i\ \sigma\ i\ (\partial\ i\ \beta\ y)) \neq \{\}$
using *h1* **by** *simp*
thus *?thesis*
by (*smt* (*z3*) *True add-cancel-right-right dual-order.eq-iff empty-is-image h1 h2 icat.locality-lifting local.conn-corner2-var local.icat.functionality-lem-var local.interchange-var multimagma.conv-atom not-one-le-zero*)
next
case *False*
thus *?thesis*
by (*smt* (*z3*) *UN-empty add-cancel-right-right dual-order.eq-iff image-empty local.conn-face2 local.face-compat-var local.pcomp-face-func-DD local.sym-func2-DD local.sym-type-var multimagma.conv-def not-one-le-zero*)
qed

lemma *conn-corner3-alt*: $j \neq i \Longrightarrow\ j \neq i + 1 \Longrightarrow \Gamma\Gamma\ i\ \alpha\ (\partial\ i\ \beta\ x\ \odot_j\ \partial\ i\ \gamma\ y) = \Gamma\ i\ \alpha\ (\partial\ i\ \beta\ x)\ \odot_j\ \Gamma\ i\ \alpha\ (\partial\ i\ \gamma\ y)$
by (*simp add*: *local.conn-corner3-var*)

lemma *conn-shift2*:
assumes *fFx i x*
and *fFx* $(i\ +\ 2)\ x$
shows $\vartheta\ i\ (\vartheta\ (i\ +\ 1)\ (\Gamma\ i\ \alpha\ x)) = \Gamma\ (i\ +\ 1)\ \alpha\ (\vartheta\ (i\ +\ 1)\ x)$

proof−
have $\Gamma\ i\ \alpha\ x = \sigma\ (i\ +\ 1)\ (\sigma\ i\ (\Gamma\ (i\ +\ 1)\ \alpha\ (\vartheta\ (i\ +\ 1)\ x)))$
using *assms local.conn-shift local.inv-sym-face2 local.inv-sym-face3-simp local.sym-inv-sym* **by** *simp*
thus *?thesis*
using *assms local.conn-face3 local.inv-sym-face2 local.inv-sym-sym local.inv-sym-type-var local.sym-type-var* **by** *simp*
qed

end

end

5 Cubical $(\omega, 0)$-Categories with Connections

theory *CubicalOmegaZeroCategoriesConnections*
imports *CubicalCategoriesConnections*

begin

All categories considered in this component are single-set categories.

First we define shell-invertibility.

abbreviation (**in** *cubical-omega-category-connections*) *ri-inv i x y* ≡ (*DD i x y* ∧ *DD i y x* ∧ *x* ⊗*i y* = ∂ *i ff x* ∧ *y* ⊗*i x* = ∂ *i tt x*)

abbreviation (**in** *cubical-omega-category-connections*) *ri-inv-shell k i x* ≡ (∀ *j α*. *j* + *1* ≤ *k* ∧ *j* ≠ *i* ⟶ (∃ *y*. *ri-inv i* (∂ *j α x*) *y*))

Next we define the class of cubical $(\omega, 0)$-categories with connections.

class *cubical-omega-zero-category-connections* = *cubical-omega-category-connections* +
assumes *ri-inv*: *k* ≥ *1* ⟹ *i* ≤ *k* − *1* ⟹ *dim-bound k x* ⟹ *ri-inv-shell k i x* ⟹ ∃ *y*. *ri-inv i x y*

begin

Finally, to show our axiomatisation at work we prove Proposition 2.4.7 from our companion paper, namely that every cell in an $(\omega, 0)$-category is ri-invertible for each natural number i. This requires some background theory engineering.

lemma *ri-inv-fix*:
assumes *fFx i x*
shows ∃ *y*. *ri-inv i x y*
by (*metis assms icat.st-local local.face-compat-var local.icat.sscatml.l0-absorb*)

lemma *ri-inv2*:
assumes *k* ≥ *1*
assumes *dim-bound k x*
and *ri-inv-shell k i x*
shows ∃ *y*. *ri-inv i x y*
proof (*cases i* ≤ *k* − *1*)
case *True*
thus *?thesis*
using *assms local.ri-inv* **by** *simp*
next

case *False*
hence *fFx i x*
using *assms*(*2*) **by** *fastforce*
thus *?thesis*
using *ri-inv-fix* **by** *simp*
qed

lemma *ri-inv3*:
assumes *dim-bound k x*
and *ri-inv-shell k i x*
shows ∃ *y*. *ri-inv i x y*
proof (*cases k* = *0*)
case *True*
thus *?thesis*
using *assms*(*1*) *less-eq-nat.simps*(*1*) *ri-inv-fix* **by** *simp*
next
case *False*
hence *k* ≥ *1*
by *simp*
thus *?thesis*
using *assms ri-inv2* **by** *simp*
qed

lemma *ri-unique*: (∃ *y*. *ri-inv i x y*) = (∃!*y*. *ri-inv i x y*)
by (*metis local.icat.pcomp-assoc local.icat.sscatml.assoc-defined local.icat.sscatml.l0-absorb local.icat.sts-msg.st-local local.pcomp-uface*)

lemma *ri-unique-var*: *ri-inv i x y* ⟹ *ri-inv i x z* ⟹ *y* = *z*
using *ri-unique* **by** *fastforce*

definition *ri i x* = (*THE y*. *ri-inv i x y*)

lemma *ri-inv-ri*: *ri-inv i x y* ⟹ (*y* = *ri i x*)
proof−
assume *a*: *ri-inv i x y*
hence ∃!*y*. *ri-inv i x y*
using *ri-unique* **by** *blast*
thus *y* = *ri i x*
unfolding *ri-def*
by (*smt* (*verit*, *ccfv-threshold*) *a the-equality*)
qed

lemma *ri-def-prop*:
assumes *dim-bound k x*
and *ri-inv-shell k i x*
shows *DD i x* (*ri i x*) ∧ *DD i* (*ri i x*) *x* ∧ *x* ⊗*ᵢ* (*ri i x*) = ∂ *i ff x* ∧ (*ri i x*) ⊗*ᵢ x*
= ∂ *i tt x*
proof−
have ∃ *y*. *ri-inv i x y*

using *assms ri-inv3* **by** *blast*
hence $\exists!y.\ DD\ i\ x\ y \wedge DD\ i\ y\ x \wedge x \otimes_i y = \partial\ i\ ff\ x \wedge y \otimes_i x = \partial\ i\ tt\ x$
by (*simp add*: *ri-unique*)
hence $DD\ i\ x\ (ri\ i\ x) \wedge DD\ i\ (ri\ i\ x)\ x \wedge x \otimes_i (ri\ i\ x) = \partial\ i\ ff\ x \wedge (ri\ i\ x) \otimes_i x = \partial\ i\ tt\ x$
unfolding *ri-def* **by** (*smt* (*verit*, *del-insts*) *theI'*)
thus *?thesis*
by *simp*
qed

lemma *ri-right*:
assumes *dim-bound k x*
and *ri-inv-shell k i x*
shows $x \otimes_i ri\ i\ x = \partial\ i\ ff\ x$
using *assms ri-def-prop* **by** *simp*

lemma *ri-right-set*:
assumes *dim-bound k x*
and *ri-inv-shell k i x*
shows $x \odot_i ri\ i\ x = \{\partial\ i\ ff\ x\}$
using *assms local.icat.pcomp-def-var3 ri-def-prop* **by** *blast*

lemma *ri-left*:
assumes *dim-bound k x*
and *ri-inv-shell k i x*
shows $ri\ i\ x \otimes_i x = \partial\ i\ tt\ x$
using *assms ri-def-prop* **by** *simp*

lemma *ri-left-set*:
assumes *dim-bound k x*
and *ri-inv-shell k i x*
shows $ri\ i\ x \odot_i x = \{\partial\ i\ tt\ x\}$
using *assms local.icat.pcomp-def-var3 ri-def-prop* **by** *blast*

lemma *dim-face*: *dim-bound k x* $\Longrightarrow$ *dim-bound k* $(\partial\ i\ \alpha\ x)$
by (*metis local.double-fix-prop local.face-comm-var*)

lemma *dim-ri-inv*:
assumes *dim-bound k x*
and *ri-inv i x y*
shows *dim-bound k y*
proof−
{fix $l\ \alpha$
assume *ha*: $l \geq k$
have *h1*: $DD\ i\ x\ (\partial\ l\ \alpha\ y)$
by (*smt* (*verit*, *ccfv-threshold*) *assms ha icat.st-local icid.s-absorb-var3 local.pcomp-face-func-DD*)
have *h2*: $DD\ i\ (\partial\ l\ \alpha\ y)\ x$
by (*metis* (*full-types*) *assms ha icid.ts-compat local.iDst local.locality local.pcomp-face-func-DD*)

```
  have ∂ l α (x ⊗ᵢ y) = ∂ l α x ⊗ᵢ ∂ l α y
   by (metis ha assms(1) assms(2) local.fFx-prop local.face-func local.icat.sscatml.r0-absorb
local.pcomp-uface)
  hence h3: ∂ l α (x ⊗ᵢ y) = x ⊗ᵢ ∂ l α y
    by (metis assms(1) ha local.face-compat-var)
  have ∂ l α (y ⊗ᵢ x) = ∂ l α y ⊗ᵢ ∂ l α x
   by (metis ha assms(1) assms(2) local.fFx-prop local.face-func local.icat.sscatml.r0-absorb
local.pcomp-uface)
  hence ∂ l α (y ⊗ᵢ x) = ∂ l α y ⊗ᵢ x
    by (metis assms(1) ha local.face-compat-var)
  hence ri-inv i x (∂ l α y)
    by (metis assms(1,2) h1 h2 h3 ha local.face-comm-var local.face-compat-var)
  hence ∂ l α y = y
    using ri-unique-var assms(2) by blast}
  thus ?thesis
    by simp
qed

lemma every-dim-k-ri-inv:
  assumes dim-bound k x
  shows ∀ i. ∃ y. ri-inv i x y using ‹dim-bound k x›
proof (induct k arbitrary: x)
  case 0
  thus ?case
    using ri-inv-fix by simp
next
  case (Suc k)
  {fix i
    have ∃ y. ri-inv i x y
    proof (cases Suc k ≤ i)
      case True
      thus ?thesis
        using Suc.prems ri-inv-fix by simp
    next
      case False
      {fix j α
        assume h: j ≤ k ∧ j ≠ i
        hence a: dim-bound k (Σ j (k − j) (∂ j α x))
       by (smt (z3) Suc.prems antisym-conv2 le-add-diff-inverse local.face-comm-var
local.face-compat-var local.symcomp-face2 local.symcomp-type-var nle-le not-less-eq-eq)
        have ∃ y. ri-inv i (∂ j α x) y
        proof (cases j < i)
          case True
          obtain y where b: ri-inv (i − 1) (Σ j (k − j) (∂ j α x)) y
            using Suc.hyps a by force
          have c: dim-bound k y
            apply (rule dim-ri-inv[where x = Σ j (k − j) (∂ j α x)])
            using a b by simp-all
          hence d: DD i (∂ j α x) (Θ j (k − j) y)
```

by (*smt* (*verit*) *False True a b h icid.ts-compat le-add-diff-inverse local.iDst local.icid.stopp.ts-compat local.inv-symcomp-face1 local.inv-symcomp-symcomp local.locality nle-le not-less-eq-eq*)

hence *e*: *DD i* (Θ *j* (*k* − *j*) *y*) (∂ *j* α *x*)

by (*smt* (*verit*) *False True b c dual-order.refl h icid.ts-compat le-add-diff-inverse local.iDst local.icid.stopp.ts-compat local.inv-symcomp-face1 local.inv-symcomp-symcomp local.locality local.symcomp-type-var not-less-eq-eq*)

have *f*: ∂ *j* α *x* ⊗$_i$ Θ *j* (*k* − *j*) *y* = Θ *j* (*k* − *j*) (Σ *j* (*k* − *j*) (∂ *j* α *x*) ⊗$_{(i\ -\ 1)}$ *y*)

apply (*subst inv-symcomp-comp4*)

using *True local.symcomp-type-var1 c False One-nat-def b local.face-compat-var local.inv-symcomp-symcomp a* **by** *auto*

have Θ *j* (*k* − *j*) *y* ⊗$_i$ ∂ *j* α *x* = Θ *j* (*k* − *j*) (*y* ⊗$_{(i\ -\ 1)}$ Σ *j* (*k* − *j*) (∂ *j* α *x*))

apply (*subst inv-symcomp-comp4*)

using *True local.symcomp-type-var1 b c False local.face-compat-var local.inv-symcomp-symcomp a* **by** *simp-all*

thus *?thesis*

by (*metis False True b c d dual-order.refl e f h le-add-diff-inverse local.icid.stopp.Dst local.inv-symcomp-face1 not-less-eq-eq*)

next

case *False*

obtain *y* **where** *b*: *ri-inv i* (Σ *j* (*k* − *j*) (∂ *j* α *x*)) *y*

using *Suc.hyps a* **by** *presburger*

have *c*: *dim-bound k y*

apply (*rule dim-ri-inv*[**where** *x* = Σ *j* (*k* − *j*) (∂ *j* α *x*)])

using *a b* **by** *simp-all*

hence *d*: *DD i* (∂ *j* α *x*) (Θ *j* (*k* − *j*) *y*)

by (*smt* (*verit*) *False a b dual-order.refl h icid.ts-compat le-add-diff-inverse linorder-neqE-nat local.iDst local.icid.stopp.ts-compat local.inv-symcomp-face2 local.inv-symcomp-symcomp local.locality*)

hence *e*: *DD i* (Θ *j* (*k* − *j*) *y*) (∂ *j* α *x*)

by (*smt* (*z3*) *False add.commute b c dual-order.refl h le-add-diff-inverse2 linorder-neqE-nat local.face-comm-var local.face-compat-var local.iDst local.inv-symcomp-face2 local.inv-symcomp-symcomp local.locality local.symcomp-face2*)

have *f*: ∂ *j* α *x* ⊗$_i$ Θ *j* (*k* − *j*) *y* = Θ *j* (*k* − *j*) (Σ *j* (*k* − *j*) (∂ *j* α *x*) ⊗$_i$ *y*)

apply (*subst inv-symcomp-comp2*)

using *False h nat-neq-iff local.symcomp-type-var1 b c a local.face-compat-var local.inv-symcomp-symcomp* **by** *simp-all*

have Θ *j* (*k* − *j*) *y* ⊗$_i$ ∂ *j* α *x* = Θ *j* (*k* − *j*) (*y* ⊗$_i$ Σ *j* (*k* − *j*) (∂ *j* α *x*))

apply (*subst inv-symcomp-comp2*)

using *False h a b c local.inv-symcomp-symcomp* **by** *simp-all*

thus *?thesis*

by (*metis False antisym-conv3 b d e f h local.face-compat-var local.inv-symcomp-face2 local.inv-symcomp-symcomp local.symcomp-type-var1*)

qed}

thus *?thesis*

apply (*intro ri-inv*[**where** *k* = *k* + *1*])

```
      using False Suc.prems by simp-all
    qed}
  thus ?case
    by simp
qed
```

We can now show that every cell is ri-invertible in every direction i.

```
lemma every-ri-inv: ∃ y. ri-inv i x y
  using every-dim-k-ri-inv local.fin-fix by blast

end

end
```

References

[1] P. Malbos, T. Massacrier, and G. Struth. Single-set cubical categories and their formalisation with a proof assistant. 2024. http://arxiv.org/abs/2401.10553v1.

[2] G. Struth. Catoids, categories, groupoids. *Arch. Formal Proofs*, 2023, 2023.