The Median-Of-Medians Selection Algorithm

Manuel Eberl

November 9, 2026

Abstract

This entry provides an executable functional implementation of the Median-of-Medians algorithm [1] for selecting the k-th smallest element of an unsorted list deterministically in linear time. The size bounds for the recursive call that lead to the linear upper bound on the run-time of the algorithm are also proven.

Contents

1 The Median-of-Medians Selection Algorithm **1**
1.1 Some facts about lists and multisets 1
1.2 The dual order type 2
1.3 Chopping a list into equal-sized sublists 3
1.4 k-th order statistics and medians 5
1.5 A more liberal notion of medians 7
1.6 Properties of a median-of-medians 9
1.7 The recursive step 13
1.8 Medians of lists of length at most 5 15
1.9 Median-of-medians selection algorithm 17

1 The Median-of-Medians Selection Algorithm

theory *Median-Of-Medians-Selection*
imports *Complex-Main HOL−Library.Multiset*
begin

1.1 Some facts about lists and multisets

lemma *sorted-filter-less-subset-take*:
assumes *sorted xs i < length xs*
shows $\{\#\ x \in\#\ mset\ xs.\ x < xs\ !\ i\ \#\} \subseteq\#\ mset\ (take\ i\ xs)$
using *assms*
proof (*induction xs arbitrary*: *i rule*: *list.induct*)
case (*Cons x xs i*)
show *?case*

proof (*cases i*)
case *0*
thus *?thesis* **using** *Cons.prems* **by** (*auto simp*: *filter-mset-eq-mempty-iff*)
next
case (*Suc i′*)
have {#*y* ∈# *mset* (*x* # *xs*). *y* < (*x* # *xs*) ! *i*#} ⊆# *add-mset x* {#*y* ∈# *mset xs*. *y* < *xs* ! *i′*#}
using *Suc Cons.prems* **by** (*auto*)
also have ... ⊆# *add-mset x* (*mset* (*take i′ xs*))
unfolding *mset-subset-eq-add-mset-cancel* **using** *Cons.prems Suc*
by (*intro Cons.IH*) (*auto*)
also have ... = *mset* (*take i* (*x* # *xs*)) **by** (*simp add*: *Suc*)
finally show *?thesis* **.**
qed
qed *auto*

lemma *sorted-filter-greater-subset-drop*:
assumes *sorted xs i* < *length xs*
shows {# *x* ∈# *mset xs*. *x* > *xs* ! *i* #} ⊆# *mset* (*drop* (*Suc i*) *xs*)
using *assms*
proof (*induction xs arbitrary*: *i rule*: *list.induct*)
case (*Cons x xs i*)
show *?case*
proof (*cases i*)
case *0*
thus *?thesis* **by** (*auto simp*: *sorted-append filter-mset-eq-mempty-iff*)
next
case (*Suc i′*)
have {#*y* ∈# *mset* (*x* # *xs*). *y* > (*x* # *xs*) ! *i*#} ⊆# {#*y* ∈# *mset xs*. *y* > *xs* ! *i′*#}
using *Suc Cons.prems* **by** (*auto simp*: *set-conv-nth*)
also have ... ⊆# *mset* (*drop* (*Suc i′*) *xs*)
using *Cons.prems Suc* **by** (*intro Cons.IH*) (*auto*)
also have ... = *mset* (*drop* (*Suc i*) (*x* # *xs*)) **by** (*simp add*: *Suc*)
finally show *?thesis* **.**
qed
qed *auto*

1.2 The dual order type

The following type is a copy of a given ordered base type, but with the ordering reversed. This will be useful later because we can do some of our reasoning simply by symmetry.

typedef *'a dual-ord* = *UNIV* :: *'a set* **morphisms** *of-dual-ord to-dual-ord*
by *auto*

setup-lifting *type-definition-dual-ord*

instantiation *dual-ord* :: (*ord*) *ord*

begin

lift-definition *less-eq-dual-ord* :: *'a dual-ord* ⇒ *'a dual-ord* ⇒ *bool* **is**
  λa b :: 'a. a ≥ b **.**

lift-definition *less-dual-ord* :: *'a dual-ord* ⇒ *'a dual-ord* ⇒ *bool* **is**
  λa b :: 'a. a > b **.**

instance ..
end

instance *dual-ord* :: (*preorder*) *preorder*
  by *standard* (*transfer*; *force simp*: *less-le-not-le intro*: *order-trans*)+

instance *dual-ord* :: (*linorder*) *linorder*
  by *standard* (*transfer*; *force simp*: *not-le*)+

1.3 Chopping a list into equal-sized sublists

function *chop* :: *nat* ⇒ *'a list* ⇒ *'a list list* **where**
  chop n [] = []
| *chop 0 xs = []*
| *n > 0 ⟹ xs ≠ [] ⟹ chop n xs = take n xs # chop n (drop n xs)*
  by *force*+
termination by *lexicographic-order*

context
  includes *lifting-syntax*
begin

lemma *chop-transfer* [*transfer-rule*]:
  ((=) ===> *list-all2 R* ===> *list-all2* (*list-all2 R*)) *chop chop*
proof (*intro rel-funI*)
  fix *m n* ::*nat* **and** *xs* :: *'a list* **and** *ys* :: *'b list*
  assume *m = n list-all2 R xs ys*
  from *this*(*2*) **have** *list-all2* (*list-all2 R*) (*chop n xs*) (*chop n ys*)
  proof (*induction n xs arbitrary*: *ys rule*: *chop.induct*)
    case (*3 n xs ys*)
    hence *ys ≠ []* **by** *auto*
    with *3* **show** *?case* **by** *auto*
  qed *auto*
  with ‹*m = n*› **show** *list-all2* (*list-all2 R*) (*chop m xs*) (*chop n ys*) **by** *simp*
qed

end

lemma *chop-reduce*: *chop n xs* = (*if n = 0 ∨ xs = [] then [] else take n xs # chop n* (*drop n xs*))
  by (*cases n = 0*; *cases xs = []*) *auto*

lemma *concat-chop* [*simp*]: $n > 0 \Longrightarrow concat\ (chop\ n\ xs) = xs$
by (*induction n xs rule*: *chop.induct*) *auto*

lemma *chop-elem-not-Nil* [*simp*,*dest*]: $ys \in set\ (chop\ n\ xs) \Longrightarrow ys \neq []$
by (*induction n xs rule*: *chop.induct*) (*auto simp*: *eq-commute*[*of* []])

lemma *chop-eq-Nil-iff* [*simp*]: $chop\ n\ xs = [] \longleftrightarrow n = 0 \vee xs = []$
by (*induction n xs rule*: *chop.induct*) *auto*

lemma *chop-ge-length-eq*: $n > 0 \Longrightarrow xs \neq [] \Longrightarrow n \geq length\ xs \Longrightarrow chop\ n\ xs = [xs]$
by *simp*

lemma *length-chop-part-le*: $ys \in set\ (chop\ n\ xs) \Longrightarrow length\ ys \leq n$
by (*induction n xs rule*: *chop.induct*) *auto*

lemma *length-nth-chop*:
assumes $i < length\ (chop\ n\ xs)$
shows $length\ (chop\ n\ xs\ !\ i) =$
$(if\ i = length\ (chop\ n\ xs) - 1 \wedge \neg n\ dvd\ length\ xs\ then\ length\ xs\ mod\ n\ else\ n)$
proof (*cases* $n = 0$)
case *False*
thus *?thesis*
using *assms*
proof (*induction n xs arbitrary*: *i rule*: *chop.induct*)
case (*3 n xs i*)
show *?case*
proof (*cases i*)
case *0*
thus *?thesis* **using** *3.prems*
by (*cases length xs* $< n$) (*auto simp*: *le-Suc-eq dest*: *dvd-imp-le*)
next
case [*simp*]: (*Suc i'*)
with *3.prems* **have** [*simp*]: $xs \neq []$ **by** *auto*
with *3.prems* **have** $*$: $length\ xs > n$ **by** (*cases length xs* $\leq n$) *simp-all*
with *3.prems* **have** $chop\ n\ xs\ !\ i = chop\ n\ (drop\ n\ xs)\ !\ i'$ **by** *simp*
also have $length\ \ldots = (if\ i = length\ (chop\ n\ xs) - 1 \wedge \neg\ n\ dvd\ (length\ xs - n)$
$then\ (length\ xs - n)\ mod\ n\ else\ n)$
by (*subst 3.IH*) (*use Suc 3.prems* **in** *auto*)
also have $n\ dvd\ (length\ xs - n) \longleftrightarrow n\ dvd\ length\ xs$
using $*$ **by** (*subst dvd-minus-self*) *auto*
also have $(length\ xs - n)\ mod\ n = length\ xs\ mod\ n$
using $*$ **by** (*subst le-mod-geq* [*symmetric*]) *auto*
finally show *?thesis* **.**
qed
qed *auto*

qed (*insert assms*, *auto*)

lemma *length-chop*:
assumes $n > 0$
shows *length* (*chop n xs*) = *nat* ⌈*length xs* / *n*⌉
using *assms*
proof (*induction n xs rule*: *chop.induct*)
case (*3 n xs*)
show *?case*
proof (*cases length xs* ≥ *n*)
case *False*
hence ⌈*real* (*length xs*) / *real n*⌉ = *1* **using** *3.hyps*
by (*intro ceiling-unique*) *auto*
with *False* **show** *?thesis* **using** *3.prems 3.hyps*
by (*auto simp*: *chop-ge-length-eq not-le*)
next
case *True*
hence *real* (*length xs*) = *real n* + *real* (*length* (*drop n xs*))
by *simp*
also have ... / *real n* = *real* (*length* (*drop n xs*)) / *real n* + *1*
using ‹*n* > *0*› **by** (*simp add*: *divide-simps*)
also have *ceiling* ... = *ceiling* (*real* (*length* (*drop n xs*)) / *real n*) + *1* **by** *simp*
also have *nat* ... = *nat* (*ceiling* (*real* (*length* (*drop n xs*)) / *real n*)) + *nat 1*
by (*intro nat-add-distrib*[*OF order.trans*[*OF - ceiling-mono*[*of 0*]]]) *auto*
also have ... = *length* (*chop n xs*)
using ‹*n* > *0*› *3.hyps* **by** (*subst 3.IH* [*symmetric*]) *auto*
finally show *?thesis* **..**
qed
qed *auto*

lemma *sum-msets-chop*: *n* > *0* ⟹ (∑ *ys*←*chop n xs*. *mset ys*) = *mset xs*
by (*subst mset-concat* [*symmetric*]) *simp-all*

lemma *UN-sets-chop*: *n* > *0* ⟹ (⋃ *ys*∈*set* (*chop n xs*). *set ys*) = *set xs*
by (*simp only*: *set-concat* [*symmetric*] *concat-chop*)

lemma *in-set-chopD* [*dest*]:
assumes *x* ∈ *set ys ys* ∈ *set* (*chop d xs*)
shows *x* ∈ *set xs*
proof (*cases d* > *0*)
case *True*
thus *?thesis* **by** (*subst UN-sets-chop* [*symmetric*]) (*use assms* **in** *auto*)
qed (*use assms* **in** *auto*)

1.4 *k*-th order statistics and medians

This returns the *k*-th smallest element of a list. This is also known as the *k*-th order statistic.

definition *select* :: *nat* ⇒ *'a list* ⇒ (*'a* :: *linorder*) **where**

select k xs = sort xs ! k

The median of a list, where, for lists of even lengths, the smaller one is favoured:

definition *median* **where** *median xs = select ((length xs − 1) div 2) xs*

lemma *select-in-set* [*intro*,*simp*]:
assumes *k < length xs*
shows *select k xs ∈ set xs*
proof −
from *assms* **have** *sort xs ! k ∈ set (sort xs)* **by** (*intro nth-mem*) *auto*
also have *set (sort xs) = set xs* **by** *simp*
finally show *?thesis* **by** (*simp add*: *select-def*)
qed

lemma *median-in-set* [*intro*, *simp*]:
assumes *xs ≠ []*
shows *median xs ∈ set xs*
proof −
from *assms* **have** *length xs > 0* **by** *auto*
hence *(length xs − 1) div 2 < length xs* **by** *linarith*
thus *?thesis* **by** (*simp add*: *median-def*)
qed

We show that selection and medians does not depend on the order of the elements:

lemma *sort-cong*: *mset xs = mset ys ⟹ sort xs = sort ys*
by (*rule properties-for-sort*) *simp-all*

lemma *select-cong*:
k = k′ ⟹ mset xs = mset xs′ ⟹ select k xs = select k′ xs′
by (*auto simp*: *select-def dest*: *sort-cong*)

lemma *median-cong*: *mset xs = mset xs′ ⟹ median xs = median xs′*
unfolding *median-def* **by** (*intro select-cong*) (*auto dest*: *mset-eq-length*)

Selection distributes over appending lists under certain conditions:

lemma *sort-append*:
assumes *⋀x y. x ∈ set xs ⟹ y ∈ set ys ⟹ x ≤ y*
shows *sort (xs @ ys) = sort xs @ sort ys*
using *assms* **by** (*intro properties-for-sort*) (*auto simp*: *sorted-append*)

lemma *select-append*:
assumes *⋀y z. y ∈ set ys ⟹ z ∈ set zs ⟹ y ≤ z*
shows *k < length ys ⟹ select k (ys @ zs) = select k ys*
k ∈ {length ys..<length ys + length zs} ⟹
select k (ys @ zs) = select (k − length ys) zs
using *assms* **by** (*simp-all add*: *select-def sort-append nth-append*)

lemma *select-append'*:
assumes $\bigwedge y\ z.\ y \in set\ ys \Longrightarrow z \in set\ zs \Longrightarrow y \leq z\ k < length\ ys + length\ zs$
shows *select k (ys @ zs) = (if k < length ys then select k ys else select (k − length ys) zs)*
using *assms* **by** (*auto intro*!: *select-append*)

We can find simple upper bounds for the number of elements that are strictly less than (resp. greater than) the median of a list.

lemma *size-less-than-median*:
size {#y ∈# mset xs. y < median xs#} ≤ (length xs − 1) div 2
proof (*cases xs = []*)
case *False*
hence *length xs > 0* **by** *simp*
hence *(length xs − 1) div 2 < length xs* **by** *linarith*
hence *size {#y ∈# mset (sort xs). y < median xs#} ≤*
size (mset (take ((length xs − 1) div 2) (sort xs)))
unfolding *median-def select-def* **using** *False*
by (*intro size-mset-mono sorted-filter-less-subset-take*) *auto*
thus *?thesis* **using** *False* **by** *simp*
qed *auto*

lemma *size-greater-than-median*:
size {#y ∈# mset xs. y > median xs#} ≤ length xs div 2
proof (*cases xs = []*)
case *False*
hence *length xs > 0* **by** *simp*
hence *(length xs − 1) div 2 < length xs* **by** *linarith*
hence *size {#y ∈# mset (sort xs). y > median xs#} ≤*
size (mset (drop (Suc ((length xs − 1) div 2)) (sort xs)))
unfolding *median-def select-def* **using** *False*
by (*intro size-mset-mono sorted-filter-greater-subset-drop*) *auto*
hence *size (filter-mset (λy. y > median xs) (mset xs)) ≤*
length xs − Suc ((length xs − 1) div 2) **by** *simp*
also have *... = length xs div 2* **by** *linarith*
finally show *?thesis* **.**
qed *auto*

1.5 A more liberal notion of medians

We now define a more relaxed version of being "a median" as opposed to being "*the* median". A value is a median if at most half the values in the list are strictly smaller than it and at most half are strictly greater. Note that, by this definition, the median does not even have to be in the list itself.

definition *is-median* :: *'a :: linorder ⇒ 'a list ⇒ bool* **where**
is-median x xs ⟷ length (filter (λy. y < x) xs) ≤ length xs div 2 ∧
length (filter (λy. y > x) xs) ≤ length xs div 2

We set up some transfer rules for *is-median*. In particular, we have a rule that shows that something is a median for a list iff it is a median on that list w. r. t. the dual order, which will later allow us to argue by symmetry.

context
  includes *lifting-syntax*
begin
lemma *transfer-is-median* [*transfer-rule*]:
  assumes [*transfer-rule*]: (*r* ===> *r* ===> (=)) (<) (<)
  shows (*r* ===> *list-all2 r* ===> (=)) *is-median is-median*
  unfolding *is-median-def* **by** *transfer-prover*

lemma *list-all2-eq-fun-conv-map*: *list-all2* (λ*x y*. *x* = *f y*) *xs ys* ⟷ *xs* = *map f ys*
proof
  assume *list-all2* (λ*x y*. *x* = *f y*) *xs ys*
  thus *xs* = *map f ys* **by** *induction auto*
next
  assume *xs* = *map f ys*
  moreover have *list-all2* (λ*x y*. *x* = *f y*) (*map f ys*) *ys*
    by (*induction ys*) *auto*
  ultimately show *list-all2* (λ*x y*. *x* = *f y*) *xs ys* **by** *simp*
qed

lemma *transfer-is-median-dual-ord* [*transfer-rule*]:
  (*pcr-dual-ord* (=) ===> *list-all2* (*pcr-dual-ord* (=)) ===> (=)) *is-median is-median*
  by (*auto simp*: *pcr-dual-ord-def cr-dual-ord-def OO-def rel-fun-def is-median-def*
      list-all2-eq-fun-conv-map o-def less-dual-ord.rep-eq)
end

lemma *is-median-to-dual-ord-iff* [*simp*]:
  is-median (*to-dual-ord x*) (*map to-dual-ord xs*) ⟷ *is-median x xs*
  unfolding *is-median-def* **by** *transfer auto*

The following is an obviously equivalent definition of *is-median* in terms of multisets that is occasionally nicer to use.

lemma *is-median-altdef*:
  is-median x xs ⟷ *size* (*filter-mset* (λ*y*. *y* < *x*) (*mset xs*)) ≤ *length xs div 2* ∧
                size (*filter-mset* (λ*y*. *y* > *x*) (*mset xs*)) ≤ *length xs div 2*
proof −
  have ∗: *length* (*filter P xs*) = *size* (*filter-mset P* (*mset xs*)) **for** *P* **and** *xs* :: *'a list*
    by (*simp flip*: *mset-filter*)
  show *?thesis* **by** (*simp only*: *is-median-def* ∗)
qed

lemma *is-median-cong*:
  assumes *x* = *y mset xs* = *mset ys*
  shows *is-median x xs* ⟷ *is-median y ys*

unfolding *is-median-altdef* **by** (*simp only*: *assms mset-eq-length*[*OF assms*(*2*)])

If an element is the median of a list of odd length, we can add any element to the list and the element is still a median. Conversely, if we want to compute a median of a list with even length n, we can simply drop one element and reduce the problem to a median of a list of size $n - 1$.

lemma *is-median-Cons-odd*:
assumes *is-median x xs* **and** *odd* (*length xs*)
shows *is-median x* (*y # xs*)
using *assms* **by** (*auto simp*: *is-median-def*)

And, of course, *the* median is a median.

lemma *is-median-median* [*simp*,*intro*]: *is-median* (*median xs*) *xs*
using *size-less-than-median*[*of xs*] *size-greater-than-median*[*of xs*]
unfolding *is-median-def size-mset* [*symmetric*] *mset-filter* **by** *linarith*+

1.6 Properties of a median-of-medians

We can now bound the number of list elements that can be strictly smaller than a median-of-medians of a chopped-up list (where each part has length d except for the last one, which can also be shorter).

The core argument is that at least roughly half of the medians of the sublists are greater or equal to the median-of-medians, and about $\frac{d}{2}$ elements in each such sublist are greater than or equal to their median and thereby also than the median-of-medians.

lemma *size-less-than-median-of-medians-strong*:
fixes *xs* :: *'a* :: *linorder list* **and** *d* :: *nat*
assumes *d*: *d > 0*
assumes *median*: $\bigwedge$*xs*. *xs* $\neq$ [] $\Longrightarrow$ *length xs* $\leq$ *d* $\Longrightarrow$ *is-median* (*med xs*) *xs*
assumes *median'*: *is-median x* (*map med* (*chop d xs*))
defines *m* $\equiv$ *length* (*chop d xs*)
shows *size* {#*y* $\in$# *mset xs*. *y* < *x*#} $\leq$ *m* * (*d div 2*) + *m div 2* * ((*d* + *1*) *div 2*)
proof −
define *n* **where** [*simp*]: *n* = *length xs*
— The medians of the sublists
define *M* **where** *M* = *mset* (*map med* (*chop d xs*))
define *YS* **where** *YS* = *mset* (*chop d xs*)
— The sublists with a smaller median than the median-of-medians *x* and the rest.
define *YS1* **where** *YS1* = *filter-mset* (λ*ys*. *med ys* < *x*) (*mset* (*chop d xs*))
define *YS2* **where** *YS2* = *filter-mset* (λ*ys*. ¬(*med ys* < *x*)) (*mset* (*chop d xs*))

— At most roughly half of the lists have a median that is smaller than *M*
have *size YS1* = *size* (*image-mset med YS1*) **by** *simp*
also have *image-mset med YS1* = {#*y* $\in$# *mset* (*map med* (*chop d xs*)). *y* < *x*#}
unfolding *YS1-def* **by** (*subst filter-mset-image-mset* [*symmetric*]) *simp-all*

also have *size ... ≤ (length (map med (chop d xs))) div 2*
using *median'* **unfolding** *is-median-altdef* **by** *simp*
also have *... = m div 2* **by** (*simp add*: *m-def*)
finally have *size-YS1*: *size YS1 ≤ m div 2* **.**

have *m = size (mset (chop d xs))* **by** (*simp add*: *m-def*)
also have *mset (chop d xs) = YS1 + YS2* **unfolding** *YS1-def YS2-def*
by (*rule multiset-partition*)
finally have *m-eq*: *m = size YS1 + size YS2* **by** *simp*

— We estimate the number of elements less than x by grouping them into elements coming from *YS1* and elements coming from *YS2*. In the first case, we just note that no more than d elements can come from each sublist, whereas in the second case, we make the analysis more precise and note that only elements that are less than the median of their sublist can be less than x.
have {# *y* ∈# *mset xs. y < x*#} = {# *y* ∈# (∑ *ys*←*chop d xs. mset ys*). *y < x*#} **using** *d*
by (*subst sum-msets-chop*) *simp-all*
also have *... =* (∑ *ys*←*chop d xs.* {#*y* ∈# *mset ys. y < x*#})
by (*subst filter-mset-sum-list*) (*simp add*: *o-def*)
also have *... =* (∑ *ys*∈#*YS.* {#*y* ∈# *mset ys. y < x*#}) **unfolding** *YS-def*
by (*subst sum-mset-sum-list* [*symmetric*]) *simp-all*
also have *YS = YS1 + YS2*
by (*simp add*: *YS-def YS1-def YS2-def not-le*)
also have (∑ *ys*∈#*...* {#*y* ∈# *mset ys. y < x*#}) =
(∑ *ys*∈#*YS1.* {#*y* ∈# *mset ys. y < x*#}) + (∑ *ys*∈#*YS2.* {#*y* ∈# *mset ys. y < x*#})
by *simp*
also have *... ⊆#* (∑ *ys*∈#*YS1. mset ys*) + (∑ *ys*∈#*YS2.* {#*y* ∈# *mset ys. y < med ys*#})
by (*intro subset-mset.add-mono sum-mset-image-mset-mono-strong filter-mset-mono-strong*)
(*auto simp*: *YS2-def*)
finally have {# *y* ∈# *mset xs. y < x* #} ⊆# *...* **.**
hence *size* {# *y* ∈# *mset xs. y < x* #} ≤ *size ...* **by** (*rule size-mset-mono*)

— We do some further straightforward estimations and arrive at our goal.
also have *... =* (∑ *ys*∈#*YS1. length ys*) + (∑ *x*∈#*YS2. size* {#*y* ∈# *mset x. y < med x*#})
by (*simp add*: *multiset.map-comp o-def*)
also have (∑ *ys*∈#*YS1. length ys*) ≤ (∑ *ys*∈#*YS1. d*)
by (*intro sum-mset-mono*) (*auto simp*: *YS1-def length-chop-part-le*)
also have *... = size YS1 * d* **by** *simp*
also have *d*: *d = (d div 2) + ((d + 1) div 2)* **using** *d* **by** *linarith*
have *size YS1 * d = size YS1 * (d div 2) + size YS1 * ((d + 1) div 2)*
by (*subst d*) (*simp add*: *algebra-simps*)
also have (∑ *ys*∈#*YS2. size* {#*y* ∈# *mset ys. y < med ys*#}) ≤
(∑ *ys*∈#*YS2. length ys div 2*)
proof (*intro sum-mset-mono size-less-than-median*, *goal-cases*)
case (*1 ys*)

hence *ys* ≠ [] *length ys* ≤ *d* **by** (*auto simp*: *YS2-def length-chop-part-le*)
from *median*[*OF this*] **show** *?case* **by** (*auto simp*: *is-median-altdef*)
qed
also have ... ≤ (∑ *ys*∈#*YS2*. *d div 2*)
by (*intro sum-mset-mono div-le-mono diff-le-mono*) (*auto simp*: *YS2-def dest*: *length-chop-part-le*)
also have ... = *size YS2* ∗ (*d div 2*) **by** *simp*
also have *size YS1* ∗ (*d div 2*) + *size YS1* ∗ ((*d* + *1*) *div 2*) + ... =
m ∗ (*d div 2*) + *size YS1* ∗ ((*d* + *1*) *div 2*) **by** (*simp add*: *m-eq algebra-simps*)
also have *size YS1* ∗ ((*d* + *1*) *div 2*) ≤ (*m div 2*) ∗ ((*d* + *1*) *div 2*)
by (*intro mult-right-mono size-YS1*) *auto*
finally show *size* {#*y* ∈# *mset xs*. *y* < *x*#} ≤
m ∗ (*d div 2*) + *m div 2* ∗ ((*d* + *1*) *div 2*) **by** *simp-all*
qed

We now focus on the case of an odd chopping size and make some further estimations to simplify the above result a little bit.

theorem *size-less-than-median-of-medians*:
fixes *xs* :: *'a* :: *linorder list* **and** *d* :: *nat*
assumes *median*: ⋀*xs*. *xs* ≠ [] ⟹ *length xs* ≤ *Suc* (*2* ∗ *d*) ⟹ *is-median* (*med xs*) *xs*
assumes *median'*: *is-median x* (*map med* (*chop* (*Suc* (*2*∗*d*)) *xs*))
defines *n* ≡ *length xs*
defines *c* ≡ (*3* ∗ *real d* + *1*) / (*2* ∗ (*2* ∗ *d* + *1*))
shows *size* {#*y* ∈# *mset xs*. *y* < *x*#} ≤ *nat* ⌈*c* ∗ *n*⌉ + (*5* ∗ *d*) *div 2* + *1*
proof (*cases xs* = [])
case *False*
define *m* **where** *m* = *length* (*chop* (*Suc* (*2*∗*d*)) *xs*)

have *real* (*m div 2*) ≤ *real* (*nat* ⌈*real n* / (*1* + *2* ∗ *real d*)⌉) / *2*
by (*simp add*: *m-def length-chop n-def flip*: *of-nat-int-ceiling*)
also have *real* (*nat* ⌈*real n* / (*1* + *2* ∗ *real d*)⌉) =
of-int ⌈*real n* / (*1* + *2* ∗ *real d*)⌉
by (*intro of-nat-nat*) (*auto simp*: *divide-simps*)
also have ... / *2* ≤ (*real n* / (*1* + *2* ∗ *real d*) + *1*) / *2*
by (*intro divide-right-mono*) *linarith*+
also have ... = *n* / (*2* ∗ (*2* ∗ *real d* + *1*)) + *1* / *2* **by** (*simp add*: *field-simps*)
finally have *m*: *real* (*m div 2*) ≤ ... .

have *size* {#*y* ∈# *mset xs*. *y* < *x*#} ≤ *d* ∗ *m* + *Suc d* ∗ (*m div 2*)
using *size-less-than-median-of-medians-strong*[*of Suc* (*2* ∗ *d*) *med x xs*] *assms*
unfolding *m-def* **by** (*simp add*: *algebra-simps*)
also have ... ≤ *d* ∗ (*2* ∗ (*m div 2*) + *1*) + *Suc d* ∗ (*m div 2*)
by (*intro add-mono mult-left-mono*) *linarith*+
also have ... = (*3* ∗ *d* + *1*) ∗ (*m div 2*) + *d*
by (*simp add*: *algebra-simps*)
finally have *real* (*size* {#*y* ∈# *mset xs*. *y* < *x*#}) ≤ *real* ...
by (*subst of-nat-le-iff*)

also have ... $\leq (3 * real\ d + 1) * (n\ /\ (2 * (2 * d + 1)) + 1/2) + real\ d$
unfolding *of-nat-add of-nat-mult of-nat-1 of-nat-numeral*
by (*intro add-mono mult-mono order.refl m*) (*auto simp*: *m-def length-chop n-def add-ac*)
also have ... $= c * real\ n + (5 * real\ d + 1)\ /\ 2$
by (*simp add*: *field-simps c-def*)
also have ... $\leq real\ (nat\ \lceil c * n \rceil) + ((5 * d)\ div\ 2 + 1))$
unfolding *of-nat-add* **by** (*intro add-mono*) (*linarith*, *simp add*: *field-simps*)
finally show *?thesis* **by** (*subst* (*asm*) *of-nat-le-iff*) (*simp-all add*: *add-ac*)
qed *auto*

We get the analogous result for the number of elements that are greater than a median-of-medians by looking at the dual order and using the *transfer* method.

theorem *size-greater-than-median-of-medians*:
fixes *xs* :: *'a* :: *linorder list* **and** *d* :: *nat*
assumes *median*: $\bigwedge xs.\ xs \neq [] \Longrightarrow length\ xs \leq Suc\ (2 * d) \Longrightarrow is\text{-}median\ (med\ xs)\ xs$
assumes *median'*: *is-median x* (*map med* (*chop* (*Suc* (*2*d*)) *xs*))
defines $n \equiv length\ xs$
defines $c \equiv (3 * real\ d + 1)\ /\ (2 * (2 * d + 1))$
shows $size\ \{\#y \in\# mset\ xs.\ y > x\#\} \leq nat\ \lceil c * n \rceil + (5 * d)\ div\ 2 + 1$
proof −
include *lifting-syntax*
define *med'* **where** $med' = (\lambda xs.\ to\text{-}dual\text{-}ord\ (med\ (map\ of\text{-}dual\text{-}ord\ xs)))$
have $xs = map\ of\text{-}dual\text{-}ord\ ys$ **if** *list-all2 cr-dual-ord xs ys* **for** *xs* :: *'a list* **and** *ys*
using *that* **by** *induction* (*auto simp*: *cr-dual-ord-def*)
hence [*transfer-rule*]: (*list-all2* (*pcr-dual-ord* (=)) ===> *pcr-dual-ord* (=)) *med med'*
by (*auto simp*: *rel-fun-def pcr-dual-ord-def OO-def med'-def cr-dual-ord-def dual-ord.to-dual-ord-inverse*)

have $size\ \{\#y \in\# mset\ xs.\ y > x\#\} = length\ (filter\ (\lambda y.\ y > x)\ xs)$
by (*subst size-mset* [*symmetric*]) (*simp only*: *mset-filter*)
also have ... $= length\ (map\ to\text{-}dual\text{-}ord\ (filter\ (\lambda y.\ y > x)\ xs))$ **by** *simp*
also have $(\lambda y.\ y > x) = (\lambda y.\ to\text{-}dual\text{-}ord\ y < to\text{-}dual\text{-}ord\ x)$
by *transfer simp-all*
hence $length\ (map\ to\text{-}dual\text{-}ord\ (filter\ (\lambda y.\ y > x)\ xs)) = length\ (map\ to\text{-}dual\text{-}ord\ (filter\ \ldots\ xs))$
by *simp*
also have ... $= length\ (filter\ (\lambda y.\ y < to\text{-}dual\text{-}ord\ x)\ (map\ to\text{-}dual\text{-}ord\ xs))$
unfolding *filter-map o-def* **by** *simp*
also have ... $= size\ \{\#y \in\# mset\ (map\ to\text{-}dual\text{-}ord\ xs).\ y < to\text{-}dual\text{-}ord\ x\#\}$
by (*subst size-mset* [*symmetric*]) (*simp only*: *mset-filter*)
also have ... $\leq nat\ \lceil (3 * real\ d + 1)\ /\ real\ (2 * (2 * d + 1)) * length\ (map\ to\text{-}dual\text{-}ord\ xs) \rceil + 5 * d\ div\ 2 + 1$
proof (*intro size-less-than-median-of-medians*)
fix *xs* :: *'a dual-ord list* **assume** *xs*: $xs \neq []$ $length\ xs \leq Suc\ (2 * d)$

```
  from xs show is-median (med' xs) xs by (transfer fixing: d) (rule median)
 next
  show is-median (to-dual-ord x) (map med' (chop (Suc (2 * d)) (map to-dual-ord
xs)))
    by (transfer fixing: d x xs) (use median' in simp-all)
 qed
 finally show ?thesis by (simp add: n-def c-def)
qed
```

The most important case is that of chopping size 5, since that is the most practical one for the median-of-medians selection algorithm. For it, we obtain the following nice and simple bounds:

```
corollary size-less-greater-median-of-medians-5:
 fixes xs :: 'a :: linorder list
 assumes ⋀xs. xs ≠ [] ⟹ length xs ≤ 5 ⟹ is-median (med xs) xs
 assumes is-median x (map med (chop 5 xs))
 shows length (filter (λy. y < x) xs) ≤ nat ⌈0.7 * length xs⌉ + 6
   and length (filter (λy. y > x) xs) ≤ nat ⌈0.7 * length xs⌉ + 6
 using size-less-than-median-of-medians[of 2 med x xs]
       size-greater-than-median-of-medians[of 2 med x xs] assms
 by (simp-all add: size-mset [symmetric] mset-filter mult-ac add-ac del: size-mset)
```

1.7 The recursive step

We now turn to the actual selection algorithm itself. The following simple reduction lemma illustrates the idea of the algorithm quite well already, but it has the disadvantage that, if one were to use it as a recursive algorithm, it would only work for lists with distinct elements. If the list contains repeated elements, this may not even terminate.

The basic idea is that we choose some pivot element, partition the list into elements that are bigger than the pivot and those that are not, and then recurse into one of these (hopefully smaller) lists.

```
theorem select-rec-partition:
 assumes d > 0 k < length xs
 shows select k xs = (
         let (ys, zs) = partition (λy. y ≤ x) xs
         in  if k < length ys then select k ys else select (k − length ys) zs
        ) (is - = ?rhs)
proof −
 define ys zs where ys = filter (λy. y ≤ x) xs and zs = filter (λy. ¬(y ≤ x)) xs
 have select k xs = select k (ys @ zs)
   by (intro select-cong) (simp-all add: ys-def zs-def)
 also have ... = (if k < length ys then select k ys else select (k − length ys) zs)
  using assms(2) by (intro select-append') (auto simp: ys-def zs-def sum-length-filter-compl)
 finally show ?thesis by (simp add: ys-def zs-def Let-def o-def)
qed
```

The following variant uses a three-way partitioning function instead. This

way, the size of the list in the final recursive call decreases by a factor of at least $\frac{3d'+1}{2(2d'+1)}$ by the previous estimates, given that the chopping size is $d = 2d' + 1$. For a chopping size of 5, we get a factor of 0.7.

definition *threeway-partition* :: *'a* ⇒ *'a* :: *linorder list* ⇒ *'a list* × *'a list* × *'a list*
where
threeway-partition x xs = (*filter* (λ*y*. *y* < *x*) *xs*, *filter* (λ*y*. *y* = *x*) *xs*, *filter* (λ*y*. *y* > *x*) *xs*)

lemma *threeway-partition-code* [*code*]:
threeway-partition x [] = ([], [], [])
threeway-partition x (*y* # *ys*) =
(*case threeway-partition x ys of* (*ls*, *es*, *gs*) ⇒
if y < *x then* (*y* # *ls*, *es*, *gs*) *else if x* = *y then* (*ls*, *y* # *es*, *gs*) *else* (*ls*, *es*, *y* # *gs*))
by (*auto simp*: *threeway-partition-def*)

theorem *select-rec-threeway-partition*:
assumes *d* > *0 k* < *length xs*
shows *select k xs* = (
let (*ls*, *es*, *gs*) = *threeway-partition x xs*;
nl = *length ls*; *ne* = *length es*
in
if k < *nl then select k ls*
else if k < *nl* + *ne then x*
else select (*k* − *nl* − *ne*) *gs*
) (**is** - = *?rhs*)
proof −
define *ls es gs* **where** *ls* = *filter* (λ*y*. *y* < *x*) *xs* **and** *es* = *filter* (λ*y*. *y* = *x*) *xs*
and *gs* = *filter* (λ*y*. *y* > *x*) *xs*
define *nl ne* **where** [*simp*]: *nl* = *length ls ne* = *length es*
have *mset-eq*: *mset xs* = *mset ls* + *mset es* + *mset gs* **unfolding** *ls-def es-def gs-def*
by (*induction xs*) *auto*
have *length-eq*: *length xs* = *length ls* + *length es* + *length gs* **unfolding** *ls-def es-def gs-def*
by (*induction xs*) (*auto simp del*: *filter-True*)

have [*simp*]: *select i es* = *x* **if** *i* < *length es* **for** *i*
proof −
have *select i es* ∈ *set* (*sort es*) **unfolding** *select-def*
using *that* **by** (*intro nth-mem*) *auto*
hence *select i es* ∈ *set es* **using** *that* **by** (*auto simp*: *select-def*)
also have *set es* ⊆ {*x*} **unfolding** *es-def* **by** (*induction es*) *auto*
finally show *?thesis* **by** *simp*
qed

have *select k xs* = *select k* (*ls* @ (*es* @ *gs*))
by (*intro select-cong*) (*simp-all add*: *mset-eq*)

```
  also have ... = (if k < nl then select k ls else select (k − nl) (es @ gs))
    unfolding nl-ne-def using assms
    by (intro select-append′) (auto simp: ls-def es-def gs-def length-eq)
  also have ... = (if k < nl then select k ls else if k < nl + ne then x
                   else select (k − nl − ne) gs) (is ?lhs′ = ?rhs′)
  proof (cases k < nl)
    case False
    hence ?lhs′ = select (k − nl) (es @ gs) by simp
    also have ... = (if k − nl < ne then select (k − nl) es else select (k − nl −
ne) gs)
      unfolding nl-ne-def using assms False
      by (intro select-append′) (auto simp: ls-def es-def gs-def length-eq)
    also have ... = (if k − nl < ne then x else select (k − nl − ne) gs)
      by simp
    also from False have ... = ?rhs′ by auto
    finally show ?thesis .
  qed simp-all
  also have ... = ?rhs
    by (simp add: threeway-partition-def Let-def ls-def es-def gs-def)
  finally show ?thesis .
qed
```

By the above results, it can be seen quite easily that, in each recursive step, the algorithm takes a list of length n, does $O(n)$ work for the chopping, computing the medians of the sublists, and partitioning, and it calls itself recursively with lists of size at most $\lceil 0.2n \rceil$ and $\lceil 0.7n \rceil + 6$, respectively. This means that the runtime of the algorithm is bounded above by the Akra–Bazzi-style recurrence

$$T(n) = T(\lceil 0.2n \rceil) + T(\lceil 0.7n \rceil + 6) + O(n)$$

which, by the Akra–Bazzi theorem, can be shown to fulfil $T \in \Theta(n)$.

However, a proper analysis of this would require an actual execution model and some way of measuring the runtime of the algorithm, which is not what we aim to do here. Additionally, the entire algorithm can be performed in-place in an imperative way, but this because quite tedious.

Instead of this, we will now focus on developing the above recursion into an executable functional algorithm.

1.8 Medians of lists of length at most 5

We now show some basic results about how to efficiently find a median of a list of size at most 5. For length 1 or 2, this is trivial, since we can just pick any element. For length 3 and 4, we need at most three comparisons. For length 5, we need at most six comparisons.

This allows us to save some comparisons compared with the naive method of performing insertion sort and then returning the element in the middle.

```
definition median-3 :: 'a :: linorder ⇒ - where
  median-3 a b c =
    (if a ≤ b then
       if b ≤ c then b else max a c
     else
       if c ≤ b then b else min a c)

lemma median-3: median-3 a b c = median [a, b, c]
  by (auto simp: median-3-def median-def select-def min-def max-def)

definition median-5-aux :: 'a :: linorder ⇒ - where
  median-5-aux x1 x2 x3 x4 x5 = (
    if x2 ≤ x3 then if x2 ≤ x4 then min x3 x4 else min x2 x5
    else if x4 ≤ x3 then min x3 x5 else min x2 x4)

lemma median-5-aux:
  assumes x1 ≤ x2 x4 ≤ x5 x1 ≤ x4
  shows   median-5-aux x1 x2 x3 x4 x5 = median [x1,x2,x3,x4,x5]
  using assms by (auto simp: median-5-aux-def median-def select-def min-def)

definition median-5 :: 'a :: linorder ⇒ - where
  median-5 a b c d e = (
    let (x1, x2) = (if a ≤ b then (a, b) else (b, a));
        (x4, x5) = (if d ≤ e then (d, e) else (e, d))
    in
       if x1 ≤ x4 then median-5-aux x1 x2 c x4 x5 else median-5-aux x4 x5 c x1
x2)

lemma median-5: median-5 a b c d e = median [a, b, c, d, e]
  by (auto simp: median-5-def Let-def median-5-aux intro: median-cong)

fun median-le-5 where
  median-le-5 [a] = a
| median-le-5 [a,b] = a
| median-le-5 [a,b,c] = median-3 a b c
| median-le-5 [a,b,c,d] = median-3 a b c
| median-le-5 [a,b,c,d,e] = median-5 a b c d e
| median-le-5 - = undefined

lemma median-5-in-set: median-5 a b c d e ∈ {a, b, c, d, e}
proof −
  have median-5 a b c d e ∈ set [a, b, c, d, e]
    unfolding median-5 by (rule median-in-set) auto
  thus ?thesis by simp
qed

lemma median-le-5-in-set:
  assumes xs ≠ [] length xs ≤ 5
  shows   median-le-5 xs ∈ set xs
```

proof (*cases xs rule*: *median-le-5.cases*)
case (*5 a b c d e*)
with *median-5-in-set*[*of a b c d e*] **show** *?thesis* **by** *simp*
qed (*insert assms*, *auto simp*: *median-3-def min-def max-def*)

lemma *median-le-5*:
assumes *xs* ≠ [] *length xs* ≤ *5*
shows *is-median* (*median-le-5 xs*) *xs*
proof (*cases xs rule*: *median-le-5.cases*)
case (*3 a b c*)
have *is-median* (*median xs*) *xs* **by** *simp*
also have *median xs* = *median-3 a b c* **by** (*simp add*: *median-3 3*)
finally show *?thesis* **using** *3* **by** *simp*
next
case (*4 a b c d*)
have *is-median* (*median* [*a*,*b*,*c*]) [*a*,*b*,*c*] **by** *simp*
also have *median* [*a*,*b*,*c*] = *median-3 a b c* **by** (*simp add*: *median-3 4*)
finally have *is-median* (*median-3 a b c*) (*d* # [*a*,*b*,*c*]) **by** (*rule is-median-Cons-odd*)
auto
also have *?this* ⟷ *is-median* (*median-3 a b c*) [*a*,*b*,*c*,*d*] **by** (*intro is-median-cong*)
auto
finally show *?thesis* **using** *4* **by** *simp*
next
case (*5 a b c d e*)
have *is-median* (*median xs*) *xs* **by** *simp*
also have *median xs* = *median-5 a b c d e* **by** (*simp add*: *median-5 5*)
finally show *?thesis* **using** *5* **by** *simp*
qed (*insert assms*, *auto simp*: *is-median-def*)

1.9 Median-of-medians selection algorithm

The fast selection function now simply computes the median-of-medians of the chopped-up list as a pivot, partitions the list into with respect to that pivot, and recurses into one of the resulting sublists.

function *fast-select* **where**
fast-select k xs = (
if length xs ≤ *20 then*
sort xs ! *k*
else
let x = *fast-select* (((*length xs* + *4*) *div 5* − *1*) *div 2*) (*map median-le-5* (*chop 5 xs*));
(*ls*, *es*, *gs*) = *threeway-partition x xs*
in
if k < *length ls then fast-select k ls*
else if k < *length ls* + *length es then x*
else fast-select (*k* − *length ls* − *length es*) *gs*
)
by *auto*

The correctness of this is obvious from the above theorems, but the proof is still somewhat complicated by the fact that termination depends on the correctness of the function.

lemma *fast-select-correct-aux*:
assumes *fast-select-dom* (*k*, *xs*) *k* < *length xs*
shows *fast-select k xs* = *select k xs*
using *assms*
proof *induction*
case (*1 k xs*)
show *?case*
proof (*cases length xs* ≤ *20*)
case *True*
thus *?thesis* **using** *1.prems 1.hyps*
by (*subst fast-select.psimps*) (*auto simp*: *select-def*)
next
case *False*
define *x* **where**
x = *fast-select* (((*length xs* + *4*) *div 5* − *Suc 0*) *div 2*) (*map median-le-5* (*chop 5 xs*))
define *ls* **where** *ls* = *filter* (λ*y*. *y* < *x*) *xs*
define *es* **where** *es* = *filter* (λ*y*. *y* = *x*) *xs*
define *gs* **where** *gs* = *filter* (λ*y*. *y* > *x*) *xs*
define *nl ne* **where** *nl* = *length ls* **and** *ne* = *length es*
note *defs* = *nl-def ne-def x-def ls-def es-def gs-def*
have *tw*: (*ls*, *es*, *gs*) = *threeway-partition* (*fast-select* (((*length xs* + *4*) *div 5* − *1*) *div 2*)
(*map median-le-5* (*chop 5 xs*))) *xs*
unfolding *threeway-partition-def defs One-nat-def* **..**
have *tw′*: (*ls*, *es*, *gs*) = *threeway-partition x xs*
by (*simp add*: *tw x-def*)

have *fast-select k xs* = (*if k* < *nl then fast-select k ls else if k* < *nl* + *ne then x*
else fast-select (*k* − *nl* − *ne*) *gs*) **using** *1.hyps False*
by (*subst fast-select.psimps*) (*simp-all add*: *threeway-partition-def defs* [*symmetric*])
also have ... = (*if k* < *nl then select k ls else if k* < *nl* + *ne then x*
else select (*k* − *nl* − *ne*) *gs*)
proof (*intro if-cong refl*)
assume ∗: *k* < *nl*
show *fast-select k ls* = *select k ls*
by (*rule 1*; (*rule refl tw*)*?*)
(*insert* ∗, *auto simp*: *False threeway-partition-def ls-def x-def nl-def*)+
next
assume ∗: ¬*k* < *nl* ¬*k* < *nl* + *ne*
have ∗∗: *length xs* = *length ls* + *length es* + *length gs*
unfolding *ls-def es-def gs-def* **by** (*induction xs*) (*auto simp del*: *filter-True*)
show *fast-select* (*k* − *nl* − *ne*) *gs* = *select* (*k* − *nl* − *ne*) *gs*
unfolding *nl-def ne-def*
by (*rule 1*; (*rule refl tw*)*?*) (*insert False* ∗ ∗∗ ‹*k* < *length xs*›, *auto simp*: *nl-def ne-def*)

```
    qed
    also have ... = select k xs using ‹k < length xs›
      by (subst (3) select-rec-threeway-partition[of 5::nat - - x])
        (unfold Let-def nl-def ne-def ls-def gs-def es-def x-def threeway-partition-def,
simp-all)
    finally show ?thesis .
  qed
qed
```

Termination of the algorithm is reasonably obvious because the lists that are recursed into never contain the pivot (the median-of-medians), while the original list clearly does. The proof is still somewhat technical though.

```
lemma fast-select-termination: All fast-select-dom
proof (relation measure (length ∘ snd); (safe)?, goal-cases)
  case (1 k xs)
  thus ?case
    by (auto simp: length-chop nat-less-iff ceiling-less-iff)
next
  fix k :: nat and xs ls es gs :: 'a list
   define x where x = fast-select (((length xs + 4) div 5 − 1) div 2) (map
median-le-5 (chop 5 xs))
  assume A: ¬ length xs ≤ 20
          (ls, es, gs) = threeway-partition x xs
          fast-select-dom (((length xs + 4) div 5 − 1) div 2,
                           map median-le-5 (chop 5 xs))
  from A have eq: ls = filter (λy. y < x) xs gs = filter (λy. y > x) xs
    by (simp-all add: x-def threeway-partition-def)
  have len: (length xs + 4) div 5 = nat ⌈length xs / 5⌉ by linarith
  have less: (nat ⌈real (length xs) / 5⌉ − Suc 0) div 2 < nat ⌈real (length xs) /
5⌉
    using A(1) by linarith
  have x = select (((length xs + 4) div 5 − 1) div 2) (map median-le-5 (chop 5
xs))
     using less unfolding x-def by (intro fast-select-correct-aux A) (auto simp:
length-chop len)
   also have ... = median (map median-le-5 (chop 5 xs)) by (simp add: median-def
len length-chop)
  finally have x: x = ... .
  moreover {
    have x ∈ set (map median-le-5 (chop 5 xs))
      using A(1) unfolding x by (intro median-in-set) auto
    also have ... ⊆ (⋃ys∈set (chop 5 xs). {median-le-5 ys}) by auto
    also have ... ⊆ (⋃ys∈set (chop 5 xs). set ys) using A(1)
      by (intro UN-mono) (auto simp: median-le-5-in-set length-chop-part-le)
    also have ... = set xs by (subst UN-sets-chop) auto
    finally have x ∈ set xs .
  }
  ultimately show ((k, ls), k, xs) ∈ measure (length ∘ snd)
            and ((k − length ls − length es, gs), k, xs) ∈ measure (length ∘ snd)
```

using *A(1)* **by** (*auto simp*: *eq intro*!: *length-filter-less*[*of x*])
qed

We now have all the ingredients to show that *fast-select* terminates and does, indeed, compute the k-th order statistic.

termination *fast-select* **by** (*rule fast-select-termination*)

theorem *fast-select-correct*: $k < length\ xs \Longrightarrow fast\text{-}select\ k\ xs = select\ k\ xs$
using *fast-select-termination* **by** (*intro fast-select-correct-aux*) *auto*

The following version is then suitable for code export.

```
lemma fast-select-code [code]:
  fast-select k xs = (
    if length xs ≤ 20 then
      fold insort xs [] ! k
    else
      let x = fast-select (((length xs + 4) div 5 − 1) div 2) (map median-le-5
(chop 5 xs));
          (ls, es, gs) = threeway-partition x xs;
          nl = length ls; ne = nl + length es
      in
        if k < nl then fast-select k ls
        else if k < ne then x
        else fast-select (k − ne) gs
    )
  by (subst fast-select.simps) (simp-all only: Let-def algebra-simps sort-conv-fold)

lemma select-code [code]:
  select k xs = (if k < length xs then fast-select k xs
                 else Code.abort (STR ''Selection index out of bounds.'') (λ-. select
k xs))
proof (cases k < length xs)
  case True
  thus ?thesis by (simp only: if-True fast-select-correct)
qed (simp-all only: Code.abort-def if-False)

end
```

References

[1] T. H. Cormen, C. E. Leiserson, R. L. Rivest, and C. Stein. *Introduction to Algorithms, 3rd Edition.* MIT Press, 2009.