van Emde Boas Trees

Thomas Ammer and Peter Lammich

November 9, 2026

Abstract

The *van Emde Boas tree* or *van Emde Boas priority queue* [1, 2] is a data structure supporting membership test, insertion, predecessor and successor search, minimum and maximum determination and deletion in $\mathcal{O}(\log\log|\mathcal{U}|)$ time, where $\mathcal{U} = \{0, ..., 2^n - 1\}$ is the overall range to be considered. The presented formalization follows Chapter 20 of the popular *Introduction to Algorithms (3rd ed.)* [3] by Cormen, Leiserson, Rivest and Stein (CLRS), extending the list of formally verified CLRS algorithms [4]. Our current formalization is based on the first author's bachelor's thesis.

First, we prove correct a *functional* implementation, w.r.t. an abstract data type for sets. Apart from functional correctness, we show a resource bound, and runtime bounds w.r.t. manually defined timing functions [5] for the operations.

Next, we refine the operations to Imperative HOL [6, 7] with time [8], and show correctness and complexity. This yields a practically more efficient implementation, and eliminates the manually defined timing functions from the trusted base of the proof.

Contents

1 Preliminaries and Preparations **5**
- 1.1 Data Type Definition . . . 5
- 1.2 Functions for obtaining high and low bits of an input number. . . . 5
- 1.3 Some auxiliary lemmata . . . 5
- 1.4 Auxiliary functions for defining valid Van Emde Boas Trees . . . 6
- 1.5 Inductive Definition of semantically valid Vam Emde Boas Trees . . . 6
- 1.6 Function for generating an empty tree of arbitrary degree respectively order . . . 9

2 Member Function **10**

3 Insert Function **13**

4 Correctness of the Insert Operation **14**
- 4.1 Validness Preservation . . . 14
- 4.2 Correctness with Respect to Set Interpretation . . . 15

5 The Minimum and Maximum Operation **15**

6 The Successor Operation **18**
- 6.1 Auxiliary Lemmas on Sets and Successorship . . . 18
- 6.2 The actual Function . . . 19
- 6.3 Lemmas for Term Decomposition . . . 19
- 6.4 Correctness Proof . . . 20

7 The Predecessor Operation **21**
- 7.1 Lemmas on Sets and Predecessorship . . . 21
- 7.2 The actual Function for Predecessor Search . . . 21
- 7.3 Auxiliary Lemmas . . . 22
- 7.4 Correctness Proof . . . 22

8 Deletion **23**
- 8.1 Function Definition . . . 23
- 8.2 Auxiliary Lemmas . . . 24
- 8.3 Validness Preservation . . . 30
- 8.4 Correctness with Respect to Set Interpretation . . . 30

9 Uniqueness Property of valid Trees **30**

10 Heights of van Emde Boas Trees **31**

11 Upper Bounds for canonical Functions: Relationships between Run Time and Tree Heights **32**
- 11.1 Membership test . . . 32
- 11.2 Minimum, Maximum, Emptiness Test . . . 33

11.3 Insertion . . . 34
11.4 Successor Function . . . 35
11.5 Predecessor Function . . . 36
11.6 Running Time Bounds for Deletion . . . 37

12 Space Complexity and *buildup* Time Consumption **40**
12.1 Space Comlexity of valid van Emde Boas Trees . . . 40
12.2 Auxiliary Lemmas for List Summation . . . 40
12.3 Actual Space Reasoning . . . 41
12.4 Complexity of Generation Time . . . 41

13 Functional Interface **43**
13.1 Code Generation Setup . . . 43
13.1.1 Code Equations . . . 43
13.2 Correctness Lemmas . . . 46
13.2.1 Space Bound . . . 46
13.2.2 Buildup . . . 46
13.2.3 Equality . . . 47
13.2.4 Member . . . 47
13.2.5 Insert . . . 47
13.2.6 Maximum . . . 47
13.2.7 Minimum . . . 47
13.3 Emptiness determination . . . 48
13.3.1 Successor . . . 48
13.3.2 Predecessor . . . 48
13.3.3 Delete . . . 49
13.4 Interface Usage Example . . . 49
13.5 Lists . . . 50

14 Imperative van Emde Boas Trees **54**
14.1 Assertions on van Emde Boas Trees . . . 54
14.2 High and low Bitsequences Definition . . . 56

15 Imperative Implementation of *vebt − buildup* **57**

16 Minimum and Maximum Determination **60**

17 Membership Test on imperative van Emde Boas Trees **62**
17.1 *minNulli*: empty tree? . . . 63

18 Imperative *vebt − insert* to van Emde Boas Tree **64**

19 Imperative Successor **67**

20 Imperative Predecessor **70**

21 Imperative Delete **71**

22 Imperative Interface **75**
22.1 Code Export . . . 75
22.2 Interface . . . 76
22.2.1 Buildup . . . 76
22.2.2 Member . . . 76
22.2.3 Insert . . . 76
22.2.4 Maximum . . . 76
22.2.5 Minimum . . . 77
22.2.6 Successor . . . 77
22.2.7 Predecessor . . . 77
22.2.8 Delete . . . 77
22.3 Setup of VCG . . . 77

23 Interface Usage Example **77**
23.1 Test Program . . . 77
23.2 Correctness without Time . . . 78
23.3 Time Bound Reasoning . . . 78

24 Conclusion **79**

theory *VEBT-Definitions* **imports**
Main
HOL−Library.Extended-Nat
HOL−Library.Code-Target-Numeral
HOL−Library.Code-Target-Nat

begin

1 Preliminaries and Preparations

1.1 Data Type Definition

datatype *VEBT* = *is-Node*: *Node* (*info*:(*nat*∗*nat*) *option*)(*deg*: *nat*)(*treeList*: *VEBT list*) (*summary*:*VEBT*)
|
is-Leaf: *Leaf* *bool* *bool*

hide-const (**open**) *info deg treeList summary*

locale *VEBT-internal* **begin**

1.2 Functions for obtaining high and low bits of an input number.

definition *high* :: *nat* ⇒ *nat* ⇒ *nat* **where**
high x n = (*x div* (2^*n*))

definition *low* :: *nat* ⇒ *nat* ⇒ *nat* **where**
low x n = (*x mod* (2^*n*))

1.3 Some auxiliary lemmata

lemma *inthall*[*termination-simp*]: (⋀ *x*. *x* ∈ *set xs* ⟹ *P x*) ⟹ *n* < *length xs* ⟹ *P* (*xs* ! *n*)
⟨*proof*⟩

lemma *intind*: *i* < *n* ⟹ *P x* ⟹ *P* (*replicate n x* ! *i*)
⟨*proof*⟩

lemma *concat-inth*:(*xs* @[*x*]@*ys*)! (*length xs*) = *x*
⟨*proof*⟩

lemma *pos-n-replace*: *n*<*length xs* ⟹ *length xs* = *length* (*take n xs* @ [*y*] @*drop* (*Suc n*) *xs*)
⟨*proof*⟩

lemma *inthrepl*: *i* < *n* ⟹ (*replicate n x*) ! *i* = *x* ⟨*proof*⟩

lemma *nth-repl*: *m*<*length xs* ⟹ *n* <*length xs* ⟹ *m*≠ *n* ⟹(*take n xs* @ [*x*] @ *drop* (*n*+*1*) *xs*) !
m = *xs* ! *m*
⟨*proof*⟩

lemma [*termination-simp*]:**assumes** *high x deg* < *length treeList*
shows*size* (*treeList* ! *high x deg*) < *Suc* (*size-list size treeList* + *size s*)
⟨*proof*⟩

1.4 Auxiliary functions for defining valid Van Emde Boas Trees

This function checks whether an element occurs in a Leaf

fun *naive-member* :: *VEBT* ⇒ *nat* ⇒ *bool* **where**
naive-member (*Leaf a b*) *x* = (*if x* = *0 then a else if x* = *1 then b else False*)|
naive-member (*Node - 0 -*) - = *False*|
naive-member (*Node - deg treeList s*) *x* = (*let pos* = *high x* (*deg div 2*) *in*
(*if pos* < *length treeList then naive-member* (*treeList* ! *pos*) (*low x* (*deg div 2*)) *else False*))

Test for elements stored by using the provide min-max-fields

fun *membermima* :: *VEBT* ⇒ *nat* ⇒ *bool* **where**
membermima (*Leaf - -*) - = *False*|
membermima (*Node None 0 - -*)- =*False*|
membermima (*Node* (*Some* (*mi*,*ma*)) *0 - -*) *x* = (*x* = *mi* ∨ *x* = *ma*)|
membermima (*Node* (*Some* (*mi*, *ma*)) *deg treeList -*) *x* = (*x* = *mi* ∨ *x* = *ma* ∨ (
let pos = *high x* (*deg div 2*) *in* (*if pos* < *length treeList*
then membermima (*treeList* ! *pos*) (*low x* (*deg div 2*)) *else False*)))|
membermima (*Node None* (*deg*) *treeList -*) *x* = (*let pos* = *high x* (*deg div 2*) *in*
(*if pos* < *length treeList then membermima* (*treeList* ! *pos*) (*low x* (*deg div 2*)) *else False*))

lemma *length-mul-elem*:(∀ *x* ∈ *set xs*. *length x* = *n*) ⟹ *length* (*concat xs*) = (*length xs*) ∗ *n*
⟨*proof*⟩

We combine both auxiliary functions: The following test returns true if and only if an element occurs in the tree with respect to our interpretation no matter where it is stored.

definition *both-member-options* :: *VEBT* ⇒ *nat* ⇒ *bool* **where**
both-member-options t x = (*naive-member t x* ∨ *membermima t x*)

end
context begin
interpretation *VEBT-internal* ⟨*proof*⟩

definition *set-vebt* :: *VEBT* ⇒ *nat set* **where**
set-vebt t = {*x*. *both-member-options t x*}
end

1.5 Inductive Definition of semantically valid Vam Emde Boas Trees

Invariant for verification proofs

context begin
interpretation *VEBT-internal* ⟨*proof*⟩

inductive *invar-vebt*::*VEBT* ⇒ *nat* ⇒ *bool* **where**

$invar\text{-}vebt\ (Leaf\ \ a\ b)\ (Suc\ 0)\ |$
$(\ \forall\ t \in set\ treeList.\ invar\text{-}vebt\ t\ n) \Longrightarrow invar\text{-}vebt\ summary\ m\ \Longrightarrow\ length\ treeList = 2\hat{}m$
$\Longrightarrow m = n \Longrightarrow deg = n + m \Longrightarrow (\nexists\ i.\ both\text{-}member\text{-}options\ summary\ i)$
$\Longrightarrow(\forall\ t \in set\ treeList.\ \nexists\ x.\ both\text{-}member\text{-}options\ t\ x)$
$\Longrightarrow invar\text{-}vebt\ (Node\ None\ deg\ treeList\ summary)\ deg|$
$(\ \forall\ t \in set\ treeList.\ invar\text{-}vebt\ t\ n) \Longrightarrow invar\text{-}vebt\ summary\ m$
$\Longrightarrow\ length\ treeList = 2\hat{}m \Longrightarrow m = Suc\ n \Longrightarrow deg = n + m \Longrightarrow (\nexists\ i.\ both\text{-}member\text{-}options\ summary\ i)$
$\Longrightarrow (\forall\ t \in set\ treeList.\ \nexists\ x.\ both\text{-}member\text{-}options\ t\ x)$
$\Longrightarrow invar\text{-}vebt\ (Node\ None\ deg\ treeList\ summary)\ deg|$
$(\ \forall\ t \in set\ treeList.\ invar\text{-}vebt\ t\ n) \Longrightarrow invar\text{-}vebt\ summary\ m\ \Longrightarrow length\ treeList = 2\hat{}m \Longrightarrow m = n$
$\Longrightarrow deg = n + m \Longrightarrow (\forall\ i < 2\hat{}m.\ (\exists\ x.\ both\text{-}member\text{-}options\ (treeList\ !\ i)\ x) \longleftrightarrow (\ both\text{-}member\text{-}options\ summary\ i)) \Longrightarrow$
$(mi = ma \longrightarrow (\forall\ t \in set\ treeList.\ \nexists\ x.\ both\text{-}member\text{-}options\ t\ x)) \Longrightarrow$
$mi \le ma \Longrightarrow ma < 2\hat{}deg \Longrightarrow$
$(mi \neq ma \longrightarrow$
$(\forall\ i < 2\hat{}m.$
$(high\ ma\ n = i \longrightarrow both\text{-}member\text{-}options\ (treeList\ !\ i)\ (low\ ma\ n)) \wedge$
$(\forall\ x.\ (high\ x\ n = i \wedge both\text{-}member\text{-}options\ (treeList\ !\ i)\ (low\ x\ n)) \longrightarrow mi < x \wedge x \le ma)\ )\ )$
$\Longrightarrow invar\text{-}vebt\ (Node\ (Some\ (mi,\ ma))\ deg\ treeList\ summary)\ deg|$
$(\ \forall\ t \in set\ treeList.\ invar\text{-}vebt\ t\ n) \Longrightarrow invar\text{-}vebt\ summary\ m\ \Longrightarrow\ length\ treeList = 2\hat{}m$
$\Longrightarrow\ m = Suc\ n \Longrightarrow deg = n + m \Longrightarrow (\forall\ i < 2\hat{}m.\ (\exists\ x.\ both\text{-}member\text{-}options\ (treeList\ !\ i)\ x) \longleftrightarrow (\ both\text{-}member\text{-}options\ summary\ i)) \Longrightarrow$
$(mi = ma \longrightarrow (\forall\ t \in set\ treeList.\ \nexists\ x.\ both\text{-}member\text{-}options\ t\ x)) \Longrightarrow$
$mi \le ma \Longrightarrow ma < 2\hat{}deg \Longrightarrow$
$(mi \neq ma \longrightarrow$
$(\forall\ i < 2\hat{}m.$
$(high\ ma\ n = i \longrightarrow both\text{-}member\text{-}options\ (treeList\ !\ i)\ (low\ ma\ n)) \wedge$
$(\forall\ x.\ (high\ x\ n = i \wedge both\text{-}member\text{-}options\ (treeList\ !\ i)\ (low\ x\ n)) \longrightarrow mi < x \wedge x \le ma)))$
$\Longrightarrow invar\text{-}vebt\ (Node\ (Some\ (mi,\ ma))\ deg\ treeList\ summary)\ deg$

end

context *VEBT-internal* **begin**

definition $in\text{-}children\ n\ treeList\ x \equiv both\text{-}member\text{-}options\ (treeList\ !\ high\ x\ n)\ (low\ x\ n)$

functional validness definition

fun $valid' :: VEBT \Rightarrow nat \Rightarrow bool$ **where**
$valid'\ (Leaf\ -\ -)\ d \longleftrightarrow d=1$
$|\ valid'\ (Node\ mima\ deg\ treeList\ summary)\ deg' \longleftrightarrow$
$($
$deg=deg' \wedge ($
$let\ n = deg\ div\ 2;\ m = deg - n\ in$
$(\ \forall\ t \in set\ treeList.\ valid'\ t\ n\ )$
$\wedge\ valid'\ summary\ m$

```
    ∧ length treeList = 2^m
    ∧ (
      case mima of
       None ⇒ (∄ i. both-member-options summary i) ∧ (∀ t ∈ set treeList. ∄ x. both-member-options
t x)
     | Some (mi,ma) ⇒
         mi ≤ ma ∧ ma<2^deg
       ∧ (∀ i < 2^m. (∃ x. both-member-options (treeList ! i) x) ⟷ ( both-member-options summary
i))
        ∧ (if mi=ma then (∀ t ∈ set treeList. ∄ x. both-member-options t x)
           else
             in-children n treeList ma
           ∧ (∀x < 2^deg. in-children n treeList x ⟶ mi<x ∧ x≤ma)
          )
    )
    )
  )
```

equivalence proofs

lemma *high-bound-aux*: *ma* < *2^*(*n*+*m*) ⟹ *high ma n* < *2^m*
⟨*proof*⟩

lemma *valid-eq1*:
assumes *invar-vebt t d*
shows *valid′ t d*
⟨*proof*⟩

lemma *even-odd-cases*:
fixes *x* :: *nat*
obtains *n* **where** *x*=*n*+*n* | *n* **where** *x* = *n* + *Suc n*
⟨*proof*⟩

lemma *valid-eq2*: *valid′ t d* ⟹ *invar-vebt t d*
⟨*proof*⟩

lemma *valid-eq*: *valid′ t d* ⟷ *invar-vebt t d*
⟨*proof*⟩

lemma [*termination-simp*]: **assumes** *odd* (*v*::*nat*) **shows** *v div 2* < *v*
⟨*proof*⟩

lemma [*termination-simp*]:**assumes** *n* > *1* **and** *odd n* **shows** *Suc* (*n div 2*) < *n*
⟨*proof*⟩

end

1.6 Function for generating an empty tree of arbitrary degree respectively order

context begin
interpretation *VEBT-internal* ⟨*proof*⟩

fun *vebt-buildup* :: *nat* ⇒ *VEBT* **where**
vebt-buildup 0 = Leaf False False|
vebt-buildup (*Suc 0*) = *Leaf False False*|
vebt-buildup n = (*if even n then* (*let half* = *n div 2 in*
Node None n (*replicate* (*2^half*) (*vebt-buildup half*)) (*vebt-buildup half*))
else (*let half* = *n div 2 in*
Node None n (*replicate* (*2^*(*Suc half*)) (*vebt-buildup half*)) (*vebt-buildup* (*Suc half*))))

end

context *VEBT-internal* **begin**

lemma *buildup-nothing-in-leaf*: ¬ *naive-member* (*vebt-buildup n*) *x*
⟨*proof*⟩

lemma *buildup-nothing-in-min-max*:¬ *membermima* (*vebt-buildup n*) *x*
⟨*proof*⟩

The empty tree generated by $vebt_buildup$ is indeed a valid tree.

lemma *buildup-gives-valid*: *n>0* ⟹ *invar-vebt* (*vebt-buildup n*) *n*
⟨*proof*⟩

lemma *mi-ma-2-deg*: **assumes** *invar-vebt* (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*) *n* **shows** *mi*≤ *ma* ∧ *ma* < *2^deg*
⟨*proof*⟩

lemma *deg-not-0*: *invar-vebt t n* ⟹ *n* > *0*
⟨*proof*⟩

lemma *set-n-deg-not-0*:**assumes** ∀ *t*∈*set treeList*. *invar-vebt t n***and** *length treeList* = *2^m* **shows** *n* ≥ *1*
⟨*proof*⟩

lemma *both-member-options-ding*: **assumes***invar-vebt* (*Node info deg treeList summary*) *n* **and** *x*<*2^deg***and** *both-member-options* (*treeList* ! (*high x* (*deg div 2*))) (*low x* (*deg div 2*))**shows** *both-member-options* (*Node info deg treeList summary*) *x*
⟨*proof*⟩

lemma *exp-split-high-low*: **assumes** *x* < *2^*(*n*+*m*) **and** *n* > *0* **and** *m*> *0*
shows *high x n* < *2^m* **and** *low x n* < *2^n*
⟨*proof*⟩

lemma *low-inv*: **assumes** *x*< *2^n* **shows** *low* (*y*∗*2^n* + *x*) *n* = *x* ⟨*proof*⟩

lemma *high-inv*: **assumes** $x< 2\hat{}n$ **shows** *high* $(y*2\hat{}n + x)$ $n = y$ ⟨*proof*⟩

lemma *both-member-options-from-chilf-to-complete-tree*:
assumes *high x* (*deg div 2*) < *length treeList* **and** *deg* ≥*1* **and** *both-member-options* (*treeList* ! (*high x* (*deg div 2*))) (*low x* (*deg div 2*))
shows *both-member-options* (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*) *x*
⟨*proof*⟩

lemma *both-member-options-from-complete-tree-to-child*:
assumes *deg* ≥*1* **and** *both-member-options* (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*) *x*
shows *both-member-options* (*treeList* ! (*high x* (*deg div 2*))) (*low x* (*deg div 2*)) ∨ *x* = *mi* ∨ *x* = *ma*
⟨*proof*⟩

lemma *pow-sum*: (*divide*::*nat* ⇒ *nat* ⇒ *nat*) ((*2*::*nat*) ^((*a*::*nat*)+(*b*::*nat*))) (*2*^*a*) = *2*^*b*
⟨*proof*⟩

fun *elim-dead*::*VEBT* ⇒ *enat* ⇒ *VEBT* **where**
elim-dead (*Leaf a b*) - = *Leaf a b* |
elim-dead (*Node info deg treeList summary*) ∞ =
(*Node info deg* (*map* (λ *t*. *elim-dead t* (*enat* (*2*^(*deg div 2*)))) *treeList*)
(*elim-dead summary* ∞))|
elim-dead (*Node info deg treeList summary*) (*enat l*) =
(*Node info deg* (*take* (*l div* (*2*^(*deg div 2*))) (*map* (λ *t*. *elim-dead t* (*enat* (*2*^(*deg div 2*))))*treeList*))
(*elim-dead summary* ((*enat* (*l div* (*2*^(*deg div 2*)))))))

lemma *elimnum*: *invar-vebt* (*Node info deg treeList summary*) *n* ⟹
elim-dead (*Node info deg treeList summary*) (*enat* ((*2*::*nat*)^*n*)) = (*Node info deg treeList summary*)
⟨*proof*⟩

lemma *elimcomplete*:
assumes *invar-vebt* (*Node info deg treeList summary*) *n*
shows *elim-dead* (*Node info deg treeList summary*) ∞ = (*Node info deg treeList summary*)
⟨*proof*⟩

end
end

theory *VEBT-Member* **imports** *VEBT-Definitions*
begin

2 Member Function

context begin
interpretation *VEBT-internal* ⟨*proof*⟩

fun *vebt-member* :: *VEBT* ⇒ *nat* ⇒ *bool* **where**
vebt-member (*Leaf a b*) *x* = (*if x = 0 then a else if x = 1 then b else False*)|

```
  vebt-member (Node None - - -) x = False|
  vebt-member (Node - 0 - -) x = False|
  vebt-member (Node - (Suc 0) - -) x = False|
  vebt-member (Node (Some (mi, ma)) deg treeList summary) x = (
    if x = mi then True else
    if x = ma then True else
    if x < mi then False else
    if x > ma then False else (
     let h = high x (deg div 2);
         l = low x (deg div 2) in(
          if h < length treeList
          then vebt-member (treeList ! h) l
          else False)))

end

context VEBT-internal begin

lemma member-inv:
  assumes vebt-member  (Node (Some (mi, ma)) deg treeList summary) x
  shows deg ≥ 2 ∧
        (x = mi ∨ x = ma ∨ (x < ma ∧ x > mi ∧  high x (deg div 2) < length treeList ∧
                              vebt-member (treeList ! ( high x (deg div 2))) (low x (deg div 2))))
⟨proof⟩


definition bit-concat::nat ⇒ nat ⇒ nat ⇒ nat where
bit-concat h l d = h∗2^d + l

lemma bit-split-inv: bit-concat (high x d) (low x d) d = x
  ⟨proof⟩

definition set-vebt'::VEBT ⇒ nat set where
  set-vebt' t = {x. vebt-member t x}

lemma Leaf-0-not: assumes invar-vebt (Leaf a b) 0 shows  False
⟨proof⟩

lemma  valid-0-not: invar-vebt t 0 ⟹ False
⟨proof⟩

theorem valid-tree-deg-neq-0: (¬ invar-vebt t 0)
  ⟨proof⟩

lemma deg-1-Leafy:  invar-vebt t n ⟹ n = 1 ⟹ ∃ a b. t = Leaf a b
  ⟨proof⟩

lemma deg-1-Leaf: invar-vebt t 1 ⟹  ∃ a b. t = Leaf a b
  ⟨proof⟩
```

corollary *deg1Leaf*: *invar-vebt t 1* $\longleftrightarrow$ $(\exists\ a\ b.\ t = Leaf\ a\ b)$
⟨*proof*⟩

lemma *deg-SUcn-Node*: **assumes** *invar-vebt tree* (*Suc* (*Suc n*)) **shows**
$\exists$ *info treeList s. tree* = *Node info* (*Suc* (*Suc n*)) *treeList s*
⟨*proof*⟩

lemma *invar-vebt* (*Node info deg treeList summary*) *deg* $\Longrightarrow$ *deg* > *1*
⟨*proof*⟩

lemma *deg-deg-n*: **assumes** *invar-vebt* (*Node info deg treeList summary*) *n* **shows** *deg* = *n*
⟨*proof*⟩

lemma *member-valid-both-member-options*:
invar-vebt tree n $\Longrightarrow$ *vebt-member tree x* $\Longrightarrow$ (*naive-member tree x* $\vee$ *membermima tree x*)
⟨*proof*⟩

lemma *member-bound*: *vebt-member tree x* $\Longrightarrow$ *invar-vebt tree n* $\Longrightarrow$ *x* < *2^n*
⟨*proof*⟩

theorem *inrange*: **assumes** *invar-vebt t n* **shows** *set-vebt' t* $\subseteq$ {*0..2^n−1*}
⟨*proof*⟩

theorem *buildup-gives-empty*: *set-vebt'* (*vebt-buildup n*) = {}
⟨*proof*⟩

fun *minNull*::*VEBT* $\Rightarrow$ *bool* **where**
minNull (*Leaf False False*) = *True*|
minNull (*Leaf - -*) = *False*|
minNull (*Node None - - -*) = *True*|
minNull (*Node* (*Some -*) *- - -*) = *False*

lemma *min-Null-member*: *minNull t* $\Longrightarrow$ $\neg$ *vebt-member t x*
⟨*proof*⟩

lemma *not-min-Null-member*: $\neg$ *minNull t* $\Longrightarrow$ $\exists$ *y. both-member-options t y*
⟨*proof*⟩

lemma *valid-member-both-member-options*: *invar-vebt t n* $\Longrightarrow$ *both-member-options t x* $\Longrightarrow$ *vebt-member t x*
⟨*proof*⟩

corollary *both-member-options-equiv-member*: **assumes** *invar-vebt t n*
shows *both-member-options t x* $\longleftrightarrow$ *vebt-member t x*
⟨*proof*⟩

lemma *member-correct*: *invar-vebt t n* $\Longrightarrow$ *vebt-member t x* $\longleftrightarrow$ *x* $\in$ *set-vebt t*
⟨*proof*⟩

corollary *set-vebt-set-vebt'-valid*: **assumes** *invar-vebt t n* **shows** *set-vebt t =set-vebt' t*
⟨*proof*⟩

lemma *set-vebt-finite*: *invar-vebt t n* ⟹ *finite* (*set-vebt' t*)
⟨*proof*⟩

lemma *mi-eq-ma-no-ch*:**assumes** *invar-vebt* (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*) *deg* **and** *mi* = *ma*
shows (∀ *t* ∈ *set treeList*. ∄ *x*. *both-member-options t x*) ∧ (∄ *x*. *both-member-options summary x*)
⟨*proof*⟩

end
end

theory *VEBT-Insert* **imports** *VEBT-Member*
begin

3 Insert Function

context begin
interpretation *VEBT-internal* ⟨*proof*⟩

fun *vebt-insert* :: *VEBT* ⇒ *nat* ⇒*VEBT* **where**
vebt-insert (*Leaf a b*) *x* = (*if x=0 then Leaf True b else if x = 1 then Leaf a True else Leaf a b*)|
vebt-insert (*Node info 0 ts s*) *x* = (*Node info 0 ts s*)|
vebt-insert (*Node info* (*Suc 0*) *ts s*) *x* = (*Node info* (*Suc 0*) *ts s*)|
vebt-insert (*Node None* (*Suc deg*) *treeList summary*) *x* =
(*Node* (*Some* (*x*,*x*)) (*Suc deg*) *treeList summary*)|
vebt-insert (*Node* (*Some* (*mi*,*ma*)) *deg treeList summary*) *x* = (
let xn = (*if x* < *mi then mi else x*);
minn = (*if x* < *mi then x else mi*);
l = *low xn* (*deg div 2*);
h = *high xn* (*deg div 2*) *in* (
if h < *length treeList* ∧ ¬ (*x* = *mi* ∨ *x* = *ma*) *then*
Node (*Some* (*minn*, *max xn ma*)) *deg* (*treeList*[*h*:= *vebt-insert* (*treeList* ! *h*) *l*])
(*if minNull* (*treeList* ! *h*) *then vebt-insert summary h else summary*)
else (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*)))

end

context *VEBT-internal* **begin**

lemma *insert-simp-norm*:
assumes *high x* (*deg div 2*) < *length treeList* **and** (*mi*::*nat*)< *x* **and** *deg*≥ *2* **and** *x* ≠ *ma*
shows *vebt-insert* (*Node* (*Some* (*mi*,*ma*)) *deg treeList summary*) *x* =
Node (*Some* (*mi*, *max x ma*)) *deg* (*treeList* [(*high x* (*deg div 2*)):= *vebt-insert* (*treeList* ! (*high x* (*deg div 2*))) (*low x* (*deg div 2*))])

(*if minNull* (*treeList* ! (*high x* (*deg div 2*))) *then* *vebt-insert summary* (*high x* (*deg div 2*)) *else summary*)
⟨*proof*⟩

lemma *insert-simp-excp*:
assumes *high mi* (*deg div 2*) < *length treeList* **and** (*x*::*nat*) < *mi* **and** *deg*≥ *2* **and** *x* ≠ *ma*
shows *vebt-insert* (*Node* (*Some* (*mi*,*ma*)) *deg treeList summary*) *x* =
Node (*Some* (*x*, *max mi ma*)) *deg* (*treeList*[(*high mi* (*deg div 2*)) := *vebt-insert* (*treeList* ! (*high mi* (*deg div 2*))) (*low mi* (*deg div 2*))])
(*if minNull* (*treeList* ! (*high mi* (*deg div 2*))) *then* *vebt-insert summary* (*high mi* (*deg div 2*)) *else summary*)
⟨*proof*⟩

lemma *insert-simp-mima*: **assumes** *x* = *mi* ∨ *x* = *ma* **and** *deg* ≥ *2*
shows *vebt-insert* (*Node* (*Some* (*mi*,*ma*)) *deg treeList summary*) *x* = (*Node* (*Some* (*mi*,*ma*)) *deg treeList summary*)
⟨*proof*⟩

lemma *valid-insert-both-member-options-add*: *invar-vebt t n* ⟹ *x*< *2*^*n* ⟹ *both-member-options* (*vebt-insert t x*) *x*
⟨*proof*⟩

lemma *valid-insert-both-member-options-pres*: *invar-vebt t n* ⟹ *x*<*2*^*n* ⟹ *y* < *2*^*n* ⟹ *both-member-options t x*
⟹ *both-member-options* (*vebt-insert t y*) *x*
⟨*proof*⟩

lemma *post-member-pre-member*:*invar-vebt t n* ⟹ *x*< *2*^*n* ⟹ *y* <*2*^*n* ⟹ *vebt-member* (*vebt-insert t x*) *y* ⟹ *vebt-member t y* ∨ *x* = *y*
⟨*proof*⟩

end
end

theory *VEBT-InsertCorrectness* **imports** *VEBT-Member VEBT-Insert*
begin

context *VEBT-internal* **begin**

4 Correctness of the Insert Operation

4.1 Validness Preservation

theorem *valid-pres-insert*: *invar-vebt t n* ⟹ *x*< *2*^*n* ⟹ *invar-vebt* (*vebt-insert t x*) *n*
⟨*proof*⟩

4.2 Correctness with Respect to Set Interpretation

theorem *insert-corr*:
assumes *invar-vebt t n* **and** $x < 2\hat{}n$
shows *set-vebt' t* $\cup$ $\{x\}$ = *set-vebt' (vebt-insert t x)*
⟨*proof*⟩

corollary *insert-correct*: **assumes** *invar-vebt t n* **and** $x < 2\hat{}n$ **shows**
set-vebt t $\cup$ $\{x\}$ = *set-vebt (vebt-insert t x)*
⟨*proof*⟩

fun *insert'*::*VEBT* ⇒ *nat* ⇒ *VEBT* **where**
insert' (Leaf a b) x = vebt-insert (Leaf a b) x|
insert' (Node info deg treeList summary) x =
(if x ≥ $2\hat{}$*deg then (Node info deg treeList summary)*
else vebt-insert (Node info deg treeList summary) x)

theorem *insert'-pres-valid*: **assumes** *invar-vebt t n* **shows** *invar-vebt (insert' t x) n*
⟨*proof*⟩

theorem *insert'-correct*: **assumes** *invar-vebt t n*
shows *set-vebt (insert' t x)* = *(set-vebt t* $\cup$ $\{x\}$*)*$\cap\{0..2\hat{}n-1\}$
⟨*proof*⟩

end
end

theory *VEBT-MinMax* **imports** *VEBT-Member*
begin

5 The Minimum and Maximum Operation

fun *vebt-mint* :: *VEBT* ⇒ *nat option* **where**
vebt-mint (Leaf a b) = (if a then Some 0 else if b then Some 1 else None)|
vebt-mint (Node None - - -) = None|
vebt-mint (Node (Some (mi,ma)) - - -) = Some mi

fun *vebt-maxt* :: *VEBT* ⇒ *nat option* **where**
vebt-maxt (Leaf a b) = (if b then Some 1 else if a then Some 0 else None)|
vebt-maxt (Node None - - -) = None|
vebt-maxt (Node (Some (mi,ma)) - - -) = Some ma

context *VEBT-internal* **begin**

fun *option-shift*::('*a*⇒'*a*⇒'*a*) ⇒'*a option* ⇒'*a option*⇒ '*a option* **where**
option-shift - None - = None|
option-shift - - None = None|

option-shift f (Some a) (Some b) = Some (f a b)

definition *power*::*nat option* ⇒ *nat option* ⇒ *nat option* (**infixl**‹$\widehat{}_o$› *81*) **where**
power= *option-shift* (^)

definition *add*::*nat option* ⇒ *nat option* ⇒ *nat option* (**infixl**‹$+_o$› *79*) **where**
add= *option-shift* (+)

definition *mul*::*nat option* ⇒ *nat option* ⇒ *nat option* (**infixl**‹$*_o$› *80*) **where**
mul = *option-shift* (∗)

fun *option-comp-shift*::('*a* ⇒ '*a* ⇒ *bool*) ⇒ '*a option* ⇒ '*a option* ⇒ *bool* **where**
option-comp-shift - None - = False|
option-comp-shift - - None = False|
option-comp-shift f (Some x) (Some y) = f x y

fun *less*::*nat option* ⇒ *nat option* ⇒ *bool* (**infixl**‹$<_o$› *80*) **where**
less x y= *option-comp-shift* (<) *x y*

fun *lesseq*::*nat option* ⇒ *nat option* ⇒ *bool* (**infixl**‹$\leq_o$› *80*) **where**
lesseq x y = *option-comp-shift* (≤) *x y*

fun *greater*::*nat option* ⇒ *nat option* ⇒ *bool* (**infixl**‹$>_o$› *80*) **where**
greater x y = *option-comp-shift* (>) *x y*

lemma *add-shift*:*x*+*y* = *z* ⟷ *Some x* +$_o$ *Some y* = *Some z*
⟨*proof*⟩

lemma *mul-shift*:*x*∗*y* = *z* ⟷ *Some x* ∗$_o$ *Some y* = *Some z* ⟨*proof*⟩

lemma *power-shift*:*x*^*y* = *z* ⟷ *Some x* ^$_o$ *Some y* = *Some z* ⟨*proof*⟩

lemma *less-shift*: *x* < *y* ⟷ *Some x* <$_o$ *Some y* ⟨*proof*⟩

lemma *lesseq-shift*: *x* ≤ *y* ⟷ *Some x* ≤$_o$ *Some y* ⟨*proof*⟩

lemma *greater-shift*: *x* > *y* ⟷ *Some x* >$_o$ *Some y* ⟨*proof*⟩

definition *max-in-set* :: *nat set* ⇒ *nat* ⇒ *bool* **where**
max-in-set xs x ⟷ (*x* ∈ *xs* ∧ (∀ *y* ∈ *xs*. *y* ≤ *x*))

lemma *maxt-member*: *invar-vebt t n* ⟹ *vebt-maxt t* = *Some maxi* ⟹ *vebt-member t maxi*
⟨*proof*⟩

lemma *maxt-corr-help*:
assumes *invar-vebt t n vebt-maxt t* = *Some maxi vebt-member t x*
shows *maxi* ≥ *x*
⟨*proof*⟩

lemma *maxt-corr-help-empty*: *invar-vebt t n* $\Longrightarrow$ *vebt-maxt t* = *None* $\Longrightarrow$ *set-vebt′ t* = {}
⟨*proof*⟩

theorem *maxt-corr*:**assumes** *invar-vebt t n* **and** *vebt-maxt t* = *Some x* **shows** *max-in-set* (*set-vebt′ t*) *x*
⟨*proof*⟩

theorem *maxt-sound*:**assumes** *invar-vebt t n* **and** *max-in-set* (*set-vebt′ t*) *x* **shows** *vebt-maxt t* = *Some x*
⟨*proof*⟩

definition *min-in-set* :: *nat set* ⇒ *nat* ⇒ *bool* **where**
min-in-set xs x $\longleftrightarrow$ (*x* ∈ *xs* ∧ (∀ *y* ∈ *xs*. *y* ≥ *x*))

lemma *mint-member*: *invar-vebt t n* $\Longrightarrow$ *vebt-mint t* = *Some maxi* $\Longrightarrow$ *vebt-member t maxi*
⟨*proof*⟩

lemma *mint-corr-help*:
assumes *invar-vebt t n vebt-mint t* = *Some mini vebt-member t x*
shows *mini* ≤ *x*
⟨*proof*⟩

lemma *mint-corr-help-empty*: *invar-vebt t n* $\Longrightarrow$ *vebt-mint t* = *None* $\Longrightarrow$ *set-vebt′ t* = {}
⟨*proof*⟩

theorem *mint-corr*:**assumes** *invar-vebt t n* **and** *vebt-mint t* = *Some x* **shows** *min-in-set* (*set-vebt′ t*) *x*
⟨*proof*⟩

theorem *mint-sound*:**assumes** *invar-vebt t n* **and** *min-in-set* (*set-vebt′ t*) *x* **shows** *vebt-mint t* = *Some x*
⟨*proof*⟩

lemma *summaxma*:**assumes** *invar-vebt* (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*) *deg* **and** *mi* ≠ *ma*
shows *the* (*vebt-maxt summary*) = *high ma* (*deg div 2*)
⟨*proof*⟩

lemma *maxbmo*: *vebt-maxt t* = *Some x* $\Longrightarrow$ *both-member-options t x*
⟨*proof*⟩

lemma *misiz*:*invar-vebt t n* $\Longrightarrow$ *Some m* = *vebt-mint t* $\Longrightarrow$ *m* < 2^*n*
⟨*proof*⟩

lemma *mintlistlength*: **assumes** *invar-vebt* (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*) *n*

mi ≠ *ma* **shows** *ma* > *mi* ∧ (∃ *m*. *Some m* = *vebt-mint summary* ∧ *m* < 2^(*n* − *n div* 2))
⟨*proof*⟩

lemma *power-minus-is-div*:
b ≤ *a* ⟹ (2 :: *nat*) ^ (*a* − *b*) = 2 ^ *a div* 2 ^ *b*
⟨*proof*⟩

lemma *nested-mint*:**assumes** *invar-vebt* (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*) *n* *n* = *Suc* (*Suc va*)
¬ *ma* < *mi* *ma* ≠ *mi* **shows**
high (*the* (*vebt-mint summary*) ∗ (2 ∗ 2 ^ (*va div* 2)) + *the* (*vebt-mint* (*treeList* ! *the* (*vebt-mint summary*)))) (*Suc* (*va div* 2))
< *length treeList*
⟨*proof*⟩

lemma *minminNull*: *vebt-mint t* = *None* ⟹ *minNull t*
⟨*proof*⟩

lemma *minNullmin*: *minNull t* ⟹ *vebt-mint t* = *None*
⟨*proof*⟩

end
end

theory *VEBT-Succ* **imports** *VEBT-Insert VEBT-MinMax*
begin

6 The Successor Operation

definition *is-succ-in-set* :: *nat set* ⇒ *nat* ⇒ *nat* ⇒ *bool* **where**
is-succ-in-set xs x y = (*y* ∈ *xs* ∧ *y* > *x* ∧ (∀ *z* ∈ *xs*. (*z* > *x* ⟶ *z* ≥ *y*)))

context *VEBT-internal* **begin**

corollary *succ-member*: *is-succ-in-set* (*set-vebt' t*) *x y* = (*vebt-member t y* ∧ *y* > *x* ∧ (∀ *z*. *vebt-member t z* ∧ *z* > *x* ⟶ *z* ≥ *y*))
⟨*proof*⟩

6.1 Auxiliary Lemmas on Sets and Successorship

lemma *finite* (*A*:: *nat set*) ⟹ *A* ≠ {}⟹ *Min A* ∈ *A*
⟨*proof*⟩

lemma *obtain-set-succ*: **assumes** (*x*::*nat*) < *z* **and** *max-in-set A z* **and** *finite B* **and** *A*=*B* **shows** ∃ *y*. *is-succ-in-set A x y*
⟨*proof*⟩

lemma *succ-none-empty*: **assumes** (∄ *x*. *is-succ-in-set* (*xs*) *a x*) **and** *finite xs***shows** ¬ (∃ *x* ∈ *xs*.

ord-class.greater x a)
⟨*proof*⟩

end

6.2 The actual Function

context begin
interpretation *VEBT-internal* ⟨*proof*⟩

fun *vebt-succ* :: *VEBT* ⇒ *nat* ⇒ *nat option* **where**
vebt-succ (*Leaf* - *b*) *0* = (*if b then Some 1 else None*)|
vebt-succ (*Leaf* - -) (*Suc n*) = *None*|
vebt-succ (*Node None* - - -) - = *None*|
vebt-succ (*Node* - *0* - -) - = *None*|
vebt-succ (*Node* - (*Suc 0*) - -) - = *None*|
vebt-succ (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*) *x* = (
if x < *mi then* (*Some mi*)
else (*let l* = *low x* (*deg div 2*); *h* = *high x* (*deg div 2*) *in*
if h < *length treeList then*
let maxlow = *vebt-maxt* (*treeList* ! *h*) *in* (
if maxlow ≠ *None* ∧ (*Some l* <$_o$ *maxlow*) *then*
Some (*2*^(*deg div 2*)) *∗*$_o$ *Some h* +$_o$ *vebt-succ* (*treeList* ! *h*) *l*
else let sc = *vebt-succ summary h in*
if sc = *None then None*
else Some (*2*^(*deg div 2*)) *∗*$_o$ *sc* +$_o$ *vebt-mint* (*treeList* ! *the sc*))
else None))

end

6.3 Lemmas for Term Decomposition

context *VEBT-internal* **begin**

lemma *succ-min*: **assumes** *deg* ≥ *2* **and** (*x*::*nat*) < *mi* **shows**
vebt-succ (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*) *x* = *Some mi*
⟨*proof*⟩

lemma *succ-greatereq-min*: **assumes** *deg* ≥ *2* **and** (*x*::*nat*) ≥ *mi* **shows**
vebt-succ (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*) *x* = (*let l* = *low x* (*deg div 2*); *h* = *high x* (*deg div 2*) *in*
if h < *length treeList then*

let maxlow = *vebt-maxt* (*treeList* ! *h*) *in*
(*if maxlow* ≠ *None* ∧ (*Some l* <$_o$ *maxlow*) *then*
Some (*2*^(*deg div 2*)) *∗*$_o$ *Some h* +$_o$ *vebt-succ* (*treeList* ! *h*) *l*
else let sc = *vebt-succ summary h in*
if sc = *None then None*
else Some (*2*^(*deg div 2*)) *∗*$_o$ *sc* +$_o$ *vebt-mint* (*treeList* ! *the sc*))

else None)
⟨*proof*⟩

lemma *succ-list-to-short*: **assumes** $deg \geq 2$ **and** $x \geq mi$ **and** $high\ x\ (deg\ div\ 2) \geq length\ treeList$ **shows**
vebt-succ (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*) *x* = *None*
⟨*proof*⟩

lemma *succ-less-length-list*: **assumes** $deg \geq 2$ **and** $x \geq mi$ **and** $high\ x\ (deg\ div\ 2) < length\ treeList$ **shows**
vebt-succ (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*) *x* =
(*let l* = *low x* (*deg div 2*); *h* = *high x* (*deg div 2*) ; *maxlow* = *vebt-maxt* (*treeList* ! *h*) *in*
(*if maxlow* ≠ *None* ∧ (*Some l* <$_o$ *maxlow*) *then*
Some (2^(*deg div 2*)) *∗*$_o$ *Some h* +$_o$ *vebt-succ* (*treeList* ! *h*) *l*
else let sc = *vebt-succ summary h in*
if sc = *None then None*
else Some (2^(*deg div 2*)) *∗*$_o$ *sc* +$_o$ *vebt-mint* (*treeList* !*the sc*)))
⟨*proof*⟩

6.4 Correctness Proof

theorem *succ-corr*: *invar-vebt t n* ⟹ *vebt-succ t x* = *Some sx* == *is-succ-in-set* (*set-vebt′ t*) *x sx*
⟨*proof*⟩

corollary *succ-empty*: **assumes** *invar-vebt t n*
shows (*vebt-succ t x* = *None*) = ({*y*. *vebt-member t y* ∧ *y* > *x*} = {})
⟨*proof*⟩

theorem *succ-correct*: *invar-vebt t n* ⟹ *vebt-succ t x* = *Some sx* ⟷*is-succ-in-set* (*set-vebt t*) *x sx*
⟨*proof*⟩

lemma *is-succ-in-set S x y* ⟷ *min-in-set* {*s* . *s* ∈ *S* ∧ *s* > *x*} *y*
⟨*proof*⟩

lemma *helpyd*:*invar-vebt t n* ⟹ *vebt-succ t x* = *Some y* ⟹ *y* < 2^*n*
⟨*proof*⟩

lemma *geqmaxNone*:
assumes *invar-vebt* (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*) *n x* ≥ *ma*
shows *vebt-succ* (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*) *x* = *None*
⟨*proof*⟩

end
end

theory *VEBT-Pred* **imports** *VEBT-MinMax VEBT-Insert*
begin

7 The Predecessor Operation

definition *is-pred-in-set* :: *nat set* ⇒ *nat* ⇒ *nat* ⇒ *bool* **where**
is-pred-in-set xs x y = (*y* ∈ *xs* ∧ *y* < *x* ∧ (∀ *z* ∈ *xs*. (*z* < *x* ⟶ *z* ≤ *y*)))

context *VEBT-internal* **begin**

7.1 Lemmas on Sets and Predecessorship

corollary *pred-member*: *is-pred-in-set* (*set-vebt'* *t*) *x y* = (*vebt-member t y* ∧ *y* < *x* ∧ (∀ *z*. *vebt-member t z* ∧ *z* < *x* ⟶ *z* ≤ *y*))
⟨*proof*⟩

lemma *finite* (*A*:: *nat set*) ⟹ *A* ≠ {}⟹ *Max A* ∈ *A*
⟨*proof*⟩

lemma *obtain-set-pred*: **assumes** (*x*::*nat*) > *z* **and** *min-in-set A z* **and** *finite A* **shows** ∃ *y*. *is-pred-in-set A x y*
⟨*proof*⟩

lemma *pred-none-empty*: **assumes** (∄ *x*. *is-pred-in-set* (*xs*) *a x*) **and** *finite xs***shows** ¬ (∃ *x* ∈ *xs*. *ord-class.less x a*)
⟨*proof*⟩

end

7.2 The actual Function for Predecessor Search

context begin
interpretation *VEBT-internal* ⟨*proof*⟩

fun *vebt-pred* :: *VEBT* ⇒ *nat* ⇒ *nat option* **where**
vebt-pred (*Leaf* - -) *0* = *None*|
vebt-pred (*Leaf a* -) (*Suc 0*) = (*if a then Some 0 else None*)|
vebt-pred (*Leaf a b*) - = (*if b then Some 1 else if a then Some 0 else None*)|
vebt-pred (*Node None* - - -) - = *None*|
vebt-pred (*Node* - *0* - -) - = *None*|
vebt-pred (*Node* - (*Suc 0*) - -) - = *None*|
vebt-pred (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*) *x* = (
  if x > *ma then Some ma*
  else (*let l* = *low x* (*deg div 2*); *h* = *high x* (*deg div 2*) *in*
    if h < *length treeList then*
      let minlow = *vebt-mint* (*treeList* ! *h*) *in* (
        if minlow ≠ *None* ∧ (*Some l* >*o* *minlow*) *then*
          Some (*2*^(*deg div 2*)) ∗*o* *Some h* +*o* *vebt-pred* (*treeList* ! *h*) *l*
        else let pr = *vebt-pred summary h in*
          if pr = *None then* (
            if x > *mi then Some mi*
            else None)
          else Some (*2*^(*deg div 2*)) ∗*o* *pr* +*o* *vebt-maxt* (*treeList* ! *the pr*))

else None))

end

context *VEBT-internal* **begin**

7.3 Auxiliary Lemmas

lemma *pred-max*:
assumes $deg \geq 2$ **and** $(x::nat) > ma$
shows *vebt-pred* (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*) x = *Some ma*
⟨*proof*⟩

lemma *pred-lesseq-max*:
assumes $deg \geq 2$ **and** $(x::nat) \leq ma$
shows *vebt-pred* (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*) x = (*let* l = *low* x (*deg div 2*); h = *high* x (*deg div 2*) *in*
if $h <$ *length treeList then*

let minlow = *vebt-mint* (*treeList* ! h) *in*
(*if minlow* ≠ *None* ∧ (*Some* $l >_o$ *minlow*) *then*
Some (2^(*deg div 2*)) $*_o$ *Some* h $+_o$ *vebt-pred* (*treeList* ! h) l
else let pr = *vebt-pred summary h in*
if pr = *None then* (*if* $x >$ *mi then Some mi else None*)
else Some (2^(*deg div 2*)) $*_o$ *pr* $+_o$ *vebt-maxt* (*treeList* ! *the pr*))

else None)
⟨*proof*⟩

lemma *pred-list-to-short*:
assumes $deg \geq 2$ **and** *ord-class.less-eq x ma* **and** *high x* (*deg div 2*) ≥ *length treeList*
shows *vebt-pred* (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*) x = *None*
⟨*proof*⟩

lemma *pred-less-length-list*:
assumes $deg \geq 2$ **and** *ord-class.less-eq x ma* **and** *high x* (*deg div 2*) < *length treeList*
shows
vebt-pred (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*) x = (*let* l = *low* x (*deg div 2*); h = *high* x (*deg div 2*); *minlow* = *vebt-mint* (*treeList* ! h) *in*
(*if minlow* ≠ *None* ∧ (*Some* $l >_o$ *minlow*) *then*
Some (2^(*deg div 2*)) $*_o$ *Some* h $+_o$ *vebt-pred* (*treeList* ! h) l
else let pr = *vebt-pred summary h in*
if pr = *None then* (*if* $x >$ *mi then Some mi else None*)
else Some (2^(*deg div 2*)) $*_o$ *pr* $+_o$ *vebt-maxt* (*treeList* ! *the pr*)))
⟨*proof*⟩

7.4 Correctness Proof

theorem *pred-corr*: *invar-vebt t n* ⟹ *vebt-pred t x* = *Some px* == *is-pred-in-set* (*set-vebt'* *t*) *x px*

⟨*proof*⟩

corollary *pred-empty*: **assumes** *invar-vebt t n*
shows (*vebt-pred t x* = *None*) = ({*y*. *vebt-member t y* ∧ *y* < *x*} = {})
⟨*proof*⟩

theorem *pred-correct*: *invar-vebt t n* ⟹ *vebt-pred t x* = *Some sx* ⟷*is-pred-in-set* (*set-vebt t*) *x sx*
⟨*proof*⟩

lemma *helpypredd*:*invar-vebt t n* ⟹ *vebt-pred t x* = *Some y* ⟹ *y* < *2*^*n*
⟨*proof*⟩

lemma *invar-vebt t n* ⟹ *vebt-pred t x* = *Some y* ⟹ *y* < *x*
⟨*proof*⟩

end
end

theory *VEBT-Delete* **imports** *VEBT-Pred VEBT-Succ*
begin

8 Deletion

8.1 Function Definition

context begin
interpretation *VEBT-internal* ⟨*proof*⟩

fun *vebt-delete* :: *VEBT* ⇒ *nat* ⇒ *VEBT* **where**
vebt-delete (*Leaf a b*) *0* = *Leaf False b*|
vebt-delete (*Leaf a b*) (*Suc 0*) = *Leaf a False*|
vebt-delete (*Leaf a b*) (*Suc* (*Suc n*)) = *Leaf a b*|
vebt-delete (*Node None deg treeList summary*) - = (*Node None deg treeList summary*)|
vebt-delete (*Node* (*Some* (*mi*, *ma*)) *0 trLst smry*) *x* = (*Node* (*Some* (*mi*, *ma*)) *0 trLst smry*) |
vebt-delete (*Node* (*Some* (*mi*, *ma*)) (*Suc 0*) *tr sm*) *x* = (*Node* (*Some* (*mi*, *ma*)) (*Suc 0*) *tr sm*) |
vebt-delete (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*) *x* =(
if (*x* < *mi* ∨ *x* > *ma*) *then* (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*)
else if (*x* = *mi* ∧ *x* = *ma*) *then* (*Node None deg treeList summary*)
else let xn = (*if x* = *mi*
then the (*vebt-mint summary*) ∗ *2*^(*deg div 2*)
+ *the* (*vebt-mint* (*treeList* ! *the* (*vebt-mint summary*)))
else x);
minn = (*if x* = *mi then xn else mi*);
l = *low xn* (*deg div 2*);
h = *high xn* (*deg div 2*) *in*
if h < *length treeList*
then(
let newnode = *vebt-delete* (*treeList* ! *h*) *l*;
newlist = *treeList*[*h*:= *newnode*]*in*

```
                    if minNull newnode
                    then( let sn = vebt-delete summary h in(
                        Node (Some (minn, if xn  = ma then
                                        (let maxs = vebt-maxt sn in (
                                         if maxs = None
                                         then minn
                                         else 2^(deg div 2) * the maxs
                                           + the (vebt-maxt (newlist ! the maxs))))
                                    else ma)) deg newlist sn))
                    else (Node (Some (minn, (if xn = ma
                                then h * 2^(deg div 2) + the( vebt-maxt (newlist ! h))
                                else ma))) deg newlist summary ))
            else (Node (Some (mi, ma)) deg treeList summary))
```

end

8.2 Auxiliary Lemmas

context *VEBT-internal* **begin**

context begin

lemma *delt-out-of-range*:
assumes $x < mi \vee x > ma$ **and** $deg \geq 2$
shows
vebt-delete (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*) *x* =(*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*)
⟨*proof*⟩

lemma *del-single-cont*:
assumes $x = mi \wedge x = ma$ **and** $deg \geq 2$
shows *vebt-delete* (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*) *x* = (*Node None deg treeList summary*)
⟨*proof*⟩

lemma *del-in-range*:
assumes $x \geq mi \wedge x \leq ma$ **and** $mi \neq ma$ **and** $deg \geq 2$
shows
vebt-delete (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*) *x* = (*let xn* = (*if x* = *mi*
then the (*vebt-mint summary*) * 2^(*deg div 2*)
+ *the* (*vebt-mint* (*treeList* ! *the* (*vebt-mint summary*)))
else x);
minn = (*if x* = *mi then xn else mi*);
l = *low xn* (*deg div 2*);
h = *high xn* (*deg div 2*) *in*
if h < *length treeList*
then(
let newnode = *vebt-delete* (*treeList* ! *h*) *l*;
newlist = *treeList*[*h*:= *newnode*] *in*

```
                        if minNull newnode
                        then(
                           let sn = vebt-delete summary h in
                          (Node (Some (minn, if xn  = ma then (let maxs = vebt-maxt sn in
                                                          (if maxs = None
                                                             then minn
                                                             else 2^(deg div 2) * the maxs
                                                                 + the (vebt-maxt (newlist ! the maxs))
                                                           )
                                                      )
                                                 else ma))
                                deg newlist sn)
                        )else
                          (Node (Some (minn, (if xn = ma then
                                          h * 2^(deg div 2) + the( vebt-maxt (newlist ! h))
                                             else ma)))
                            deg newlist summary )
                    )else
                     (Node (Some (mi, ma)) deg treeList summary))
⟨proof⟩

lemma del-x-not-mia:
  assumes x > mi ∧ x ≤ ma and mi ≠ ma  and deg ≥ 2  and high x (deg div 2) = h and
  low x (deg div 2) = land  high x (deg div 2) < length treeList
  shows
   vebt-delete (Node (Some (mi, ma)) deg treeList summary) x = (
              let  newnode = vebt-delete (treeList ! h) l;
                    newlist = treeList[h:= newnode] in
                        if minNull newnode
                        then(
                           let sn = vebt-delete summary h in
                          (Node (Some (mi, if x  = ma then (let maxs = vebt-maxt sn in
                                                          (if maxs = None
                                                             then mi
                                                             else 2^(deg div 2) * the maxs
                                                                 + the (vebt-maxt (newlist ! the maxs))
                                                           )
                                                      )
                                                 else ma))
                                deg newlist sn)
                        )else
                          (Node (Some (mi, (if x = ma then
                                          h * 2^(deg div 2) + the( vebt-maxt (newlist ! h))
                                             else ma)))
                            deg newlist summary )
)
  ⟨proof⟩

lemma del-x-not-mi:
```

assumes $x > mi \wedge x \leq ma$ **and** $mi \neq ma$ **and** $deg \geq 2$ **and** $high\ x\ (deg\ div\ 2) = h$ **and**
$low\ x\ (deg\ div\ 2) = l$**and** $newnode = vebt\text{-}delete\ (treeList\ !\ h)\ l$
and $newlist = treeList[h := newnode]$ **and** $high\ x\ (deg\ div\ 2) < length\ treeList$
shows
$vebt\text{-}delete\ (Node\ (Some\ (mi,\ ma))\ deg\ treeList\ summary)\ x = ($
$if\ minNull\ newnode$
$then($
$let\ sn = vebt\text{-}delete\ summary\ h\ in$
$(Node\ (Some\ (mi,\ if\ x = ma\ then\ (let\ maxs = vebt\text{-}maxt\ sn\ in$
$(if\ maxs = None$
$then\ mi$
$else\ 2\hat{}(deg\ div\ 2) * the\ maxs$
$+\ the\ (vebt\text{-}maxt\ (newlist\ !\ the\ maxs))$
$)$
$)$
$else\ ma))$
$deg\ newlist\ sn)$
$)else$
$(Node\ (Some\ (mi,\ (if\ x = ma\ then$
$h * 2\hat{}(deg\ div\ 2) + the(\ vebt\text{-}maxt\ (newlist\ !\ h))$
$else\ ma)))$
$deg\ newlist\ summary\ )$
$)$ ⟨*proof*⟩

lemma *del-x-not-mi-new-node-nil*:
assumes $x > mi \wedge x \leq ma$ **and** $mi \neq ma$ **and** $deg \geq 2$ **and** $high\ x\ (deg\ div\ 2) = h$ **and**
$low\ x\ (deg\ div\ 2) = l$**and** $newnode = vebt\text{-}delete\ (treeList\ !\ h)\ l$ **and** $minNull\ newnode$ **and**
$sn = vebt\text{-}delete\ summary\ h$ **and** $newlist = treeList[h := newnode]$ **and** $high\ x\ (deg\ div\ 2) < length\ treeList$
shows
$vebt\text{-}delete\ (Node\ (Some\ (mi,\ ma))\ deg\ treeList\ summary)\ x = (Node\ (Some\ (mi,\ if\ x = ma\ then\ (let\ maxs = vebt\text{-}maxt\ sn\ in$
$(if\ maxs = None$
$then\ mi$
$else\ 2\hat{}(deg\ div\ 2) * the\ maxs$
$+\ the\ (vebt\text{-}maxt\ (newlist\ !\ the\ maxs))$
$)$
$)$
$else\ ma))\ deg\ newlist\ sn)$
⟨*proof*⟩

lemma *del-x-not-mi-newnode-not-nil*:
assumes $x > mi \wedge x \leq ma$ **and** $mi \neq ma$ **and** $deg \geq 2$ **and** $high\ x\ (deg\ div\ 2) = h$ **and**
$low\ x\ (deg\ div\ 2) = l$**and** $newnode = vebt\text{-}delete\ (treeList\ !\ h)\ l$ **and** $\neg\ minNull\ newnode$ **and**
$newlist = treeList[h := newnode]$ **and**$high\ x\ (deg\ div\ 2) < length\ treeList$
shows
$vebt\text{-}delete\ (Node\ (Some\ (mi,\ ma))\ deg\ treeList\ summary)\ x =$
$(Node\ (Some\ (mi,\ (if\ x = ma\ then$
$h * 2\hat{}(deg\ div\ 2) + the(\ vebt\text{-}maxt\ (newlist\ !\ h))$

```
                                                    else ma)))
                                deg newlist summary )
  ⟨proof⟩

lemma del-x-mia: assumes x = mi ∧ x < ma and mi ≠ ma  and deg ≥ 2
  shows vebt-delete (Node (Some (mi, ma)) deg treeList summary) x =(
            let xn = the (vebt-mint summary) * 2^(deg div 2)
                                + the (vebt-mint (treeList ! the (vebt-mint summary)));
                                    minn = xn;
                l = low xn (deg div 2);
                h = high xn (deg div 2) in
                 if h < length treeList
                    then(
                      let newnode = vebt-delete (treeList ! h) l;
                          newlist = treeList[h:= newnode]in
                        if minNull newnode
                        then(
                           let sn = vebt-delete summary h in
                            (Node (Some (minn, if xn  = ma then (let maxs = vebt-maxt sn in
                                                          (if maxs = None
                                                             then minn
                                                             else 2^(deg div 2) * the maxs
                                                                 + the (vebt-maxt (newlist ! the maxs))
                                                           )
                                                      )
                                                  else ma))
                                    deg newlist sn)
                        )else
                          (Node (Some (minn, (if xn = ma then
                                              h * 2^(deg div 2) + the( vebt-maxt (newlist ! h))
                                                 else ma)))
                             deg newlist summary )
                    )else
                     (Node (Some (mi, ma)) deg treeList summary)
          )
  ⟨proof⟩

lemma del-x-mi:
  assumes x = mi ∧ x < ma and mi ≠ ma  and deg ≥ 2  and high xn (deg div 2) = h and
    xn =  the (vebt-mint summary) * 2^(deg div 2) + the (vebt-mint (treeList ! the (vebt-mint summary)))
    low xn (deg div 2) = land  high xn (deg div 2) < length treeList
  shows
  vebt-delete (Node (Some (mi, ma)) deg treeList summary) x =(
                        let newnode = vebt-delete (treeList ! h) l;
                            newlist = treeList[h:= newnode]in
                          if minNull newnode
                          then(
                             let sn = vebt-delete summary h in
```

$(Node\ (Some\ (xn,\ if\ xn\ =\ ma\ then\ (let\ maxs\ =\ vebt\text{-}maxt\ sn\ in$
$(if\ maxs\ =\ None$
$then\ xn$
$else\ 2\hat{}(deg\ div\ 2)\ *\ the\ maxs$
$+\ the\ (vebt\text{-}maxt\ (newlist\ !\ the\ maxs))$
$)$
$)$
$else\ ma))$
$deg\ newlist\ sn)$
$)else$
$(Node\ (Some\ (xn,\ (if\ xn\ =\ ma\ then$
$h\ *\ 2\hat{}(deg\ div\ 2)\ +\ the(\ vebt\text{-}maxt\ (newlist\ !\ h))$
$else\ ma)))$
$deg\ newlist\ summary\ ))$

⟨*proof*⟩

lemma *del-x-mi-lets-in*:
assumes $x = mi \wedge x < ma$ **and** $mi \neq ma$ **and** $deg \geq 2$ **and** $high\ xn\ (deg\ div\ 2) = h$ **and**
$xn = the\ (vebt\text{-}mint\ summary) * 2\hat{}(deg\ div\ 2) + the\ (vebt\text{-}mint\ (treeList\ !\ the\ (vebt\text{-}mint\ summary)))$
$low\ xn\ (deg\ div\ 2) = l$**and** $high\ xn\ (deg\ div\ 2) < length\ treeList$ **and**
$newnode = vebt\text{-}delete\ (treeList\ !\ h)\ l$ **and** $newlist = treeList[h:= newnode]$
shows $vebt\text{-}delete\ (Node\ (Some\ (mi,\ ma))\ deg\ treeList\ summary)\ x =($ $if\ minNull\ newnode$
$then($
$let\ sn = vebt\text{-}delete\ summary\ h\ in$
$(Node\ (Some\ (xn,\ if\ xn\ =\ ma\ then\ (let\ maxs\ =\ vebt\text{-}maxt\ sn\ in$
$(if\ maxs\ =\ None$
$then\ xn$
$else\ 2\hat{}(deg\ div\ 2)\ *\ the\ maxs$
$+\ the\ (vebt\text{-}maxt\ (newlist\ !\ the\ maxs))$
$)$
$)$
$else\ ma))$
$deg\ newlist\ sn)$
$)else$
$(Node\ (Some\ (xn,\ (if\ xn\ =\ ma\ then$
$h\ *\ 2\hat{}(deg\ div\ 2)\ +\ the(\ vebt\text{-}maxt\ (newlist\ !\ h))$
$else\ ma)))$
$deg\ newlist\ summary\ ))$

⟨*proof*⟩

lemma *del-x-mi-lets-in-minNull*:
assumes $x = mi \wedge x < ma$ **and** $mi \neq ma$ **and** $deg \geq 2$ **and** $high\ xn\ (deg\ div\ 2) = h$ **and**
$xn = the\ (vebt\text{-}mint\ summary) * 2\hat{}(deg\ div\ 2) + the\ (vebt\text{-}mint\ (treeList\ !\ the\ (vebt\text{-}mint\ summary)))$
$low\ xn\ (deg\ div\ 2) = l$**and** $high\ xn\ (deg\ div\ 2) < length\ treeList$ **and**
$newnode = vebt\text{-}delete\ (treeList\ !\ h)\ l$ **and** $newlist = treeList[h:= newnode]$ **and**
$minNull\ newnode$ **and** $sn = vebt\text{-}delete\ summary\ h$

shows
vebt-delete (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*) *x* =
(*Node* (*Some* (*xn*, *if xn* = *ma then* (*let maxs* = *vebt-maxt sn in*
(*if maxs* = *None*
then xn
else 2^(*deg div* 2) ∗ *the maxs*
+ *the* (*vebt-maxt* (*newlist* ! *the maxs*))
)
)
else ma)) *deg newlist sn*)
⟨*proof*⟩

lemma *del-x-mi-lets-in-not-minNull*:
assumes *x* = *mi* ∧ *x* < *ma* **and** *mi* ≠ *ma* **and** *deg* ≥ 2 **and** *high xn* (*deg div* 2) = *h* **and**
xn = *the* (*vebt-mint summary*) ∗ 2^(*deg div* 2) + *the* (*vebt-mint* (*treeList* ! *the* (*vebt-mint summary*)))
low xn (*deg div* 2) = *l***and** *high xn* (*deg div* 2) < *length treeList* **and**
newnode = *vebt-delete* (*treeList* ! *h*) *l* **and** *newlist* = *treeList*[*h*:= *newnode*] **and**
¬*minNull newnode*
shows
vebt-delete (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*) *x* =
(*Node* (*Some* (*xn*, (*if xn* = *ma then*
h ∗ 2^(*deg div* 2) + *the*(*vebt-maxt* (*newlist* ! *h*))
else ma)))
deg newlist summary)
⟨*proof*⟩

theorem *dele-bmo-cont-corr*:*invar-vebt t n* ⟹ (*both-member-options* (*vebt-delete t x*) *y* ⟷ *x* ≠ *y* ∧ *both-member-options t y*)
⟨*proof*⟩

end

corollary *invar-vebt t n* ⟹ *both-member-options t x* ⟹ *x* ≠ *y* ⟹ *both-member-options* (*vebt-delete t y*) *x*
⟨*proof*⟩

corollary *invar-vebt t n* ⟹ *both-member-options t x* ⟹ ¬ *both-member-options* (*vebt-delete t x*) *x*
⟨*proof*⟩

corollary *invar-vebt t n* ⟹ *both-member-options* (*vebt-delete t y*) *x* ⟹ *both-member-options t x* ∧ *x* ≠ *y*
⟨*proof*⟩

end
end

theory *VEBT-DeleteCorrectness* **imports** *VEBT-Delete*
begin

context *VEBT-internal* **begin**

8.3 Validness Preservation

theorem *delete-pres-valid*: *invar-vebt t n* $\Longrightarrow$ *invar-vebt* (*vebt-delete t x*) *n*
⟨*proof*⟩

corollary *dele-member-cont-corr*:*invar-vebt t n* $\Longrightarrow$ (*vebt-member* (*vebt-delete t x*) *y* $\longleftrightarrow$ $x \neq y \wedge$ *vebt-member t y*)
⟨*proof*⟩

8.4 Correctness with Respect to Set Interpretation

theorem *delete-correct′*: **assumes** *invar-vebt t n*
shows *set-vebt′* (*vebt-delete t x*) = *set-vebt′ t* − {*x*}
⟨*proof*⟩

corollary *delete-correct*: **assumes** *invar-vebt t n*
shows *set-vebt′* (*vebt-delete t x*) = *set-vebt t* − {*x*}
⟨*proof*⟩

end
end

theory *VEBT-Uniqueness* **imports** *VEBT-InsertCorrectness VEBT-Succ VEBT-Pred VEBT-DeleteCorrectness*
begin

context *VEBT-internal* **begin**

9 Uniqueness Property of valid Trees

Two valid van Emde Boas trees having equal degree number and representing the same integer set are equal.

theorem *uniquetree*: *invar-vebt t n* $\Longrightarrow$ *invar-vebt s n* $\Longrightarrow$ *set-vebt′ t* = *set-vebt′ s* $\Longrightarrow$ *s* = *t*
⟨*proof*⟩

corollary *invar-vebt t n* $\Longrightarrow$ *set-vebt′ t* = {} $\Longrightarrow$ *t* = *vebt-buildup n*
⟨*proof*⟩

corollary *unique-tree*: *invar-vebt t n* $\Longrightarrow$ *invar-vebt s n* $\Longrightarrow$ *set-vebt t* = *set-vebt s* $\Longrightarrow$ *s* = *t*
⟨*proof*⟩

corollary *invar-vebt t n* $\Longrightarrow$ *set-vebt t* = {} $\Longrightarrow$ *t* = *vebt-buildup n*
⟨*proof*⟩

All valid trees can be generated by $vebt - insertion$ chains on an empty tree with same degree parameter:

inductive *perInsTrans*::*VEBT* ⇒ *VEBT* ⇒ *bool* **where**
perInsTrans t t|
(*t* = *vebt-insert s x*) ⟹ *perInsTrans t u* ⟹ *perInsTrans s u*

lemma *perIT-concat*: *perInsTrans s t* ⟹ *perInsTrans t u* ⟹ *perInsTrans s u*
⟨*proof*⟩

lemma assumes *invar-vebt t n* **shows**
perInsTrans (*vebt-buildup n*) *t*
⟨*proof*⟩

end
end

theory *VEBT-Height* **imports** *VEBT-Definitions Complex-Main*
begin

context *VEBT-internal* **begin**

10 Heights of van Emde Boas Trees

fun *height*::*VEBT* ⇒ *nat* **where**
height (*Leaf a b*) = *0*|
height (*Node - deg treeList summary*) = (*1*+ *Max* (*height* ‘ (*insert summary* (*set treeList*))))

abbreviation *lb x* ≡ *log 2 x*

lemma *setceilmax*: *invar-vebt s m* ⟹∀ *t* ∈ *set listy*. *invar-vebt t n*
⟹*m* = *Suc n* ⟹(∀ *t* ∈ *set listy*. *height t* = ⌈*lb n* ⌉) ⟹ *height s* = ⌈*lb m*⌉
⟹ *Max* (*height* ‘ (*insert s* (*set listy*))) = ⌈*lb m*⌉
⟨*proof*⟩

lemma *log-ceil-idem*:
assumes(*x*::*real*) ≥ *1*
shows ⌈*lb x* ⌉ = ⌈*lb* ⌈*x*⌉⌉
⟨*proof*⟩

lemma *heigt-uplog-rel*:*invar-vebt t n* ⟹ (*height t*) = ⌈*lb n*⌉
⟨*proof*⟩

lemma *two-powr-height-bound-deg*:
assumes *invar-vebt t n*
shows *2*^(*height t*) ≤ *2*∗(*n*::*nat*)
⟨*proof*⟩

Main Theorem

theorem *height-double-log-univ-size*:
assumes *u* = *2*^*deg* **and** *invar-vebt t deg*
shows *height t* ≤ *1* + *lb* (*lb u*)

⟨*proof*⟩

lemma *height-compose-list*: $t \in$ *set treeList* $\Longrightarrow$
Max (*height* ' (*insert summary* (*set treeList*))) $\geq$ *height t*
⟨*proof*⟩

lemma *height-compose-child*: $t \in$ *set treeList* $\Longrightarrow$
height (*Node info deg treeList summary*) $\geq 1+$ *height t* ⟨*proof*⟩

lemma *height-compose-summary*: *height* (*Node info deg treeList summary*) $\geq 1+$ *height summary*
⟨*proof*⟩

lemma *height-i-max*: $i <$ *length x13* $\Longrightarrow$
height (*x13* ! *i*) $\leq$ *max foo* (*Max* (*height* ' *set x13*))
⟨*proof*⟩

lemma *max-ins-scaled*: $n *$ *height x14* $\leq m + n *$ *Max* (*insert* (*height x14*) (*height* ' *set x13*))
⟨*proof*⟩

lemma *max-idx-list*:
assumes $i <$ *length x13*
shows $n *$ *height* (*x13* !*i*) $\leq$ *Suc* (*Suc* ($n *$ *max* (*height x14*) (*Max* (*height* ' *set x13*))))
⟨*proof*⟩

end
end

theory *VEBT-Bounds* **imports** *VEBT-Height VEBT-Member VEBT-Insert VEBT-Succ VEBT-Pred*
begin

11 Upper Bounds for canonical Functions: Relationships between Run Time and Tree Heights

11.1 Membership test

context begin

interpretation *VEBT-internal* ⟨*proof*⟩

fun T_{member}::*VEBT* $\Rightarrow$ *nat* $\Rightarrow$ *nat* **where**
T_{member} (*Leaf a b*) *x* = *2* + (*if x* = *0 then 1 else 1* +(*if x*=*1 then 1 else 1*))|
T_{member} (*Node None - - -*) *x* = *2*|
T_{member} (*Node - 0 - -*) *x* = *2*|
T_{member} (*Node - (Suc 0) - -*) *x* = *2*|
T_{member} (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*) *x* = *2* + (
if x = *mi then 1 else 1*+ (
if x = *ma then 1 else 1*+(
if x < *mi then 1 else 1*+ (
if x > *ma then 1 else 9* +

```
  (let
       h = high x (deg div 2);
      l = low x (deg div 2) in
    (if h < length treeList
       then 1 + T_member (treeList ! h) l
       else 1))))))


fun T_member'::VEBT ⇒ nat ⇒ nat where
  T_member' (Leaf a b) x = 1|
  T_member' (Node None - - -) x = 1|
  T_member' (Node - 0 - -) x = 1|
  T_member' (Node - (Suc 0) - -) x = 1|
  T_member' (Node (Some (mi, ma)) deg treeList summary) x = 1+(
 if x = mi then 0 else (
  if x = ma then 0  else (
  if x < mi then 0  else  (
 if x > ma then 0 else if (x>mi ∧ x < ma) then
  (let
       h = high x (deg div 2);
      l = low x (deg div 2) in
       (if h < length treeList
        then  T_member' (treeList ! h) l
        else 0))
else 0))))


lemma height-node: invar-vebt  (Node (Some (mi, ma)) deg treeList summary) n
                ⟹ height  (Node (Some (mi, ma)) deg treeList summary) >= 1
  ⟨proof⟩

theorem member-bound-height: invar-vebt t n ⟹ T_member t x ≤ (1+height t)*15
⟨proof⟩

theorem member-bound-height': invar-vebt t n ⟹ T_member' t x ≤ (1+height t)
⟨proof⟩

theorem member-bound-size-univ: invar-vebt t n ⟹ u =  2^n ⟹  T_member t x ≤ 30 + 15 * lb (lb
u)
  ⟨proof⟩
```

11.2 Minimum, Maximum, Emptiness Test

```
fun T_mint::VEBT ⇒ nat where
  T_mint (Leaf a b) = (1+ (if a then 0 else 1 + (if b then 1 else 1)))|
  T_mint (Node None - - -) = 1|
  T_mint (Node (Some (mi,ma)) - - - ) = 1
```

lemma *mint-bound*: $T_{mint}\ t \leq\ 3\ \langle proof \rangle$

fun T_{maxt}::*VEBT* ⇒ *nat* **where**
T_{maxt} (*Leaf a b*) = (*1*+ (*if b then 1 else 1* +(*if a then 1 else 1*)))|
T_{maxt} (*Node None - - -*) = *1*|
T_{maxt} (*Node* (*Some* (*mi*,*ma*)) *- - -*) = *1*

lemma *maxt-bound*: $T_{maxt}\ t \leq\ 3\ \langle proof \rangle$

fun $T_{minNull}$::*VEBT* ⇒ *nat* **where**
$T_{minNull}$ (*Leaf False False*) = *1*|
$T_{minNull}$ (*Leaf - -*) = *1*|
$T_{minNull}$ (*Node None - - -*) = *1*|
$T_{minNull}$ (*Node* (*Some -*) *- - -*) = *1*

lemma *minNull-bound*: $T_{minNull}\ t \leq 1$
⟨*proof*⟩

11.3 Insertion

fun T_{insert}::*VEBT* ⇒ *nat* ⇒*nat* **where**
T_{insert} (*Leaf a b*) *x* = *1*+ (*if x=0 then 1 else 1* + (*if x=1 then 1 else 1*))|
T_{insert} (*Node info 0 ts s*) *x* = *1*|
T_{insert} (*Node info* (*Suc 0*) *ts s*) *x* = *1*|
T_{insert} (*Node None* (*Suc deg*) *treeList summary*) *x* = *2*|
T_{insert} (*Node* (*Some* (*mi*,*ma*)) *deg treeList summary*) *x* = *19*+
(*let xn* = (*if x* < *mi then mi else x*); *minn* = (*if x*< *mi then x else mi*);
l= *low xn* (*deg div 2*); *h* = *high xn* (*deg div 2*)
in
(*if h* < *length treeList* ∧ ¬ (*x* = *mi* ∨ *x* = *ma*)*then*
T_{insert} (*treeList* ! *h*) *l* + $T_{minNull}$ (*treeList* ! *h*)+
(*if minNull* (*treeList* ! *h*) *then* T_{insert} *summary h else 1*)
else 1))

fun T_{insert}'::*VEBT* ⇒ *nat* ⇒*nat* **where**
T_{insert}' (*Leaf a b*) *x* = *1*|
T_{insert}' (*Node info 0 ts s*) *x* = *1*|
T_{insert}' (*Node info* (*Suc 0*) *ts s*) *x* = *1*|
T_{insert}' (*Node None* (*Suc deg*) *treeList summary*) *x* = *1*|
T_{insert}' (*Node* (*Some* (*mi*,*ma*)) *deg treeList summary*) *x* =
(*let xn* = (*if x* < *mi then mi else x*); *minn* = (*if x*< *mi then x else mi*);
l= *low xn* (*deg div 2*); *h* = *high xn* (*deg div 2*)
in (*if h* < *length treeList* ∧ ¬ (*x* = *mi* ∨ *x* = *ma*)*then*
T_{insert}' (*treeList* ! *h*) *l* +
(*if minNull* (*treeList* ! *h*) *then* T_{insert}' *summary h else 1*) *else 1*))

lemma *insersimp*:**assumes** *invar-vebt t n* **and** ∄ *x*. *both-member-options t x* **shows** $T_{insert}\ t\ y \leq$

3
⟨*proof*⟩

lemma *insertsimp*: *invar-vebt t n* ⟹ *minNull t* ⟹ T_{insert} *t l* ≤ *3*
⟨*proof*⟩

lemma *insersimp'*:**assumes** *invar-vebt t n* **and** ∄ *x*. *both-member-options t x* **shows** $T_{insert}{}'$ *t y* ≤ *1*
⟨*proof*⟩

lemma *insertsimp'*: *invar-vebt t n* ⟹ *minNull t* ⟹ $T_{insert}{}'$ *t l* ≤ *1*
⟨*proof*⟩

theorem *insert-bound-height*: *invar-vebt t n* ⟹ T_{insert} *t x* ≤ (*1*+*height t*)∗*23*
⟨*proof*⟩

theorem *insert-bound-size-univ*: *invar-vebt t n* ⟹ *u* = *2*^*n* ⟹ T_{insert} *t x* ≤ *46* + *23* ∗ *lb* (*lb u*)
⟨*proof*⟩

theorem *insert'-bound-height*: *invar-vebt t n* ⟹ $T_{insert}{}'$ *t x* ≤ (*1*+*height t*)
⟨*proof*⟩

11.4 Successor Function

fun T_{succ}::*VEBT* ⇒ *nat* ⇒ *nat* **where**
T_{succ} (*Leaf - b*) *0* = *1*+ (*if b then 1 else 1*)|
T_{succ} (*Leaf - -*) (*Suc n*) = *1*|
T_{succ} (*Node None - - -*) *- = 1*|
T_{succ} (*Node - 0 - -*) *- = 1*|
T_{succ} (*Node - (Suc 0) - -*) *- = 1*|
T_{succ} (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*) *x* = *1*+ (
if x < *mi then 1*
else (*let l* = *low x* (*deg div 2*); *h* = *high x* (*deg div 2*) *in 10* +
(*if h* < *length treeList then 1*+ T_{maxt} (*treeList* ! *h*) + (
let maxlow = *vebt-maxt* (*treeList* ! *h*) *in 3* +
(*if maxlow* ≠ *None* ∧ (*Some l* <$_o$ *maxlow*) *then*
4 + T_{succ} (*treeList* ! *h*) *l*
else let sc = *vebt-succ summary h in 1*+ T_{succ} *summary h* + *1* + (
if sc = *None then 1*
else (*4* + T_{mint} (*treeList* ! *the sc*)))))

else 1)))

fun $T_{succ}{}'$::*VEBT* ⇒ *nat* ⇒ *nat* **where**
$T_{succ}{}'$ (*Leaf - b*) *0* = *1*|
$T_{succ}{}'$ (*Leaf - -*) (*Suc n*) = *1*|
$T_{succ}{}'$ (*Node None - - -*) *- = 1*|
$T_{succ}{}'$ (*Node - 0 - -*) *- = 1*|

```
  T_succ' (Node - (Suc 0) - -) - = 1|
  T_succ' (Node (Some (mi, ma)) deg treeList summary) x =(
            if x < mi then 1
            else (let l = low x (deg div 2); h = high x (deg div 2) in
                (if h < length treeList then  (
                        let maxlow = vebt-maxt (treeList ! h) in
                        (if maxlow ≠ None ∧ (Some l <_o  maxlow) then
                                              1+ T_succ' (treeList ! h) l
                         else let sc = vebt-succ summary h in  T_succ' summary h + (
                         if sc = None then 1
                         else 1 )))
                 else 1)))
```

theorem *succ-bound-height*: *invar-vebt t n* $\Longrightarrow$ T_{succ} *t x* $\leq$ (*1+height t*)∗*27*
⟨*proof*⟩

theorem *succ-bound-size-univ*: *invar-vebt t n* $\Longrightarrow$ *u = 2^n* $\Longrightarrow$ T_{succ} *t x* $\leq$ *54 + 27 ∗ lb* (*lb u*)
⟨*proof*⟩

theorem *succ'-bound-height*: *invar-vebt t n* $\Longrightarrow$ T_{succ}' *t x* $\leq$ (*1+height t*)
⟨*proof*⟩

theorem *succ-bound-size-univ'*: *invar-vebt t n* $\Longrightarrow$ *u = 2^n* $\Longrightarrow$ T_{succ}' *t x* $\leq$ *2 + lb* (*lb u*)
⟨*proof*⟩

11.5 Predecessor Function

```
fun T_pred::VEBT ⇒ nat ⇒ nat  where
  T_pred (Leaf - -) 0 = 1|
  T_pred (Leaf a -) (Suc 0) = 1+ (if a then 1 else 1)|
  T_pred (Leaf a b) - = 1+ (if b then 1 else 1+ (if a then 1 else 1))|

T_pred (Node None - - -) - = 1|
T_pred (Node - 0 - -) - = 1|
T_pred (Node - (Suc 0) - -) - = 1|
T_pred (Node (Some (mi, ma)) deg treeList summary) x = 1+ (
                    if x > ma then 1
                    else (let l = low x (deg div 2); h = high x (deg div 2) in 10 + 1+
                    (if h < length treeList then

                        let minlow = vebt-mint (treeList ! h) in 2 + T_mint(treeList ! h) + 3 +
                        (if minlow ≠ None ∧ (Some l >_o  minlow) then
                                              4 +  T_pred (treeList ! h) l
                         else let pr = vebt-pred summary h in  1 + T_pred summary h+ 1 + (
                         if pr = None then 1 + (if x > mi then 1 else 1)
                         else 4 +  T_maxt (treeList ! the pr) ))
                 else 1)))
```

theorem *pred-bound-height*: *invar-vebt t n* $\Longrightarrow$ T_{pred} *t x* $\leq$ (*1+height t*)∗*29*

⟨*proof*⟩

theorem *pred-bound-size-univ*: *invar-vebt t n* ⟹ *u* = *2^n* ⟹ T_{pred} *t x* ≤ *58* + *29* ∗ *lb* (*lb u*)
⟨*proof*⟩

fun T_{pred}'::*VEBT* ⇒ *nat* ⇒ *nat* **where**
T_{pred}' (*Leaf* - -) *0* = *1*|
T_{pred}' (*Leaf a* -) (*Suc 0*) = *1*|
T_{pred}' (*Leaf a b*) - = *1*|

T_{pred}' (*Node None* - - -) - = *1*|
T_{pred}' (*Node* - *0* - -) - = *1*|
T_{pred}' (*Node* - (*Suc 0*) - -) - = *1*|
T_{pred}' (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*) *x* = (
if x > *ma then 1*
else (*let l* = *low x* (*deg div 2*); *h* = *high x* (*deg div 2*) *in*
(*if h* < *length treeList then*

let minlow = *vebt-mint* (*treeList* ! *h*) *in*
(*if minlow* ≠ *None* ∧ (*Some l* >$_o$ *minlow*) *then*
1+ T_{pred}' (*treeList* ! *h*) *l*
else let pr = *vebt-pred summary h in* T_{pred}' *summary h*+ (
if pr = *None then 1*
else 1))
else 1)))

theorem *pred-bound-height'*: *invar-vebt t n*⟹ T_{pred}' *t x* ≤ (*1* + *height t*)
⟨*proof*⟩

theorem *pred-bound-size-univ'*: *invar-vebt t n* ⟹ *u* = *2^n* ⟹ T_{pred}' *t x* ≤ *2* + *lb* (*lb u*)
⟨*proof*⟩

end
end

theory *VEBT-DeleteBounds* **imports** *VEBT-Bounds VEBT-Delete VEBT-DeleteCorrectness*
begin

11.6 Running Time Bounds for Deletion

context begin
interpretation *VEBT-internal* ⟨*proof*⟩

fun T_{delete}::*VEBT* ⇒ *nat* ⇒ *nat* **where**
T_{delete} (*Leaf a b*) *0* = *1*|
T_{delete} (*Leaf a b*) (*Suc 0*) = *1*|
T_{delete} (*Leaf a b*) (*Suc* (*Suc n*)) = *1*|
T_{delete} (*Node None deg treeList summary*) - = *1*|

T_{delete} (*Node* (*Some* (*mi*, *ma*)) *0 treeList summary*) *x* = *1*|
T_{delete} (*Node* (*Some* (*mi*, *ma*)) (*Suc 0*) *treeList summary*) *x* =*1* |
T_{delete} (*Node* (*Some* (*mi*, *ma*)) *deg treeList summary*) *x* = *3* + (
if (*x* < *mi* ∨ *x* > *ma*) *then 1*
else 3 + (*if* (*x* = *mi* ∧ *x* = *ma*) *then 3*
else 13 + (*if x* = *mi then* T_{mint} *summary* + T_{mint} (*treeList* ! *the* (*vebt-mint summary*))+
7 else 1)+
(*if x* = *mi then 1 else 1*) +
(*let xn* = (*if x* = *mi*
then the (*vebt-mint summary*) ∗ *2*^(*deg div 2*) + *the* (*vebt-mint* (*treeList* ! *the*
(*vebt-mint summary*)))
else x);
minn = (*if x* = *mi then xn else mi*);
l = *low xn* (*deg div 2*);
h = *high xn* (*deg div 2*) *in*
if h < *length treeList*
then(*4* + T_{delete} (*treeList* ! *h*) *l* +(
let newnode = *vebt-delete* (*treeList* ! *h*) *l*;
newlist = *treeList*[*h*:= *newnode*]*in 1* + $T_{minNull}$ *newnode* + (
if minNull newnode
then(*1* + T_{delete} *summary h* + (
let sn = *vebt-delete summary h in*
2+ (*if xn* = *ma then 1* + T_{maxt} *sn* + (*let maxs* = *vebt-maxt sn in*
1 + (*if maxs* = *None*
then 1
else 8+ T_{maxt} (*newlist* ! *the maxs*)
))
else 1)
))*else*
2 + (*if xn* = *ma then 6*+ T_{maxt} (*newlist* ! *h*) *else 1*)
)))*else 1*)))

end

context *VEBT-internal* **begin**

lemma *tdeletemimi*:
assumes *deg* ≥ *2*
shows T_{delete} (*Node* (*Some* (*mi*, *mi*)) *deg treeList summary*) *x* ≤ *9*
⟨*proof*⟩

lemma *minNull-delete-time-bound*: *invar-vebt t n* ⟹ *minNull* (*vebt-delete t x*) ⟹ T_{delete} *t x* ≤ *9*
⟨*proof*⟩

lemma *delete-bound-height*: *invar-vebt t n* ⟹ T_{delete} *t x* ≤ (*1*+ *height t*)∗*70*
⟨*proof*⟩

theorem *delete-bound-size-univ*: *invar-vebt t n* ⟹ *u* = *2*^*n* ⟹ T_{delete} *t x* ≤ *140* + *70* ∗ *lb* (*lb*

```
u)
  ⟨proof⟩

fun T_delete'::VEBT ⇒ nat ⇒ nat where
  T_delete' (Leaf a b) 0 = 1|
  T_delete' (Leaf a b) (Suc 0) = 1|
  T_delete' (Leaf a b) (Suc (Suc n)) = 1|
  T_delete' (Node None deg treeList summary) - = 1|
  T_delete' (Node (Some (mi, ma)) 0 treeList summary) x = 1|
  T_delete' (Node (Some (mi, ma)) (Suc 0) treeList summary) x =1 |
  T_delete' (Node (Some (mi, ma)) deg treeList summary) x =  (
            if (x < mi ∨ x > ma) then 1
            else if (x = mi ∧ x = ma) then 1
            else  (  let xn = (if x = mi
                        then the (vebt-mint summary) * 2^(deg div 2) + the (vebt-mint (treeList ! the
(vebt-mint summary)))
                        else x);
                  minn = (if x = mi then xn else mi);
                  l = low xn (deg div 2);
                  h = high xn (deg div 2) in
                   if h < length treeList
                     then(   T_delete' (treeList ! h) l  +(
                       let newnode = vebt-delete (treeList ! h) l;
                           newlist = treeList[h:= newnode]in
                       if minNull newnode
                       then  T_delete' summary h
                       else 1
                     ))else  1  ))


lemma tdeletemimi':deg ≥ 2 ⟹ T_delete' (Node (Some (mi, mi)) deg treeList summary) x ≤ 1
  ⟨proof⟩

lemma minNull-delete-time-bound': invar-vebt t n ⟹ minNull (vebt-delete t x) ⟹  T_delete' t x ≤
1
⟨proof⟩


lemma delete-bound-height': invar-vebt t n ⟹  T_delete' t x ≤ 1+ height t
⟨proof⟩

theorem delete-bound-size-univ': invar-vebt t n ⟹ u =  2^n ⟹   T_delete'  t x ≤ 2 +  lb (lb u)
  ⟨proof⟩

end
end

theory VEBT-Space imports VEBT-Definitions Complex-Main
begin
```

12 Space Complexity and *buildup* Time Consumption

12.1 Space Comlexity of valid van Emde Boas Trees

Space Complexity is linear in relation to universe sizes

context *VEBT-internal* **begin**

fun *space*:: *VEBT* ⇒ *nat* **where**
space (*Leaf a b*) = *3*|
space (*Node info deg treeList summary*) = *5* + *space summary* + *length treeList* + *foldr* (λ *a b*. *a*+*b*) (*map space treeList*) *0*

fun *space'*:: *VEBT* ⇒ *nat* **where**
space' (*Leaf a b*) = *4*|
space' (*Node info deg treeList summary*) = *6* + *space' summary* + *foldr* (λ *a b*. *a*+*b*) (*map space' treeList*) *0*

Count in reals

fun *cnt*:: *VEBT* ⇒ *real* **where**
cnt (*Leaf a b*) = *1*|
cnt (*Node info deg treeList summary*) = *1* + *cnt summary* + *foldr* (λ *a b*. *a*+*b*) (*map cnt treeList*) *0*

12.2 Auxiliary Lemmas for List Summation

lemma *list-every-elemnt-bound-sum-bound*:∀ *x* ∈ *set xs*. *f x* ≤ *bound* ⟹ *foldr* (λ *a b*. *a*+*b*) (*map f xs*) *i* ≤ *length xs* ∗ *bound* + *i*
⟨*proof*⟩

lemma *list-every-elemnt-bound-sum-bound-real*:∀ *x* ∈ *set* (*xs*::'*a list*). (*f*::'*a*⇒*real*) *x* ≤ (*bound*::*real*) ⟹ *foldr* (λ *a b*. *a*+*b*) (*map f xs*) *i* ≤ *real*(*length xs*) ∗ *bound* + *i*
⟨*proof*⟩

lemma *foldr-one*: *d* ≤ *foldr* (+) *ys* (*d*::*nat*)
⟨*proof*⟩

lemma *foldr-zero*: ∀ *i* < *length xs*. *xs* ! *i* > *0* ⟹
foldr (λ *a b*. *a*+*b*) *xs* (*d*::*nat*) − *d* ≥ *length xs*
⟨*proof*⟩

lemma *foldr-mono*: *length xs* = *length ys* ⟹∀ *i* < *length xs*. *xs* ! *i* < *ys* ! *i* ⟹ *c* ≤ *d* ⟹
foldr (λ *a b*. *a*+*b*) *xs c* + *length ys* ≤ *foldr* (λ *a b*. *a*+*b*) *ys* (*d*::*nat*)
⟨*proof*⟩

lemma *two-realpow-ge-two* :(*n*::*real*)≥ *1* ⟹ (*2*::*real*)^*n* ≥ *2*
⟨*proof*⟩

lemma *foldr0*: *foldr* (+) *xs* (*c*+*d*) = *foldr* (+) *xs* (*d*::*real*) + *c*
⟨*proof*⟩

lemma *f-g-map-foldr-bound*: $(\forall\ x \in set\ xs.\ f\ x \leq c * g\ x)$
$\Longrightarrow$ *foldr* $(\lambda\ a\ b.\ a+b)$ *(map f xs) d* $\leq c *$ *foldr* $(\lambda\ a\ b.\ a+b)$ *(map g xs) (0::real) + d*
⟨*proof*⟩

lemma *real-nat-list*: *real* (*foldr* (+) (*map f xs*) (*c*::*nat*))
= *foldr* (+) (*map* (λ *x*. *real*(*f x*))*xs*) *c*
⟨*proof*⟩

12.3 Actual Space Reasoning

lemma *space-space'*: *space' t* > *space t*
⟨*proof*⟩

lemma *cnt-bound*:
defines *c* ≡ *1.5*
shows *invar-vebt t n* $\Longrightarrow$ *cnt t* ≤ *2*∗((*2*^*n* − *c*)::*real*)
⟨*proof*⟩

theorem *cnt-bound'*: *invar-vebt t n* $\Longrightarrow$ *cnt t* ≤ *2* ∗ (*2* ^ *n* − *1*)
⟨*proof*⟩

lemma *space-cnt*: *space' t* ≤ *6*∗*cnt t*
⟨*proof*⟩

lemma *space-2-pow-bound*: **assumes** *invar-vebt t n* **shows** *real* (*space' t*) ≤ *12* ∗ (*2*^*n* −*1*)
⟨*proof*⟩

lemma *space'-bound*:
assumes *invar-vebt t n u* = *2*^*n*
shows *space' t* ≤ *12* ∗ *u*
⟨*proof*⟩

Main Theorem

theorem *space-bound*:
assumes *invar-vebt t n u* = *2*^*n*
shows *space t* ≤ *12* ∗ *u*
⟨*proof*⟩

12.4 Complexity of Generation Time

Space complexity is closely related to tree generation time complexity

Time approximation for replicate function. $T_{replicate}\ n\ t\ x$ denotes runnig time of the n-times replication of x into a list. t models runtime for generation of a single x.

fun $T_{buildup}$::*nat* ⇒ *nat* **where**
$T_{buildup}\ 0 = 3|$
$T_{buildup}\ (Suc\ 0) = 3|$
$T_{buildup}\ \ n = (if\ even\ n\ then\ 1 + (let\ half = n\ div\ 2\ in$
$9 + T_{buildup}\ half + \ (2\hat{}half) * (T_{buildup}\ half\ + 1))$

else (*let half* = *n div 2 in*
11 + $T_{buildup}$ (*Suc half*) + (*2*^(*Suc half*))∗ ($T_{buildup}$ *half* + *1*)))

fun T_{build}::*nat* ⇒ *nat* **where**
T_{build} *0* = *4*|
T_{build} (*Suc 0*) = *4*|
T_{build} *n* = (*if even n then 1* + (*let half* = *n div 2 in*
10 + T_{build} *half* + (*2*^*half*) ∗ (T_{build} *half*))
else (*let half* = *n div 2 in*
12 + T_{build} (*Suc half*) + (*2*^(*Suc half*))∗ (T_{build} *half*)))

lemma *buildup-build-time*: $T_{buildup}$ *n* < T_{build} *n*
⟨*proof*⟩

lemma *listsum-bound*: (⋀ *x*. *x* ∈ *set xs* ⟹ *f x* ≥ (*0*::*real*)) ⟹
foldr (+) (*map f xs*) *y* ≥ *y*
⟨*proof*⟩

lemma *cnt-non-neg*: *cnt t* ≥ *0*
⟨*proof*⟩

lemma *foldr-same*: (⋀ *x y*. *x* ∈ *set* (*xs*::*real list*) ⟹ *y* ∈ *set xs* ⟹ *x* = *y*) ⟹
(⋀ *x* . (*x*::*real*) ∈ *set xs* ⟹ *x* = (*y*::*real*)) ⟹
foldr (λ (*a*::*real*) (*b*::*real*). *a*+*b*) *xs 0* = *real* (*length xs*) ∗ *y*
⟨*proof*⟩

lemma *foldr-same-int*: (⋀ *x y*. *x* ∈ *set xs* ⟹ *y* ∈ *set xs* ⟹ *x* = *y*) ⟹
(⋀ *x* . *x* ∈ *set xs* ⟹ *x* = *y*) ⟹
foldr (+) *xs 0* = (*length xs*) ∗ *y*
⟨*proof*⟩

lemma *t-build-cnt*: T_{build} *n* ≤ *cnt* (*vebt-buildup n*) ∗ *13*
⟨*proof*⟩

lemma *t-buildup-cnt*: $T_{buildup}$ *n* ≤ *cnt* (*vebt-buildup n*) ∗ *13*
⟨*proof*⟩

lemma *count-buildup*: *cnt* (*vebt-buildup n*) ≤ *2* ∗ *2*^*n*
⟨*proof*⟩

lemma *count-buildup′*: *cnt* (*vebt-buildup n*) ≤ *2* ∗ (*2*::*nat*)^*n*
⟨*proof*⟩

theorem *vebt-buildup-bound*: *u* = *2*^*n* ⟹ $T_{buildup}$ *n* ≤ *26* ∗ *u*
⟨*proof*⟩

Count in natural numbers

fun *cnt′*:: *VEBT* ⇒ *nat* **where**

cnt′ (Leaf a b) = 1|
cnt′ (Node info deg treeList summary) = 1 + cnt′ summary + foldr (λ a b. a+b) (map cnt′ treeList) 0

lemma *cnt-cnt-eq:cnt t = cnt′ t*
⟨*proof*⟩

end
end

13 Functional Interface

theory *VEBT-Intf-Functional*
imports *Main*
VEBT-Definitions VEBT-Space
VEBT-Uniqueness
VEBT-Member
VEBT-Insert VEBT-InsertCorrectness
VEBT-MinMax
VEBT-Pred VEBT-Succ
VEBT-Bounds
VEBT-Delete VEBT-DeleteCorrectness VEBT-DeleteBounds

begin

13.1 Code Generation Setup

13.1.1 Code Equations

Code generator seems to not support patterns and nat code target

context begin
interpretation *VEBT-internal* ⟨*proof*⟩

lemma *vebt-member-code* [*code*]:
vebt-member (Leaf a b) x = (if x = 0 then a else if x=1 then b else False)
vebt-member (Node None t r e) x = False
vebt-member (Node (Some (mi, ma)) deg treeList summary) x =
(if deg = 0 ∨ deg = Suc 0 then False else (
if x = mi then True else
if x = ma then True else
if x < mi then False else
if x > ma then False else
(let
h = high x (deg div 2);
l = low x (deg div 2) in
(if h < length treeList
then vebt-member (treeList ! h) l
else False))))
⟨*proof*⟩

lemma *vebt-insert-code* [*code*]:
vebt-insert (*Leaf a b*) *x* = (*if x=0 then Leaf True b else if x=1 then Leaf a True else Leaf a b*)
vebt-insert (*Node info deg treeList summary*) *x* = (
if deg ≤ *1 then*
(*Node info deg treeList summary*)
else (*case info of*
None ⇒ (*Node* (*Some* (*x*,*x*)) *deg treeList summary*)
| *Some mima* ⇒ (*case mima of* (*mi*, *ma*) ⇒ (
let
xn = (*if x* < *mi then mi else x*);
minn = (*if x*< *mi then x else mi*);
l= *low xn* (*deg div 2*); *h* = *high xn* (*deg div 2*)
in (
if h < *length treeList* ∧ ¬ (*x* = *mi* ∨ *x* = *ma*) *then*
Node (*Some* (*minn*, *max xn ma*))
deg
(*treeList*[*h*:= *vebt-insert* (*treeList* ! *h*) *l*])
(*if minNull* (*treeList* ! *h*) *then vebt-insert summary h else summary*)
else Node (*Some* (*mi*, *ma*)) *deg treeList summary*)
))))
⟨*proof*⟩

lemma *vebt-succ-code* [*code*]:
vebt-succ (*Leaf a b*) *x* = (*if b*∧ *x* = *0 then Some 1 else None*)
vebt-succ (*Node info deg treeList summary*) *x* = (*if deg* ≤ *1 then None else*
(*case info of None* ⇒ *None* |
(*Some mima*) ⇒ (*case mima of* (*mi*, *ma*) ⇒ (
if x < *mi then* (*Some mi*)
else (*let l* = *low x* (*deg div 2*); *h* = *high x* (*deg div 2*) *in*(
if h < *length treeList then*
let maxlow = *vebt-maxt* (*treeList* ! *h*) *in*
(*if maxlow* ≠ *None* ∧ (*Some l* <*o maxlow*) *then*
Some (2^(*deg div 2*)) ∗*o Some h* +*o vebt-succ* (*treeList* ! *h*) *l*
else let sc = *vebt-succ summary h in*
if sc = *None then None*
else Some (2^(*deg div 2*)) ∗*o sc* +*o vebt-mint* (*treeList* ! *the sc*))

else None))))))
⟨*proof*⟩

lemma *vebt-pred-code*[*code*]:
vebt-pred (*Leaf a b*) *x* = (*if x* = *0 then None else if x* = *1 then*
(*if a then Some 0 else None*) *else*
(*if b then Some 1 else if a then Some 0 else None*)) **and**
vebt-pred (*Node info deg treeList summary*) *x* =(*if deg* ≤ *1 then None else* (
case info of None ⇒ *None* |
(*Some mima*) ⇒ (*case mima of* (*mi*, *ma*) ⇒ (
if x > *ma then Some ma*

```
                    else (let l = low x (deg div 2); h = high x (deg div 2) in
                    if h < length treeList then
                        let minlow = vebt-mint (treeList ! h) in
                        (if minlow ≠ None ∧ (Some l >o  minlow) then
                                        Some (2^(deg div 2)) *o Some h +o vebt-pred (treeList ! h) l
                         else let pr = vebt-pred summary h in
                         if pr = None then (if x > mi then Some mi else None)
                         else Some (2^(deg div 2)) *o pr +o vebt-maxt (treeList ! the pr) )
                    else None)))))
⟨proof⟩


lemma vebt-delete-code [code]:
  vebt-delete (Leaf a b) x = (if x = 0 then Leaf False b else if x = 1 then Leaf a False else Leaf a b)
  vebt-delete (Node info deg treeList summary) x = (
    case info of
      None ⇒ (Node info deg treeList summary)
    | Some mima ⇒ (
        if deg ≤ 1 then (Node info deg treeList summary)
        else (case mima of (mi, ma) ⇒ (
          if (x < mi ∨ x > ma) then (Node (Some (mi, ma)) deg treeList summary)
          else if (x = mi ∧ x = ma) then (Node None deg treeList summary)
          else let
            xn = (if x = mi then the (vebt-mint summary) * 2^(deg div 2)
                                + the (vebt-mint (treeList ! the (vebt-mint summary)))
                  else x);
            minn = (if x = mi then xn else mi);
            l = low xn (deg div 2);
            h = high xn (deg div 2)
          in
            if h < length treeList then let
              newnode = vebt-delete (treeList ! h) l;
              newlist = treeList[h:= newnode]
            in
              if minNull newnode then let
                sn = vebt-delete summary h;
                maxn =
                  if xn = ma then let
                    maxs = vebt-maxt sn
                    in
                      if maxs = None then minn
                      else 2^(deg div 2) * the maxs + the (vebt-maxt (newlist ! the maxs))
                  else ma
                in (Node (Some (minn, maxn)) deg newlist sn)
              else let
                maxn = (if xn = ma then h * 2^(deg div 2) + the( vebt-maxt (newlist ! h))
                                   else ma)
              in (Node (Some (minn, maxn)) deg newlist summary)
            else (Node (Some (mi, ma)) deg treeList summary)
```

))))
⟨*proof*⟩
end

lemmas [*code*] =
VEBT-internal.high-def VEBT-internal.low-def VEBT-internal.minNull.simps
VEBT-internal.less.simps VEBT-internal.mul-def VEBT-internal.add-def
VEBT-internal.option-comp-shift.simps VEBT-internal.option-shift.simps

export-code
vebt-buildup
vebt-insert
vebt-member
vebt-maxt
vebt-mint
vebt-pred
vebt-succ
vebt-delete
checking *SML*

13.2 Correctness Lemmas

named-theorems *vebt-simps* ‹*Simplifier rules for VEBT functional interface*›

locale *vebt-inst* =
fixes *n* :: *nat*
begin

interpretation *VEBT-internal* ⟨*proof*⟩

13.2.1 Space Bound

theorem *vebt-space-linear-bound*:
fixes *t*
defines $u \equiv 2\hat{}n$
shows *invar-vebt t n* ⟹ *space t* ≤ *12∗u*
⟨*proof*⟩

13.2.2 Buildup

lemma *invar-vebt-buildup*[*vebt-simps*]: *invar-vebt* (*vebt-buildup n*) *n* ⟷ *n>0*
⟨*proof*⟩

lemma *set-vebt-buildup*[*vebt-simps*]: *set-vebt* (*vebt-buildup i*) = {}
⟨*proof*⟩

lemma *time-vebt-buildup*: $u = 2\hat{}n \implies T_{buildup}\ \ n \leq 26 * u$
⟨*proof*⟩

13.2.3 Equality

lemma *set-vebt-equal*[*vebt-simps*]: *invar-vebt* t_1 $n \Longrightarrow$ *invar-vebt* t_2 $n \Longrightarrow t_1{=}t_2 \longleftrightarrow$ *set-vebt* t_1 = *set-vebt* t_2
⟨*proof*⟩

13.2.4 Member

lemma *set-vebt-member*[*vebt-simps*]: *invar-vebt t n* ⟹ *vebt-member t x* ⟷ *x*∈*set-vebt t*
⟨*proof*⟩

theorem *time-vebt-member*: *invar-vebt t n* ⟹ *u* = 2^*n* ⟹ T_{member} *t x* ≤ *30* + *15* ∗ *lb* (*lb u*)
⟨*proof*⟩

13.2.5 Insert

theorem *invar-vebt-insert*[*vebt-simps*]: *invar-vebt t n* ⟹ *x*< 2^*n* ⟹ *invar-vebt* (*vebt-insert t x*) *n*
⟨*proof*⟩

theorem *set-vebt-insert*[*vebt-simps*]: *invar-vebt t n* ⟹ *x* < 2^*n* ⟹ *set-vebt* (*vebt-insert t x*) = *set-vebt t* ∪ {*x*}
⟨*proof*⟩

theorem *time-vebt-insert*: *invar-vebt t n* ⟹ *u* = 2^*n* ⟹ T_{insert} *t x* ≤ *46* + *23* ∗ *lb* (*lb u*)
⟨*proof*⟩

13.2.6 Maximum

theorem *set-vebt-maxt*: *invar-vebt t n* ⟹ *vebt-maxt t* = *Some x* ⟷ *max-in-set* (*set-vebt t*) *x*
⟨*proof*⟩

theorem *set-vebt-maxt′*: *invar-vebt t n* ⟹ *vebt-maxt t* = *Some x* ⟷ (*x*∈*set-vebt t* ∧ (∀ *y*∈*set-vebt t*. *x*≥*y*))
⟨*proof*⟩

lemma *set-vebt-maxt″*[*vebt-simps*]:
invar-vebt t n ⟹ *vebt-maxt t* = (*if set-vebt t* = {} *then None else Some* (*Max* (*set-vebt t*)))
⟨*proof*⟩

lemma *time-vebt-maxt*: T_{maxt} *t* ≤ *3*
⟨*proof*⟩

13.2.7 Minimum

theorem *set-vebt-mint*[*vebt-simps*]: *invar-vebt t n* ⟹ *vebt-mint t* = *Some x* ⟷ *min-in-set* (*set-vebt t*) *x*
⟨*proof*⟩

theorem *set-vebt-mint′*: *invar-vebt t n* ⟹ *vebt-mint t* = *Some x* ⟷ (*x*∈*set-vebt t* ∧ (∀ *y*∈*set-vebt t*. *x*≤*y*))

⟨*proof*⟩

lemma *set-vebt-mint''*[*vebt-simps*]:
invar-vebt t n ⟹ *vebt-mint t* = (*if set-vebt t* = {} *then None else Some* (*Min* (*set-vebt t*)))
⟨*proof*⟩

lemma *time-vebt-mint*: $T_{mint}\ t \leq 3$
⟨*proof*⟩

13.3 Emptiness determination

A tree is empty if and only if its minimum is None

lemma *vebt-minNull-mint*: *minNull t* ⟷ *vebt-mint t* = *None*
⟨*proof*⟩

lemma *set-vebt-minNull*: *invar-vebt t n* ⟹ *minNull t* ⟷ *set-vebt t* = {}
⟨*proof*⟩

lemma *time-vebt-minNull*: $T_{minNull}\ t \leq 1$
⟨*proof*⟩

13.3.1 Successor

theorem *set-vebt-succ*: *invar-vebt t n* ⟹ *vebt-succ t x* = *Some sx* ⟷ *is-succ-in-set* (*set-vebt t*) *x sx*
⟨*proof*⟩

lemma *set-vebt-succ'*[*vebt-simps*]: *invar-vebt t n* ⟹ *vebt-succ t x* = (*if* ∃ *y* ∈ *set-vebt t*. *y* > *x then Some* (*LEAST y* ∈ *set-vebt t*. *y* > *x*) *else None*)
⟨*proof*⟩

theorem *time-vebt-succ*:
fixes *t* **defines** *u* ≡ 2^*n*
shows *invar-vebt t n* ⟹ $T_{succ}\ t\ x \leq 54 + 27 * lb\ (lb\ u)$
⟨*proof*⟩

13.3.2 Predecessor

theorem *set-vebt-pred*: *invar-vebt t n* ⟹ *vebt-pred t x* = *Some px* ⟷ *is-pred-in-set* (*set-vebt t*) *x px*
⟨*proof*⟩

theorem *set-vebt-pred'*[*vebt-simps*]: *invar-vebt t n* ⟹
vebt-pred t x = (*if* ∃ *y* ∈ *set-vebt t*. *y* < *x then Some* (*GREATEST y*. *y* ∈ *set-vebt t* ∧ *y* < *x*) *else None*)
⟨*proof*⟩

theorem *time-vebt-pred*: **fixes** *t* **defines** *u* ≡ 2^*n*
shows *invar-vebt t n* ⟹ $T_{pred}\ t\ x \leq 58 + 29 * lb\ (lb\ u)$

⟨*proof*⟩

13.3.3 Delete

theorem *invar-vebt-delete*[*vebt-simps*]: *invar-vebt t n* ⟹ *invar-vebt* (*vebt-delete t x*) *n*
⟨*proof*⟩

theorem *set-vebt-delete*[*vebt-simps*]: *invar-vebt t n* ⟹ *set-vebt* (*vebt-delete t x*) = *set-vebt t* − {*x*}
⟨*proof*⟩

theorem *time-vebt-delete*: **fixes** *t* **defines** *u* ≡ *2^n*
shows *invar-vebt t n* ⟹ T_{delete} *t x* ≤ *140* + *70* ∗ *lb* (*lb u*)
⟨*proof*⟩

end

13.4 Interface Usage Example

experiment
begin

definition *test n xs ys* ≡ *let*
t = *vebt-buildup n*;
t = *foldl vebt-insert t* (*0*#*xs*);

f = (λ*x*. *if vebt-member t x then x else the* (*vebt-pred t x*))
in
map f ys

context fixes *n* :: *nat* **begin**
interpretation *vebt-inst n* ⟨*proof*⟩

lemmas [*simp*] = *vebt-simps*

lemma [*simp*]:
assumes *invar-vebt t n* ∀ *x*∈*set xs*. *x*<*2^n*
shows *invar-vebt* (*foldl vebt-insert t xs*) *n*
⟨*proof*⟩

lemma [*simp*]:
assumes *invar-vebt t n* ∀ *x*∈*set xs*. *x*<*2^n*
shows *set-vebt* (*foldl vebt-insert t xs*) = *set-vebt t* ∪ *set xs*
⟨*proof*⟩

lemma ⟦∀ *x*∈*set xs*. *x*<*2^n*; *n*>*0*⟧ ⟹ *test n xs ys* = *map* (λ*y*. (*GREATEST y′*. *y′*∈*insert 0* (*set xs*) ∧ *y′*≤*y*)) *ys*
⟨*proof*⟩

end

end

end

theory *VEBT-List-Assn*
imports
Separation-Logic-Imperative-HOL/Sep-Main
HOL−Library.Rewrite

begin

13.5 Lists

fun *list-assn* :: $('a \Rightarrow 'c \Rightarrow assn) \Rightarrow 'a\ list \Rightarrow 'c\ list \Rightarrow assn$ **where**
list-assn P [] [] = *emp*
| *list-assn P* (*a*#*as*) (*c*#*cs*) = *P a c* ∗ *list-assn P as cs*
| *list-assn* - - - = *false*

lemma *list-assn-aux-simps*[*simp*]:
list-assn P [] *l'* = (↑(*l'*=[]))
list-assn P l [] = (↑(*l*=[]))
⟨*proof*⟩

lemma *list-assn-aux-append*[*simp*]:
length l1=*length l1'* ⟹
list-assn P (*l1*@*l2*) (*l1'*@*l2'*)
= *list-assn P l1 l1'* ∗ *list-assn P l2 l2'*
⟨*proof*⟩

lemma *list-assn-aux-ineq-len*: *length l* ≠ *length li* ⟹ *list-assn A l li* = *false*
⟨*proof*⟩

lemma *list-assn-aux-append2*[*simp*]:
assumes *length l2*=*length l2'*
shows *list-assn P* (*l1*@*l2*) (*l1'*@*l2'*)
= *list-assn P l1 l1'* ∗ *list-assn P l2 l2'*
⟨*proof*⟩

lemma *list-assn-simps*[*simp*]:
(*list-assn P*) [] [] = *emp*
(*list-assn P*) (*a*#*as*) (*c*#*cs*) = *P a c* ∗ (*list-assn P*) *as cs*
(*list-assn P*) (*a*#*as*) [] = *false*
(*list-assn P*) [] (*c*#*cs*) = *false*
⟨*proof*⟩

lemma *list-assn-mono*:
⟦⋀x x'. P x x' ⟹$_A$ P' x x'⟧ ⟹ list-assn P l l' ⟹$_A$ list-assn P' l l'
⟨*proof*⟩

lemma *list-assn-cong*[*fundef-cong*]:
assumes xs=xs' xsi=xsi'
assumes ⋀x xi. x∈set xs' ⟹ xi∈set xsi' ⟹ A x xi = A' x xi
shows list-assn A xs xsi = list-assn A' xs' xsi'
⟨*proof*⟩

term *prod-list*

definition *listI-assn I A xs xsi* ≡
↑(length xsi=length xs ∧ I⊆{0..<length xs})
∗ Finite-Set.fold (λi a. a ∗ A (xs!i) (xsi!i)) 1 I

lemmas *comp-fun-commute-fold-insert* =
comp-fun-commute-on.fold-insert[**where** S=UNIV, folded comp-fun-commute-def', simplified]

lemma *aux*: Finite-Set.fold (λi aa. aa ∗ P ((a # as) ! i) ((c # cs) ! i)) emp {0..<Suc (length as)}
= P a c ∗ Finite-Set.fold (λi aa. aa ∗ P (as ! i) (cs ! i)) emp {0..<length as}
⟨*proof*⟩

lemma *list-assn-conv-idx*: list-assn A xs xsi = listI-assn {0..<length xs} A xs xsi
⟨*proof*⟩

lemma *listI-assn-conv*: n=length xs ⟹ listI-assn {0..<n} A xs xsi = list-assn A xs xsi
⟨*proof*⟩

lemma *listI-assn-conv'*: n=length xs ⟹ listI-assn {0..<n} A xs xsi ∗F = list-assn A xs xsi∗ F
⟨*proof*⟩

lemma *listI-assn-finite*[*simp*]: ¬finite I ⟹ listI-assn I A xs xsi = false
⟨*proof*⟩

find-theorems Finite-Set.fold *name*: *cong*

lemma *mult-fun-commute*: comp-fun-commute (λi (a::assn). a ∗ f i)
⟨*proof*⟩

lemma *listI-assn-weak-cong*:
assumes I: I=I' A=A' length xs=length xs' length xsi=length xsi'
assumes A: ⋀i. ⟦i∈I; i<length xs; length xs=length xsi ⟧

$\Longrightarrow xs!i = xs'!i \wedge xsi!i = xsi'!i$
shows *listI-assn I A xs xsi = listI-assn I' A' xs' xsi'*
⟨*proof*⟩

lemma *listI-assn-cong*:
assumes *I*: *I=I' length xs=length xs' length xsi=length xsi'*
assumes *A*: $\bigwedge i.\ [\![i{\in}I;\ i{<}length\ xs;\ length\ xs{=}length\ xsi\ ]\!]$
$\Longrightarrow xs!i = xs'!i \wedge xsi!i = xsi'!i$
$\wedge\ A\ (xs!i)\ (xsi!i) = A'\ (xs'!i)\ (xsi'!i)$
shows *listI-assn I A xs xsi = listI-assn I' A' xs' xsi'*
⟨*proof*⟩

lemma *listI-assn-insert*: $i{\notin}I \Longrightarrow i{<}length\ xs \Longrightarrow$
listI-assn (insert i I) A xs xsi = A (xs!i) (xsi!i) ∗ listI-assn I A xs xsi
⟨*proof*⟩

lemma *listI-assn-extract*:
assumes *i∈I i<length xs*
shows *listI-assn I A xs xsi = A (xs!i) (xsi!i) ∗ listI-assn (I−{i}) A xs xsi*
⟨*proof*⟩

lemma *listI-assn-reinsert*:
assumes $P \Longrightarrow_A A\ (xs!i)\ (xsi!i) * listI\text{-}assn\ (I{-}\{i\})\ A\ xs\ xsi * F$
assumes *i<length xs i∈I*
assumes *listI-assn I A xs xsi ∗ F* $\Longrightarrow_A Q$
shows $P \Longrightarrow_A Q$
⟨*proof*⟩

lemma *listI-assn-reinsert-upd*:
fixes *xs xsi* :: *- list*
assumes $P \Longrightarrow_A A\ x\ xi * listI\text{-}assn\ (I{-}\{i\})\ A\ xs\ xsi * F$
assumes *i<length xs i∈I*
assumes *listI-assn I A (xs[i:=x]) (xsi[i:=xi]) ∗ F* $\Longrightarrow_A Q$
shows $P \Longrightarrow_A Q$
⟨*proof*⟩

lemma *listI-assn-reinsert'*:
assumes $P \Longrightarrow_A A\ (xs!i)\ (xsi!i) * listI\text{-}assn\ (I{-}\{i\})\ A\ xs\ xsi * F$
assumes *i<length xs i∈I*
assumes *<listI-assn I A xs xsi ∗ F>c<Q>*
shows *<P>c<Q>*
⟨*proof*⟩

lemma *listI-assn-reinsert-upd'*:
fixes *xs xsi* :: *- list*

assumes $P \Longrightarrow_A A\ x\ xi * listI\text{-}assn\ (I-\{i\})\ A\ xs\ xsi * F$
assumes $i<length\ xs\ i\in I$
assumes $<listI\text{-}assn\ I\ A\ (xs[i:=x])\ (xsi[i:=xi]) * F>\ c\ <Q>$
shows $<P>\ c\ <Q>$
⟨*proof*⟩

lemma *subst-not-in*:
assumes $i\notin I \quad i<length\ xs$
shows $listI\text{-}assn\ I\ A\ (xs[i:=x1])\ (xsi[i := x2]) = listI\text{-}assn\ I\ A\ xs\ xsi$
⟨*proof*⟩

lemma *listI-assn-subst*:
assumes $i\notin I \quad i<length\ xs$
shows $listI\text{-}assn\ (insert\ i\ I)\ A\ (xs[i:=x1])\ (xsi[i := x2]) = A\ x1\ x2 * listI\text{-}assn\ I\ A\ xs\ xsi$
⟨*proof*⟩

lemma *extract-pre-list-assn-lengthD*: $h \models list\text{-}assn\ A\ xs\ xsi \Longrightarrow length\ xsi = length\ xs$
⟨*proof*⟩

method *unwrap-idx* **for** i ::*nat* =
(*rewrite* **in** <¤>-<-> *list-assn-conv-idx*),
(*rewrite* **in** <¤>-<-> *listI-assn-extract*[**where** i=i]),
(*simp split*: *if-splits*; *fail*),
(*simp split*: *if-splits*; *fail*)

method *wrap-idx* **uses** R =
(*rule* R),
frame-inference,
(*simp split*: *if-splits*; *fail*),
(*simp split*: *if-splits*; *fail*),
(*subst listI-assn-conv*, (*simp*; *fail*))

method *extract-pre-pure* **uses** *dest* =
(*rule hoare-triple-preI* | *drule asm-rl*[*of* -⊨-]),
(*determ* ‹*elim mod-starE dest*[*elim-format*]›)*?*,
((*determ* ‹*thin-tac* - ⊨ -›)+)*?*,
(*simp* (*no-asm*) *only*: *triv-forall-equality*)*?*

lemma *rule-at-index*:
assumes
1:$P \Longrightarrow_A list\text{-}assn\ A\ xs\ xsi * F$ **and**
2[*simp*]:$i < length\ xs$ **and**
3:$<A\ (xs\ !\ i)\ (xsi\ !\ i)\ *$
$listI\text{-}assn\ (\{0..<length\ xs\}-\{i\})\ A\ xs\ xsi * F>\ c\ <Q'>$ **and**
4: $\bigwedge r.\ Q'\ r \Longrightarrow_A A\ (xs\ !\ i)\ (xsi\ !\ i)\ *$
$listI\text{-}assn\ (\{0..<length\ xs\}-\{i\})\ A\ xs\ xsi * F'\ r$
shows
$<P>c\ <\lambda\ r.\ list\text{-}assn\ A\ xs\ xsi * F'\ r>$
⟨*proof*⟩

end

theory *VEBT-BuildupMemImp*
imports
VEBT-List-Assn
VEBT-Space
Deriving.Derive
VEBT-Member VEBT-Insert
HOL−Library.Countable
Time-Reasoning/Time-Reasoning VEBT-DeleteBounds
begin

14 Imperative van Emde Boas Trees

datatype *VEBTi* = *Nodei* (*nat*∗*nat*) *option nat VEBTi array VEBTi* | *Leafi bool bool*

derive *countable VEBTi*
instance *VEBTi* :: *heap* ⟨*proof*⟩

14.1 Assertions on van Emde Boas Trees

fun *vebt-assn-raw* :: *VEBT* ⇒ *VEBTi* ⇒ *assn* **where**
vebt-assn-raw (*Leaf a b*) (*Leafi ai bi*) = ↑(*ai*=*a* ∧ *bi*=*b*)
| *vebt-assn-raw* (*Node mmo deg tree-list summary*) (*Nodei mmoi degi tree-array summaryi*) = (
↑(*mmoi*=*mmo* ∧ *degi*=*deg*)
∗ *vebt-assn-raw summary summaryi*
∗ (∃$_A$ *tree-is*. *tree-array* ↦$_a$ *tree-is* ∗ *list-assn vebt-assn-raw tree-list tree-is*)
)
| *vebt-assn-raw* - - = *false*

lemmas [*simp del*] = *vebt-assn-raw.simps*

context *VEBT-internal* **begin**

lemmas [*simp*] = *vebt-assn-raw.simps*

lemma *TBOUND-VEBT-case*[*TBOUND*]: **assumes** ⋀ *a b*. *ti* = *Leafi a b* ⟹ *TBOUND* (*f a b*) (*bnd a b*)
⋀ *info deg treeArray summary* . *ti* = *Nodei info deg treeArray summary* ⟹
TBOUND (*f′ info deg treeArray summary*) (*bnd′ info deg treeArray summary*)

shows *TBOUND* (*case ti of Leafi a b* ⇒ *f a b* |
Nodei info deg treeArray summary ⇒ *f′ info deg treeArray summary*)
(*case ti of Leafi a b* ⇒ *bnd a b* |
Nodei info deg treeArray summary ⇒ *bnd′ info deg treeArray summary*)

⟨*proof*⟩

Some Lemmas

lemma *length-corresp*:$(\exists_A$ *tree-is*. *tree-array* $\mapsto_a$ *tree-is*$)$ = *true* $\Longrightarrow$ *return* (*length tree-is*) = *Array-Time.len tree-array*
⟨*proof*⟩

lemma *heaphelp*:**assumes** *h* $\models$
xa $\mapsto_a$ *tree-is* $*$ *list-assn vebt-assn-raw treeList tree-is* $*$
vebt-assn-raw summary xb $*\uparrow$(*None* = *None* $\wedge$ *n* = *n*)$*$
$\uparrow$ (*xc* = *Nodei None n xa xb*)
shows *h* $\models$ *vebt-assn-raw* (*Node None n treeList summary*) *xc*
⟨*proof*⟩

lemma *assnle*: *list-assn vebt-assn-raw treeList tree-is* $*$ (*x13* $\mapsto_a$ *tree-is* $*$ *vebt-assn-raw summary x14*) $\Longrightarrow_A$
vebt-assn-raw summary x14 $*$ *x13* $\mapsto_a$ *tree-is* $*$ *list-assn vebt-assn-raw treeList tree-is*
⟨*proof*⟩

lemma *ext*: *y* < *length treeList* $\Longrightarrow$*x13* $\mapsto_a$ *tree-is* $*$ (*vebt-assn-raw summary x14* $*$
(*vebt-assn-raw* (*treeList* ! *y*) (*tree-is* ! *y*) $*$ *listI-assn* ({*0..*<*length treeList*} − {*y*}) *vebt-assn-raw treeList tree-is*))
$\Longrightarrow_A$ (*x13* $\mapsto_a$ *tree-is* $*$ *vebt-assn-raw summary x14* $*$
(*listI-assn* ({*0..*<*length treeList*} − {*y*}) *vebt-assn-raw treeList tree-is*))$*$*vebt-assn-raw* (*treeList* ! *y*) (*tree-is* ! *y*)
⟨*proof*⟩

lemma *txe*:*y* < *length treeList* $\Longrightarrow$ *vebt-assn-raw* (*treeList* ! *y*) (*tree-is* ! *y*) $*$ *x13* $\mapsto_a$ *tree-is* $*$ *vebt-assn-raw summary x14* $*$
listI-assn ({*0..*<*length treeList*} − {*y*}) *vebt-assn-raw treeList tree-is* $\Longrightarrow_A$
vebt-assn-raw summary x14 $*$ *x13* $\mapsto_a$ *tree-is* $*$ *list-assn vebt-assn-raw treeList tree-is*
⟨*proof*⟩

lemma *recomp*: *i* < *length treeList* $\Longrightarrow$ *vebt-assn-raw* (*treeList* ! *i*) (*tree-is* ! *i*) $*$
listI-assn ({*0..*<*length treeList*} − {*i*}) *vebt-assn-raw treeList tree-is* $*$
x13 $\mapsto_a$ *tree-is* $*$
vebt-assn-raw summary x14 $\Longrightarrow_A$
vebt-assn-raw summary x14 $*$ *x13* $\mapsto_a$ *tree-is* $*$ *list-assn vebt-assn-raw treeList tree-is*
⟨*proof*⟩

lemma *repack*: *i* < *length treeList* $\Longrightarrow$
vebt-assn-raw (*treeList* ! *i*) (*tree-is* ! *i*) $*$
Rest $*$
(*x13* $\mapsto_a$ *tree-is* $*$ *vebt-assn-raw summary x14* $*$
listI-assn ({*0..*<*length treeList*} − {*i*}) *vebt-assn-raw treeList tree-is*)
$\Longrightarrow_A$ *Rest*$*$ *vebt-assn-raw summary x14* $*$ *x13* $\mapsto_a$ *tree-is* $*$ *list-assn vebt-assn-raw treeList tree-is*
⟨*proof*⟩

lemma *big-assn-simp*: $h < length\ treeList \Longrightarrow$
$vebt\text{-}assn\text{-}raw\ (vebt\text{-}delete(treeList\ !\ h)\ l)\ x\ *$
$\uparrow (xaa = vebt\text{-}mint\ (vebt\text{-}delete(treeList\ !\ h)\ l)) *$
$(\ x13 \mapsto_a (tree\text{-}is\ [h := x]) *$
$vebt\text{-}assn\text{-}raw\ summary\ x14\ *$
$listI\text{-}assn\ (\{0..<length\ treeList\} - \{h\})\ vebt\text{-}assn\text{-}raw\ treeList\ tree\text{-}is) \Longrightarrow_A$
$x13 \mapsto_a tree\text{-}is[h:=x]\ *\ vebt\text{-}assn\text{-}raw\ summary\ x14\ *\ \uparrow (xaa = vebt\text{-}mint\ (vebt\text{-}delete(treeList\ !\ h)\ l)) *$
$list\text{-}assn\ vebt\text{-}assn\text{-}raw\ (treeList[h:= (vebt\text{-}delete(treeList\ !\ h)\ l)])\ (tree\text{-}is[h:= x])$
⟨*proof*⟩

lemma *tcd*: $i < length\ treeList \Longrightarrow length\ treeList = length\ treeList' \Longrightarrow$
$vebt\text{-}assn\text{-}raw\ y\ x\ *\ x13 \mapsto_a tree\text{-}is[i:= x]\ *\ vebt\text{-}assn\text{-}raw\ summary\ x14\ *\ listI\text{-}assn\ (\{0..<length\ treeList\} - \{i\})\ vebt\text{-}assn\text{-}raw\ (treeList[i :=y])\ (tree\text{-}is[i := x])$
$\Longrightarrow_A x13 \mapsto_a tree\text{-}is[i:= x]\ *\ vebt\text{-}assn\text{-}raw\ summary\ x14\ *\ list\text{-}assn\ vebt\text{-}assn\text{-}raw\ (treeList[i :=y])\ (tree\text{-}is[i := x])$
⟨*proof*⟩

lemma *big-assn-simp'*: $h < length\ treeList ==> xaa = vebt\text{-}delete\ (treeList\ !\ h) l \Longrightarrow$
$vebt\text{-}assn\text{-}raw\ xaa\ x * \uparrow (xb = vebt\text{-}mint\ xaa) *$
$(x13 \mapsto_a tree\text{-}is[h := x] * vebt\text{-}assn\text{-}raw\ summary\ x14\ *$
$listI\text{-}assn\ (\{0..<length\ treeList\} - \{h\})\ vebt\text{-}assn\text{-}raw\ treeList\ tree\text{-}is) \Longrightarrow_A$
$(x13 \mapsto_a tree\text{-}is[h:= x] * vebt\text{-}assn\text{-}raw\ summary\ x14\ *\ \uparrow (xb = vebt\text{-}mint\ xaa) *$
$list\text{-}assn\ vebt\text{-}assn\text{-}raw\ (treeList[h:= xaa])\ (tree\text{-}is[h:= x]))$
⟨*proof*⟩

lemma *refines-case-VEBTi*[*refines-rule*]: **assumes** $ti = ti' \bigwedge a\ b.\ refines\ (f1\ a\ b)\ (f1'\ a\ b) \bigwedge info\ deg\ treeArray\ summary\ .\ refines\ (f2\ info\ deg\ treeArray\ summary)\ (f2'\ info\ deg\ treeArray\ summary)$
shows $refines\ (case\ ti\ of\ Leafi\ a\ b \Rightarrow f1\ a\ b\ |$
$Nodei\ info\ deg\ treeArray\ summary \Rightarrow f2\ info\ deg\ treeArray\ summary)$
$(case\ ti'\ of\ Leafi\ a\ b \Rightarrow f1'\ a\ b\ |$
$Nodei\ info\ deg\ treeArray\ summary \Rightarrow f2'\ info\ deg\ treeArray\ summary)$
⟨*proof*⟩

14.2 High and low Bitsequences Definition

definition *highi*::*nat* ⇒ *nat* ⇒ *nat Heap* **where**
$highi\ x\ n == return\ (x\ div\ (2\hat{}n))$

definition *lowi*::*nat* ⇒ *nat* ⇒ *nat Heap* **where**
$lowi\ x\ n == return\ (x\ mod\ (2\hat{}n))$

lemma *highi-h*: $<emp>\ highi\ x\ n\ <\lambda\ r.\ \uparrow(r = high\ x\ n)>$
⟨*proof*⟩

lemma *highi-hT*: $<emp>\ highi\ x\ n\ <\lambda\ r.\ \uparrow(r = high\ x\ n)> T[1]$
⟨*proof*⟩

lemma *lowi-h*: <*emp*> *lowi x n* <λ *r*. ↑(*r* = *low x n*)>
⟨*proof*⟩

lemma *lowi-hT*: <*emp*> *lowi x n* <λ *r*. ↑(*r* = *low x n*)>*T*[*1*]
⟨*proof*⟩

15 Imperative Implementation of *vebt − buildup*

fun *replicatei*::*nat* ⇒'*a Heap* ⇒ ('*a list*) *Heap* **where**
replicatei 0 x = *return* []|
replicatei (*Suc n*) *x* = *do*{ *y* <− *x*;
ys <− *replicatei n x*;
return (*y*#*ys*) }

lemma *time-replicate*: ⟦⋀*h*. *time x h* ≤ *c* ⟧ ⟹ *time* (*replicatei n x*) *h* ≤ (*1*+(*1*+*c*)∗*n*)
⟨*proof*⟩

lemma *TBOUND-replicate*: ⟦*TBOUND x c*⟧ ⟹ *TBOUND* (*replicatei n x*) (*1*+(*1*+*c*)∗*n*)
⟨*proof*⟩

lemma *refines-replicate*[*refines-rule*]:
refines f f' ⟹ *refines* (*replicatei n f*) (*replicatei n f'*)
⟨*proof*⟩

fun *vebt-buildupi'*::*nat* ⇒ *VEBTi Heap* **where**
vebt-buildupi' 0 = *return* (*Leafi False False*)|
vebt-buildupi' (*Suc 0*) = *return* (*Leafi False False*)|
vebt-buildupi' n = (*if even n then* (*let half* = *n div 2 in do*{
treeList <− *replicatei* (*2^half*) (*vebt-buildupi' half*);
assert' (*length treeList* = *2^half*);
trees <− *Array-Time.of-list treeList*;
summary <− (*vebt-buildupi' half*);
return (*Nodei None n trees summary*)})
else (*let half* = *n div 2 in do*{
treeList <− *replicatei* (*2^*(*Suc half*)) (*vebt-buildupi' half*);
assert' (*length treeList* = *2^Suc half*);
trees <− *Array-Time.of-list treeList*;
summary <− (*vebt-buildupi'* (*Suc half*));
return (*Nodei None n trees summary*)}))

end

context begin
interpretation *VEBT-internal* ⟨*proof*⟩

fun *vebt-buildupi*::*nat* ⇒ *VEBTi Heap* **where**
vebt-buildupi 0 = *return* (*Leafi False False*)|
vebt-buildupi (*Suc 0*) = *return* (*Leafi False False*)|

```
  vebt-buildupi n =  (if even n then (let half = n div 2 in do{
                          treeList <- replicatei  (2^half) (vebt-buildupi half);
                          trees <- Array-Time.of-list  treeList;
                          summary <- (vebt-buildupi half);
                          return (Nodei None n  trees summary)})
              else (let half = n div 2 in  do{
                          treeList <-    replicatei (2^(Suc half)) (vebt-buildupi half);
                          trees <- Array-Time.of-list  treeList;
                          summary <- (vebt-buildupi (Suc half));
                          return (Nodei None n trees summary)} ))
```

end

context *VEBT-internal* **begin**

lemma *vebt-buildupi-refines*: *refines* (*vebt-buildupi n*) (*vebt-buildupi′ n*)
⟨*proof*⟩

```
fun T-vebt-buildupi where
  T-vebt-buildupi 0 = Suc 0
| T-vebt-buildupi (Suc 0) = Suc 0
| T-vebt-buildupi (Suc (Suc n)) = (
    if even n then
      Suc (Suc (Suc (T-vebt-buildupi (Suc (n div 2)) +
                  (4 * 2 ^ (n div 2) + 2 * (T-vebt-buildupi (Suc (n div 2)) * 2 ^ (n div 2))))))
    else
        Suc (Suc (Suc (T-vebt-buildupi (Suc (Suc (n div 2))) +
                  (8 * 2 ^ (n div 2) + 4 * (T-vebt-buildupi (Suc (n div 2)) * 2 ^ (n div 2)))))))
```

lemma *TBOUND-vebt-buildupi*:
defines *foo* ≡ *T-vebt-buildupi*
shows *TBOUND* (*vebt-buildupi′ n*) (*foo n*)
⟨*proof*⟩

lemma *T-vebt-buildupi*: *time* (*vebt-buildupi′ n*) *h* ≤ *T-vebt-buildupi n*
⟨*proof*⟩

lemma *repli-cons-repl*: <*Q*> *x* <λ *r*. *Q*∗ *A y r* > ⟹ <*Q*> *replicatei n x* <λ *r*. *Q*∗*list-assn A* (*replicate n y*) *r* >
⟨*proof*⟩

corollary *repli-emp*: <*emp*> *x* <λ *r*. *A y r* > ⟹ <*emp*> *replicatei n x* <λ *r*. *list-assn A* (*replicate n y*) *r* >
⟨*proof*⟩

lemma *builupi′corr*: <*emp*> *vebt-buildupi′ n* <λ *r*. *vebt-assn-raw* (*vebt-buildup n*) *r*>
⟨*proof*⟩

lemma *htt-vebt-buildupi'*: $< emp >$ (*vebt-buildupi'* *n*) $<\lambda$ *r*. *vebt-assn-raw* (*vebt-buildup n*) *r*$>$ *T* [*T-vebt-buildupi n*]
⟨*proof*⟩

lemma *builupicorr*: $<emp>$ *vebt-buildupi n* $<\lambda$ *r*. *vebt-assn-raw* (*vebt-buildup n*) *r*$>$
⟨*proof*⟩

lemma *htt-vebt-buildupi*: $<emp>$ (*vebt-buildupi n*) $<\lambda$ *r*. *vebt-assn-raw* (*vebt-buildup n*) *r*$>$ *T* [*T-vebt-buildupi n*]
⟨*proof*⟩

Closed bound for $T - vebt - buildupi$

Amortization

lemma *T-vebt-buildupi-gq-0*: *T-vebt-buildupi n* > *0*
⟨*proof*⟩

fun *T-vebt-buildupi'*::*nat* ⇒ *int* **where**
T-vebt-buildupi' 0 = *1*
| *T-vebt-buildupi'* (*Suc 0*) = *1*
| *T-vebt-buildupi'* (*Suc* (*Suc n*)) = (
if even n then
3+(*T-vebt-buildupi'* (*Suc* (*n div 2*)) +
(*4* ∗ *2* ^ (*n div 2*) + *2* ∗ (*T-vebt-buildupi'* (*Suc* (*n div 2*)) ∗ *2* ^ (*n div 2*))))
else
3+ (*T-vebt-buildupi'* (*Suc* (*Suc* (*n div 2*))) +
(*8* ∗ *2* ^ (*n div 2*) + *4* ∗ (*T-vebt-buildupi'* (*Suc* (*n div 2*)) ∗ *2* ^ (*n div 2*)))))

lemma *Tbuildupi-buildupi'*: *T-vebt-buildupi n* = *T-vebt-buildupi' n*
⟨*proof*⟩

fun *Tb*::*nat* ⇒ *int* **where**
Tb 0 = *3*
| *Tb* (*Suc 0*) =*3*
| *Tb* (*Suc* (*Suc n*)) = (
if even n then
5+ *Tb* (*Suc* (*n div 2*)) + (*Tb* (*Suc* (*n div 2*))) ∗ *2* ^ (*Suc* (*n div 2*))
else
5 + *Tb* (*Suc* (*Suc* (*n div 2*))) + (*Tb* (*Suc* (*n div 2*))) ∗ *2* ^ (*Suc* (*Suc* (*n div 2*))))

lemma *Tb-T-vebt-buildupi'*: *T-vebt-buildupi' n* ≤ *Tb n* − *2*
⟨*proof*⟩

fun *Tb'*::*nat* ⇒ *nat* **where**
Tb' 0 = *3*
| *Tb'* (*Suc 0*) =*3*
| *Tb'* (*Suc* (*Suc n*)) = (
if even n then
5+ *Tb'* (*Suc* (*n div 2*)) + (*Tb'* (*Suc* (*n div 2*))) ∗ *2* ^ (*Suc* (*n div 2*))
else

$5 + Tb'\ (Suc\ (Suc\ (n\ div\ 2)))\ + (Tb'\ (Suc\ (n\ div\ 2))) * 2\ \hat{}(Suc\ (Suc\ (n\ div\ 2))))$

lemma *Tb-Tb'*: $Tb\ t = Tb'\ t$
⟨*proof*⟩

lemma *Tb-T-vebt-buildupi*: $T\text{-}vebt\text{-}buildupi\ n \leq Tb\ n - 2$
⟨*proof*⟩

lemma *Tb-T-vebt-buildupi''*: $T\text{-}vebt\text{-}buildupi\ n \leq Tb'\ n - 2$
⟨*proof*⟩

lemma *Tb'-cnt*: $Tb'\ n \leq 5 * cnt'\ (vebt\text{-}buildup\ n)$
⟨*proof*⟩

lemma *T-vebt-buildupi-cnt'*: $T\text{-}vebt\text{-}buildupi\ n\ \leq 5 * cnt\ (vebt\text{-}buildup\ n)$
⟨*proof*⟩

lemma *T-vebt-buildupi-univ*:
assumes $u = 2\hat{}n$
shows $T\text{-}vebt\text{-}buildupi\ n\ \leq 10 * u$
⟨*proof*⟩

lemma *htt-vebt-buildupi'-univ*:
assumes $u = 2\hat{}n$
shows
$< emp > (vebt\text{-}buildupi'\ n) <\lambda\ r.\ vebt\text{-}assn\text{-}raw\ (vebt\text{-}buildup\ n)\ r> T\ [10 * u]$
⟨*proof*⟩

We obtain the main theorem for *buildupi*

lemma *htt-vebt-buildupi-univ*:
assumes $u = 2\hat{}n$
shows
$< emp > (vebt\text{-}buildupi\ n) <\lambda\ r.\ vebt\text{-}assn\text{-}raw\ (vebt\text{-}buildup\ n)\ r> T\ [10 * u]$
⟨*proof*⟩

lemma *vebt-buildupi-rule*: $<\uparrow\ (n > 0)> vebt\text{-}buildupi\ \ n <\lambda\ r.\ vebt\text{-}assn\text{-}raw\ (vebt\text{-}buildup\ n)\ r > T[10 * 2\hat{}n]$
⟨*proof*⟩

lemma *TBOUND-buildupi*: **assumes** $n>0$ **shows** $TBOUND\ (vebt\text{-}buildupi\ n)\ (10 * 2\ \hat{}\ n)$
⟨*proof*⟩

16 Minimum and Maximum Determination

end

context begin
interpretation *VEBT-internal* ⟨*proof*⟩

fun *vebt-minti*::*VEBTi* ⇒ *nat option Heap* **where**
vebt-minti (*Leafi a b*) = (*if a then return* (*Some 0*) *else if b then return* (*Some 1*) *else return None*)|
vebt-minti (*Nodei None - - -*) = *return None*|
vebt-minti (*Nodei* (*Some* (*mi*,*ma*)) *- - -*) = *return* (*Some mi*)

fun *vebt-maxti*::*VEBTi* ⇒ *nat option Heap* **where**
vebt-maxti (*Leafi a b*) = (*if b then return* (*Some 1*) *else if a then return* (*Some 0*) *else return None*)|
vebt-maxti (*Nodei None - - -*) = *return None*|
vebt-maxti (*Nodei* (*Some* (*mi*,*ma*)) *- - -*) = *return* (*Some ma*)

end

context *VEBT-internal* **begin**

lemma *vebt-minti-h*:<*vebt-assn-raw t ti*> *vebt-minti ti* <λ*r*. *vebt-assn-raw t ti* ∗ ↑(*r* = *vebt-mint t*)>

⟨*proof*⟩

lemma *vebt-maxti-h*:<*vebt-assn-raw t ti*> *vebt-maxti ti* <λ*r*. *vebt-assn-raw t ti* ∗ ↑(*r* = *vebt-maxt t*)>
⟨*proof*⟩

lemma *TBOUND-vebt-maxti*[*TBOUND*]: *TBOUND* (*vebt-maxti t*) *1*
⟨*proof*⟩

lemma *TBOUND-vebt-minti*[*TBOUND*]: *TBOUND* (*vebt-minti t*) *1*
⟨*proof*⟩

lemma *vebt-minti-hT*:<*vebt-assn-raw t ti*> *vebt-minti ti* <λ*r*. *vebt-assn-raw t ti* ∗ ↑(*r* = *vebt-mint t*)>*T*[*1*]
⟨*proof*⟩

lemma *vebt-maxti-hT*:<*vebt-assn-raw t ti*> *vebt-maxti ti* <λ*r*. *vebt-assn-raw t ti* ∗ ↑(*r* = *vebt-maxt t*)>*T*[*1*]
⟨*proof*⟩

lemma *vebt-maxtilist*:*i* < *length ts* ⟹
<*list-assn vebt-assn-raw ts tsi*> *vebt-maxti* (*tsi* ! *i*)
< λ *r*. ↑(*r* = *vebt-maxt* (*ts* ! *i*)) ∗*list-assn vebt-assn-raw ts tsi*>
⟨*proof*⟩

lemma *vebt-mintilist*:*i* < *length ts* ⟹
<*list-assn vebt-assn-raw ts tsi*> *vebt-minti* (*tsi* ! *i*)
< λ *r*. ↑(*r* = *vebt-mint* (*ts* ! *i*)) ∗*list-assn vebt-assn-raw ts tsi*>
⟨*proof*⟩

17 Membership Test on imperative van Emde Boas Trees

end

context begin
interpretation *VEBT-internal* ⟨*proof*⟩

```
partial-function (heap-time) vebt-memberi::VEBTi ⇒ nat ⇒ bool Heap where
  vebt-memberi t x =
 (case t of
       (Leafi a b ) ⇒ return (if x = 0 then a else if x=1 then b else False) |
        (Nodei info deg treeList summary ) ⇒ (
              case info of None ⇒ return False |
               (Some (mi, ma)) ⇒ ( if deg ≤ 1 then return False else (
                                   if x = mi then return True else
                                   if x = ma then return True else
                                   if x < mi then return False else
                                   if x > ma then return False else
                                   (do {
                                       h ← highi x (deg div 2);
                                       l ← lowi x (deg div 2);
                                       len ← Array-Time.len treeList;
                                       if h < len then do {
                                       th ← Array-Time.nth treeList h;
                                       vebt-memberi th l
                                       } else return False
                                   }))))))
```

end

context *VEBT-internal* **begin**

```
partial-function (heap-time) vebt-memberi'::VEBT ⇒VEBTi ⇒ nat ⇒ bool Heap where
  vebt-memberi' t ti x =
 (case ti of
       (Leafi a b ) ⇒ return (if x = 0 then a else if x=1 then b else False) |
        (Nodei info deg treeArray summary ) ⇒ ( do {assert' (is-Node t);
              case info of None ⇒ return False |
               (Some (mi, ma)) ⇒ ( if deg ≤ 1 then return False else (
                                   if x = mi then return True else
                                   if x = ma then return True else
                                   if x < mi then return False else
                                   if x > ma then return False else
                                   (do {
                                       let (info',deg',treeList,summary') =
                                        (case t of (Node info' deg' treeList summary') ⇒
                                         (info', deg', treeList, summary'));
                                    assert'(info= info' ∧ deg = deg');
                                       h ← highi x (deg div 2);
```

```
                    l ← lowi x (deg div 2);
                    assert'(l = low x (deg div 2) ∧ h = high x (deg div 2));
                    len ← Array-Time.len treeArray;
                    assert'(len = length treeList);
                    if h < len then do {
                          assert'(h = high x (deg div 2) ∧ h < length treeList);

                      th ← Array-Time.nth treeArray h;
                      vebt-memberi' (treeList ! h) th l }
                    else return False
                }))))}))
```

lemma *highsimp*: *return* (*high x n*) = *highi x n*
⟨*proof*⟩

lemma *lowsimp*: *return* (*low x n*) = *lowi x n*
⟨*proof*⟩

lemma *TBOUND-highi*[*TBOUND*]: *TBOUND* (*highi x n*) *1*
⟨*proof*⟩

lemma *TBOUND-lowi*[*TBOUND*]: *TBOUND* (*lowi x n*) *1*
⟨*proof*⟩

Correctness of $vebt - memberi$

lemma *vebt-memberi'-rf-abstr*: <*vebt-assn-raw t ti*> *vebt-memberi' t ti x* <λ*r*. *vebt-assn-raw t ti* ∗ ↑(*r* = *vebt-member t x*)>
⟨*proof*⟩

lemma *TBOUND-vebt-memberi*:
defines *foo-def*: ⋀ *t x*. *foo t x* ≡ *4* ∗ (*1*+*height t*)
shows *TBOUND* (*vebt-memberi' t ti x*) (*foo t x*)
⟨*proof*⟩

lemma *vebt-memberi-refines*: *refines* (*vebt-memberi ti x*) (*vebt-memberi' t ti x*)
⟨*proof*⟩

lemma *htt-vebt-memberi*:
<*vebt-assn-raw t ti*>*vebt-memberi ti x* <λ *r*. *vebt-assn-raw t ti* ∗ ↑(*r* = *vebt-member t x*)>*T*[*5* + *5* ∗ *height t*]
⟨*proof*⟩

lemma *htt-vebt-memberi-invar-vebt*: **assumes** *invar-vebt t n* **shows**
<*vebt-assn-raw t ti*> *vebt-memberi ti x* <λ *r*. *vebt-assn-raw t ti* ∗ ↑(*r* = *vebt-member t x*)>*T*[*5* + *5* ∗ (*nat* ⌈*lb n* ⌉)]
⟨*proof*⟩

17.1 *minNulli*: empty tree?

fun *minNulli*::*VEBTi* ⇒ *bool Heap* **where**

minNulli (Leafi False False) = return True|
minNulli (Leafi - -) = return False|
minNulli (Nodei None - - -) = return True|
minNulli (Nodei (Some -) - - -) = return False

lemma *minNulli-rule*[*sep-heap-rules*]: *<vebt-assn-raw t ti> minNulli ti <λr. vebt-assn-raw t ti ∗ ↑(r = minNull t)>*
⟨*proof*⟩

lemma *TBOUND-minNulli*[*TBOUND*]: *TBOUND (minNulli t) 1*
⟨*proof*⟩

lemma *minNrulli-ruleT*:
<vebt-assn-raw t ti> minNulli ti <λr. vebt-assn-raw t ti ∗ ↑(r = minNull t)>T[1]
⟨*proof*⟩

18 Imperative *vebt − insert* to van Emde Boas Tree

end

context begin
interpretation *VEBT-internal* ⟨*proof*⟩

partial-function (*heap-time*) *vebt-inserti*::*VEBTi ⇒ nat ⇒VEBTi Heap* **where**
vebt-inserti t x = (case t of
(Leafi a b) ⇒ (if x=0 then return (Leafi True b) else if x=1
then return (Leafi a True) else return (Leafi a b)) |
(Nodei info deg treeArray summary) ⇒ (case info of None ⇒
if deg ≤ 1 then
return (Nodei info deg treeArray summary)
else
return (Nodei (Some (x,x)) deg treeArray summary)|
(Some minma) ⇒
(if deg ≤ 1
then return (Nodei info deg treeArray summary)
else (do{
mi <− return (fst minma);
ma <− return (snd minma);
xn <− (if x < mi then return mi else return x);
minn <− (if x < mi then return x else return mi);
l<− lowi xn (deg div 2);
h <− highi xn (deg div 2);
len ← Array-Time.len treeArray;
if h < len ∧ ¬ (x = mi ∨ x = ma) then do {
node <− Array-Time.nth treeArray h;
empt <− minNulli node;
newnode <− vebt-inserti node l;

```
                                        newarray <− Array-Time.upd h newnode treeArray;
                                        newsummary<−(if empt then
                                                vebt-inserti summary h
                                                else  return summary);
                                      man <− (if xn > ma then return xn else return ma);
                                          return (Nodei (Some (minn, man)) deg newarray
newsummary)}
                                            else return  (Nodei (Some (mi,ma)) deg treeArray
summary)
                                  }))))
```

end

context *VEBT-internal* **begin**

```
partial-function (heap-time) vebt-inserti′::VEBT ⇒VEBTi ⇒ nat ⇒VEBTi Heap where
  vebt-inserti′ t ti x = (case ti of
            (Leafi a b) ⇒ (if x=0 then return (Leafi True b) else if x=1
                          then return (Leafi a True) else return (Leafi a b)) |
            (Nodei info deg treeArray summary) ⇒ ( case info of None ⇒
                                        if deg ≤ 1 then
                                            return  (Nodei info deg treeArray summary)
                                        else
                                                return (Nodei (Some (x,x)) deg treeArray
summary)|
                                    (Some minma) ⇒
                                         ( if deg ≤ 1
                                    then return  (Nodei info deg treeArray summary)
                                     else  (
                                do{
                                    assert′ (is-Node t);
                                    let (info′,deg′,treeList,summary′) =
                                    (case t of (Node info′ deg′ treeList summary′) ⇒
                                    (info′, deg′, treeList, summary′));
                                    assert′(info= info′ ∧ deg = deg′);
                                            let (mi′, ma′) = (the info′);
                                            mi <− return (fst minma);
                                            ma <− return (snd minma);
                                            xn <− (if x < mi then return mi else return x);
                                            let xn′ =  (if x < mi′ then  mi′ else x);
                                            minn <− (if x < mi then return x else return mi);
                                            let  minn′ = (if x < mi′ then x else mi′);
                                            l<− lowi xn (deg div 2);
                                            assert′ (l = low xn′ (deg′ div 2));
                                            h <− highi xn (deg div 2);
                                            len ← Array-Time.len treeArray;
                                            if h < len ∧ ¬ (x = mi ∨ x = ma) then do {
                                               assert′ (h = high xn′ (deg′ div 2));
                                               assert′( h < length treeList);
```

node <− Array-Time.nth treeArray h;
empt <− minNulli node;
assert′ (empt = minNull (treeList ! h));
newnode <− vebt-inserti′ (treeList ! h) node l;
newarray <− Array-Time.upd h newnode treeArray;
newsummary<−(if empt then
vebt-inserti′ summary′ summary h
else return summary);
man <− (if xn > ma then return xn else return ma);
return (Nodei (Some (minn, man)) deg newarray newsummary)}
else return (Nodei (Some (mi,ma)) deg treeArray summary)
})))

lemmas *listI-assn-wrap-insert = listI-assn-reinsert-upd′*[
where *x=VEBT-Insert.vebt-insert - -* **and** *A=vebt-assn-raw*]

lemma *vebt-inserti′-rf-abstr*: *<vebt-assn-raw t ti> vebt-inserti′ t ti x <λr. vebt-assn-raw (vebt-insert t x) r >*
⟨*proof*⟩

lemma *TBOUND-minNull*: *minNull t ⟹ TBOUND (vebt-inserti′ t ti x) 1*
⟨*proof*⟩

lemma *TBOUND-vebt-inserti*:
defines *foo-def*: *⋀ t x. foo t x ≡ if minNull t then 1 else 13 ∗ (1+height t)*
shows *TBOUND (vebt-inserti′ t ti x) (foo t x)*
⟨*proof*⟩

lemma *vebt-inserti-refines*: *refines (vebt-inserti ti x) (vebt-inserti′ t ti x)*
⟨*proof*⟩

lemma *htt-vebt-inserti*:
<vebt-assn-raw t ti> vebt-inserti ti x <λ r. vebt-assn-raw (vebt-insert t x) r>T[13 + 13 ∗ height t]
⟨*proof*⟩

lemma *htt-vebt-inserti-invar-vebt*: **assumes** *invar-vebt t n* **shows**
<vebt-assn-raw t ti> vebt-inserti ti x <λ r. vebt-assn-raw (vebt-insert t x) r>T[13 + 13 ∗ (nat ⌈lb n ⌉)]
⟨*proof*⟩

end
end

theory *VEBT-SuccPredImperative*
imports *VEBT-BuildupMemImp VEBT-Succ VEBT-Pred*
begin

context begin
interpretation *VEBT-internal* ⟨*proof*⟩

19 Imperative Successor

partial-function (*heap-time*) *vebt-succi*::*VEBTi* ⇒ *nat* ⇒ (*nat option*) *Heap* **where**
vebt-succi t x = (*case t of* (*Leafi a b*) ⇒(*if x* = *0 then* (*if b then return* (*Some 1*) *else return None*)
else return None)|
(*Nodei info deg treeArray summary*) ⇒ (
case info of None ⇒ *return None* |
(*Some mima*) ⇒ (*if deg* ≤ *1 then return None else*
(*if x* < *fst mima then return* (*Some* (*fst mima*)) *else*
if x ≥ *snd mima then return None else*
do {
l <− *lowi x* (*deg div 2*);
h <− *highi x* (*deg div 2*);
aktnode <− *Array-Time.nth treeArray h*;
maxlow <− *vebt-maxti aktnode*;
if (*maxlow* ≠ *None* ∧ (*Some l* <$_o$ *maxlow*))
then do {
succy <− *vebt-succi aktnode l*;
return (*Some* (2^(*deg div 2*)) *∗$_o$ Some h* +$_o$ *succy*)
}
else do {
succsum <− *vebt-succi summary h*;
if succsum = *None then*
return None
else
do{
nextnode <− *Array-Time.nth treeArray* (*the succsum*);
minnext <− *vebt-minti nextnode*;
return (*Some* (2^(*deg div 2*)) *∗$_o$ succsum* +$_o$ *minnext*)
}
}

})
)))

end

context *VEBT-internal* **begin**

partial-function (*heap-time*) *vebt-succi'*::*VEBT* ⇒ *VEBTi* ⇒ *nat* ⇒ (*nat option*) *Heap* **where**
vebt-succi' t ti x = (*case ti of* (*Leafi a b*) ⇒(*if x* = *0 then* (*if b then return* (*Some 1*) *else return None*)
else return None)|
(*Nodei info deg treeArray summary*) ⇒ *do* { *assert'*(*is-Node t*);
let (*info'*,*deg'*,*treeList*,*summary'*) =

```
(case t of Node info' deg' treeList summary' ⇒ (info',deg',treeList,summary'));
  assert'(info'=info ∧ deg'=deg ∧ is-Node t);
 case info of None ⇒ return None |
(Some mima) ⇒ (if deg ≤ 1 then return None else
                (if x < fst mima then return (Some (fst mima)) else
                 if x ≥ snd mima then return None else
                  do {
                     l <− lowi x (deg div 2);
                     h <− highi x (deg div 2);

                     assert'(l = low x (deg div 2));
                     assert'(h = high x (deg div 2));
                     assert'(h < length treeList);

                     aktnode <− Array-Time.nth treeArray h;
                     let aktnode' = treeList!h;

                        maxlow <− vebt-maxti aktnode;
                        assert' (maxlow = vebt-maxt aktnode');
                        if (maxlow ≠ None ∧ (Some l <o  maxlow))
                        then do {
                                succy <− vebt-succi' aktnode' aktnode l;
                                 return ( Some (2^(deg div 2)) *o Some h +o succy)
                                }
                        else do {
                               succsum <−  vebt-succi' summary' summary h;
                           assert'(succsum = None ⟷ vebt-succ summary' h = None);
                               if succsum = None then do{
                                   return None}
                                 else
                                   do{
                                   nextnode <− Array-Time.nth treeArray (the succsum);
                                       minnext <− vebt-minti nextnode;
                                   return (Some (2^(deg div 2)) *o succsum +o minnext)
                                     }
                               }

                     })
)})
```

theorem *vebt-succi'-rf-abstr:invar-vebt t n ⟹ <vebt-assn-raw t ti> vebt-succi' t ti x <λr. vebt-assn-raw t ti ∗ ↑(r = vebt-succ t x)>*
⟨*proof*⟩

lemma *TBOUND-vebt-succi*:
  defines *foo-def*: ⋀ *t x. foo t x ≡ 7 ∗ (1+height t)*
  shows *TBOUND (vebt-succi' t ti x) (foo t x)*
  ⟨*proof*⟩

lemma *vebt-succi-refines*: *refines* (*vebt-succi ti x*) (*vebt-succi' t ti x*)
⟨*proof*⟩

lemma *htt-vebt-succi*: **assumes** *invar-vebt t n*
shows <*vebt-assn-raw t ti*> *vebt-succi ti x* <λ *r. vebt-assn-raw t ti* ∗ ↑(*r* = *vebt-succ t x*) >*T*[7 + 7∗(*nat* ⌈*lb n*⌉)]
⟨*proof*⟩

end

context begin
interpretation *VEBT-internal* ⟨*proof*⟩

partial-function (*heap-time*) *vebt-predi*::*VEBTi* ⇒ *nat* ⇒ (*nat option*) *Heap* **where**
vebt-predi t x = (*case t of* (*Leafi a b*) ⇒(*if x* ≥ *2then* (*if b then return* (*Some 1*) *else if a then return* (*Some 0*) *else return None*)
else if x = *1 then* (*if a then return* (*Some 0*) *else return None*) *else return None*)|
(*Nodei info deg treeArray summary*) ⇒ (
case info of None ⇒ *return None* |
(*Some mima*) ⇒ (*if deg* ≤ *1 then return None else*
(*if x* > *snd mima then return* (*Some* (*snd mima*)) *else*
do {
l <− *lowi x* (*deg div 2*);
h <− *highi x* (*deg div 2*);
aktnode <− *Array-Time.nth treeArray h*;
minlow <− *vebt-minti aktnode*;
if (*minlow* ≠ *None* ∧ (*Some l* >*o* *minlow*))
then do {
predy <− *vebt-predi aktnode l*;
return (*Some* (2^(*deg div 2*)) ∗*o Some h* +*o predy*)
}
else do {
predsum <− *vebt-predi summary h*;
if predsum = *None then*
if x > *fst mima then*
return (*Some* (*fst mima*))
else
return None
else
do{
nextnode <− *Array-Time.nth treeArray* (*the predsum*);
maxnext <− *vebt-maxti nextnode*;
return (*Some* (2^(*deg div 2*)) ∗*o predsum* +*o maxnext*)
}
}
})))))

end
context *VEBT-internal* **begin**

20 Imperative Predecessor

partial-function (*heap-time*) *vebt-predi'*::*VEBT* ⇒ *VEBTi* ⇒ *nat* ⇒ (*nat option*) *Heap* **where**
vebt-predi' t ti x = (*case ti of* (*Leafi a b*) ⇒(*if x* ≥ *2then* (*if b then return* (*Some 1*) *else if a then return* (*Some 0*) *else return None*)
else if x = *1 then* (*if a then return* (*Some 0*) *else return None*) *else return None*)|
(*Nodei info deg treeArray summary*) ⇒ (*do* { *assert'*(*is-Node t*);
let (*info'*,*deg'*,*treeList*,*summary'*) =
(*case t of Node info' deg' treeList summary'* ⇒ (*info'*,*deg'*,*treeList*,*summary'*));
assert'(*info'*=*info* ∧ *deg'*=*deg* ∧ *is-Node t*);
case info of None ⇒ *return None* |
(*Some mima*) ⇒ (*if deg* ≤ *1 then return None else*
(*if x* > *snd mima then return* (*Some* (*snd mima*)) *else*
do {
l <− *lowi x* (*deg div 2*);
h <− *highi x* (*deg div 2*);

assert'(*l* = *low x* (*deg div 2*));
assert'(*h* = *high x* (*deg div 2*));
assert'(*h* < *length treeList*);

aktnode <− *Array-Time.nth treeArray h*;
let aktnode' = *treeList*!*h*;
minlow <− *vebt-minti aktnode*;
assert' (*minlow* = *vebt-mint aktnode'*);

if (*minlow* ≠ *None* ∧ (*Some l* >$_o$ *minlow*))
then do {
predy <− *vebt-predi' aktnode' aktnode l*;
return (*Some* (2^(*deg div 2*)) *∗*$_o$ *Some h* +$_o$ *predy*)
}
else do {
predsum <− *vebt-predi' summary' summary h*;
assert'(*predsum* = *None* ⟷ *vebt-pred summary' h* = *None*);
if predsum = *None then*
if x > *fst mima then*
return (*Some* (*fst mima*))
else
return None
else
do{
nextnode <− *Array-Time.nth treeArray* (*the predsum*);
maxnext <− *vebt-maxti nextnode*;
return (*Some* (2^(*deg div 2*)) *∗*$_o$ *predsum* +$_o$ *maxnext*)
}

}
}))}))

theorem *vebt-pred'-rf-abstr*:*invar-vebt t n* ⟹ <*vebt-assn-raw t ti*> *vebt-predi' t ti x* <λ*r. vebt-assn-raw t ti* ∗ ↑(*r* = *vebt-pred t x*)>
⟨*proof*⟩

lemma *TBOUND-vebt-predi*:
defines *foo-def*: ⋀ *t x. foo t x* ≡ 7 ∗ (*1*+*height t*)
shows *TBOUND* (*vebt-predi' t ti x*) (*foo t x*)
⟨*proof*⟩

lemma *vebt-predi-refines*: *refines* (*vebt-predi ti x*) (*vebt-predi' t ti x*)
⟨*proof*⟩

lemma *htt-vebt-predi*: **assumes** *invar-vebt t n*
shows <*vebt-assn-raw t ti*> *vebt-predi ti x* <λ *r. vebt-assn-raw t ti* ∗ ↑(*r* = *vebt-pred t x*) >*T*[7 + 7∗(*nat* ⌈*lb n*⌉)]
⟨*proof*⟩

end
end

theory *VEBT-DelImperative* **imports** *VEBT-DeleteCorrectness VEBT-SuccPredImperative*
begin

context begin
interpretation *VEBT-internal* ⟨*proof*⟩

21 Imperative Delete

partial-function (*heap-time*) *vebt-deletei*::*VEBTi* ⇒ *nat* ⇒ *VEBTi Heap* **where**
vebt-deletei t x = (*case t of* (*Leafi a b*) ⇒ (*if x* = *0 then return* (*Leafi False b*) *else*
if x = *1 then return* (*Leafi a False*) *else*
return (*Leafi a b*)) |
(*Nodei info deg treeArray summary*) ⇒ (
if deg ≤ *1 then return* (*Nodei info deg treeArray summary*) *else*
case info of None ⇒ *return* (*Nodei info deg treeArray summary*)|
(*Some mima*) ⇒ (*if x* < *fst mima* ∨ *x* > *snd mima then return* (*Nodei info deg treeArray summary*)
else if fst mima = *x* ∧ *snd mima* = *x then return* (*Nodei None deg treeArray summary*)
else do{ *xminew* <− (*if x* = *fst mima then do* {
firstcluster <− *vebt-minti summary*;
firsttree <− *Array-Time.nth treeArray* (*the firstcluster*);
mintft <− *vebt-minti firsttree*;
let xn = (*2*^(*deg div 2*) ∗ (*the firstcluster*) + (*the mintft*));

```
                    return (xn, xn)
                        }
                   else return (x, fst mima));
          let xnew = fst xminew;
          let minew = snd xminew;
          h <− highi xnew (deg div 2);
          l <− lowi xnew (deg div 2);
          aktnode <− Array-Time.nth treeArray h;
          aktnode'<−vebt-deletei aktnode l;
          treeArray' <− Array-Time.upd h aktnode' treeArray;
          miny <− vebt-minti aktnode';
         (if (miny = None) then
          do{
             summary' <−vebt-deletei summary h;
             ma <− (if xnew = snd mima then
             do{
                summax <− vebt-maxti summary';
                if summax = None then
                     return minew
                else do{
                    maxtree <− Array-Time.nth treeArray' (the
summax);
                      mofmtree<− vebt-maxti maxtree;
                      return (the summax * 2^(deg div 2) +
                                  the mofmtree )
                      }
              }
                else return (snd mima));
             return (Nodei (Some (minew, ma)) deg treeArray'
summary')
          } else  if xnew = snd mima then
            do{
               nextree <− Array-Time.nth treeArray' h;
               maxnext<− vebt-maxti nextree;
               let ma = h * 2^(deg div 2) +
                           (the maxnext);
             return (Nodei (Some ( minew, ma)) deg treeArray'
summary)
              }
             else return (Nodei (Some (minew, snd mima)) deg
treeArray' summary) )
          }))))
```

end

context *VEBT-internal* **begin**

Some general lemmas

lemma *midextr*:$(P * Q * Q' * R \Longrightarrow_A X) \Longrightarrow (P * R * Q * Q' \Longrightarrow_A X)$

⟨*proof*⟩

lemma *groupy*: $A *B * (C * D) \Longrightarrow_A X \Longrightarrow A *B * C * D \Longrightarrow_A X$
⟨*proof*⟩

lemma *swappa*: $B* A* C \Longrightarrow_A X \Longrightarrow A *B * C \Longrightarrow_A X$
⟨*proof*⟩

lemma *mulcomm*: $(i::nat) * (2 * 2 \hat{} (va\ div\ 2)) = (2 * 2 \hat{} (va\ div\ 2)) * i$
⟨*proof*⟩

Modified function with ghost variable

```
partial-function (heap-time) vebt-deletei'::VEBT ⇒ VEBTi ⇒ nat ⇒ VEBTi Heap where
  vebt-deletei' t ti x = (case ti of (Leafi a b) ⇒ (if x = 0 then return (Leafi False b) else
                                    if x = 1 then return (Leafi a False) else
                                     return (Leafi a b)) |
                         (Nodei info deg treeArray summary) ⇒ (
                               do { assert'( is-Node t);
                          let (info',deg',treeList,summary') =
                         (case t of Node info' deg' treeList summary'
                                  ⇒ (info',deg',treeList,summary'));
                          assert'(info'=info ∧ deg'=deg ∧ is-Node t);
                                 if deg ≤ 1 then return (Nodei info deg treeArray summary) else
                                     case info of None ⇒ return (Nodei info deg treeArray summary)|
                                          (Some mima) ⇒ (
                                               if x < fst mima ∨ x > snd mima then return (Nodei info deg
treeArray summary)
                                                  else if fst mima = x ∧ snd mima = x then return (Nodei
None deg treeArray summary)
                                                else do{ xminew <− (if x = fst mima then do {
                                                           firstcluster <− vebt-minti summary;
                                                          firsttree <− Array-Time.nth treeArray (the
firstcluster);
                                                           mintft <− vebt-minti firsttree;
                                                         let xn = (2^(deg div 2) * (the firstcluster) +
                                                                (the mintft) );
                                                           return (xn, xn)
                                                                }
                                                          else return (x, fst mima));
                                                  let xnew = fst xminew;
                                                  let xn' =
                                                   (if x = fst (the info')
                                                    then the (vebt-mint summary') * 2^(deg div 2)
                                                + the (vebt-mint (treeList ! the (vebt-mint summary')))
                                                    else x);
                                                  assert' (xnew = xn');
                                                  let minew = snd xminew;
                                                assert' (minew = (if x = fst (the info') then xn' else fst
(the info')));
```

```
  h <− highi xnew (deg div 2);
  assert′ (h = high xnew (deg div 2));
  assert′( h < length treeList);
  l <− lowi xnew (deg div 2);
  assert′(l = low xnew (deg div 2));
  aktnode <− Array-Time.nth treeArray h;
  aktnode′<−vebt-deletei′ (treeList ! h) aktnode l;
  treeArray′ <− Array-Time.upd h aktnode′ treeArray;
 let funnode = vebt-delete (treeList !  h) l;
 let treeList′ = treeList[h:= funnode];
  miny <− vebt-minti aktnode′;
  assert′ (miny = vebt-mint funnode);
 (if (miny = None) then
  do{
     summaryi′ <−vebt-deletei′ summary′ summary h;
     ma <−  (if xnew = snd mima then
     do{
        summax <− vebt-maxti summaryi′;
              assert′ (summax = vebt-maxt (vebt-delete
summary′ h));

        if summax = None then
             return minew
        else do{
            maxtree <− Array-Time.nth treeArray′ (the
summax);

              mofmtree<− vebt-maxti maxtree;
              return (the summax ∗ 2^(deg div 2) +
                           the mofmtree )
              }
       }
        else return (snd mima));
     return (Nodei (Some (minew, ma)) deg treeArray′
summaryi′)

 } else  if xnew = snd mima then
   do{
      nextree <− Array-Time.nth treeArray′ h;
      maxnext<− vebt-maxti nextree;
      assert′ (maxnext = vebt-maxt (treeList′ ! h));
      let ma = h ∗ 2^(deg div 2) +
                 (the maxnext);
     return (Nodei (Some ( minew, ma)) deg treeArray′
summary)

      }
     else return (Nodei (Some (minew, snd mima)) deg
treeArray′ summary) )

 })}))
```

theorem *deleti′-rf-abstr*:

notes *list-update-beyond* [*simp*]
shows *invar-vebt t n* $\Longrightarrow$ <*vebt-assn-raw t ti*> *vebt-deletei' t ti x*< *vebt-assn-raw* (*vebt-delete t x*)>
⟨*proof*⟩

lemma *TBOUND-vebt-deletei*:
defines *foo-def*: $\bigwedge$ *t x. foo t x* ≡ *if minNull* (*vebt-delete t x*) *then 1 else 20* ∗ (*1*+*height t*)
shows *TBOUND* (*vebt-deletei' t ti x*) (*foo t x*)
⟨*proof*⟩

lemma *vebt-deletei-refines*: *refines* (*vebt-deletei ti x*) (*vebt-deletei' t ti x*)
⟨*proof*⟩

lemma *htt-vebt-deletei*: **assumes** *invar-vebt t n*
shows <*vebt-assn-raw t ti*> *vebt-deletei ti x* <λ *r. vebt-assn-raw* (*vebt-delete t x*) *r* >*T*[*20* + *20*∗(*nat* ⌈*lb n*⌉)]
⟨*proof*⟩

end
end

22 Imperative Interface

theory *VEBT-Intf-Imperative*
imports
VEBT-Definitions
VEBT-Uniqueness
VEBT-Member
VEBT-Insert VEBT-InsertCorrectness
VEBT-MinMax
VEBT-Pred VEBT-Succ
VEBT-Delete VEBT-DeleteCorrectness
VEBT-Bounds
VEBT-DeleteBounds
VEBT-Space
VEBT-Intf-Functional
VEBT-List-Assn
VEBT-BuildupMemImp
VEBT-SuccPredImperative
VEBT-DelImperative
begin

22.1 Code Export

context begin
interpretation *VEBT-internal* ⟨*proof*⟩

lemmas [*code*] = *replicatei.simps vebt-memberi.simps highi-def lowi-def vebt-inserti.simps minNulli.simps vebt-succi.simps vebt-predi.simps vebt-deletei.simps greater.simps*

end

export-code
vebt-buildupi
vebt-memberi
vebt-inserti
vebt-maxti vebt-minti
vebt-predi vebt-succi
vebt-deletei

checking *SML-imp*

22.2 Interface

definition *vebt-assn*::*nat* ⇒ *nat set* ⇒ *VEBTi* ⇒ *assn* **where**
vebt-assn n s ti ≡ ∃$_A$ *t*. *vebt-assn-raw t ti* ∗ ↑(*s* = *set-vebt t* ∧ *invar-vebt t n*)

22.2.1 Buildup

context begin
interpretation *VEBT-internal* ⟨*proof*⟩

interpretation *vebt-inst* **for** *n* ⟨*proof*⟩

lemma *vebt-buildupi-rule-basic*[*sep-heap-rules*]: *n* > *0* ⟹ <*emp*> *vebt-buildupi n* <λ *r*. *vebt-assn n* {} *r* >
⟨*proof*⟩

lemma *vebt-buildupi-rule*: <↑ (*n* > *0*)> *vebt-buildupi n* <λ *r*. *vebt-assn n* {} *r* > *T*[*10* ∗ *2^n*]
⟨*proof*⟩

22.2.2 Member

lemma *vebt-memberi-rule*: <*vebt-assn n s ti*> *vebt-memberi ti x* <λ *r*. *vebt-assn n s ti* ∗ ↑(*r* = (*x* ∈ *s*))>*T*[*5* + *5* ∗ (*nat* ⌈*lb n* ⌉)]
⟨*proof*⟩

22.2.3 Insert

lemma *vebt-inserti-rule*: *x* < *2^n* ⟹ <*vebt-assn n s ti*> *vebt-inserti ti x* <λ *r*. *vebt-assn n* (*s* ∪ {*x*}) *r* >*T*[*13* + *13* ∗ (*nat* ⌈*lb n* ⌉)]
⟨*proof*⟩

22.2.4 Maximum

lemma *vebt-maxti-rule*: <*vebt-assn n s ti*> *vebt-maxti ti* <λ *r*. *vebt-assn n s ti* ∗ ↑(*r* = *Some y* ⟷ *max-in-set s y*)>*T*[*1*]
⟨*proof*⟩

22.2.5 Minimum

lemma *vebt-minti-rule*: <*vebt-assn n s ti*> *vebt-minti ti* <λ *r*. *vebt-assn n s ti* ∗ ↑(*r* = *Some y* ⟷ *min-in-set s y*)>*T*[*1*]
⟨*proof*⟩

22.2.6 Successor

lemma *vebt-succi-rule*: <*vebt-assn n s ti*> *vebt-succi ti x* <λ *r*. *vebt-assn n s ti* ∗ ↑(*r* = *Some y* ⟷ *is-succ-in-set s x y*)>*T*[*7* + *7* ∗ (*nat* ⌈*lb n* ⌉)]
⟨*proof*⟩

22.2.7 Predecessor

lemma *vebt-predi-rule*: <*vebt-assn n s ti*> *vebt-predi ti x* <λ *r*. *vebt-assn n s ti* ∗ ↑(*r* = *Some y* ⟷ *is-pred-in-set s x y*)>*T*[*7* + *7* ∗ (*nat* ⌈*lb n* ⌉)]
⟨*proof*⟩

22.2.8 Delete

lemma *vebt-deletei-rule*: <*vebt-assn n s ti* > *vebt-deletei ti x* <λ *r*. *vebt-assn n* (*s* − {*x*}) *r* >*T*[*20* + *20* ∗ (*nat* ⌈*lb n* ⌉)]
⟨*proof*⟩

22.3 Setup of VCG

lemmas *vebt-heap-rules*[*THEN htt-htD*,*sep-heap-rules*] =
vebt-buildupi-rule
vebt-memberi-rule
vebt-inserti-rule
vebt-maxti-rule
vebt-minti-rule
vebt-succi-rule
vebt-predi-rule
vebt-deletei-rule

end
end

23 Interface Usage Example

theory *VEBT-Example*
imports *VEBT-Intf-Imperative VEBT-Example-Setup*
begin

23.1 Test Program

definition *test n xs ys* ≡ *do* {
t ← *vebt-buildupi n*;
t ← *mfold* (λ*x s*. *vebt-inserti s x*) (*0*#*xs*) *t*;

let f = (λx. if$_m$ vebt-memberi t x then return x else the $$_m$ (vebt-predi t x));

mmap f ys
}

23.2 Correctness without Time

The non-time part of our datastructure is fully integrated into sep-auto

lemma *fold-list-rl*[*sep-heap-rules*]: ∀ *x*∈*set xs*. *x*<*2^n* ⟹ *hoare-triple*
(*vebt-assn n s t*)
(*mfold* (λ*x s*. *vebt-inserti s x*) *xs t*)
(λ*t'*. *vebt-assn n* (*s* ∪ *set xs*) *t'*)
⟨*proof*⟩

lemma *test-hoare*: ⟦∀ *x*∈*set xs*. *x*<*2^n*; *n*>*0*⟧ ⟹
<*emp*> (*test n xs ys*) <λ*r*. ↑(*r* = *map* (λ*y*. (*GREATEST y'*. *y'*∈*insert 0* (*set xs*) ∧ *y'*≤*y*)) *ys*)
>$_t$
⟨*proof*⟩

23.3 Time Bound Reasoning

We use some ad-hoc reasoning to also show the time-bound of our test program. A generalization of such methods, or the integration of this entry into existing reasoning frameworks with time is left to future work.

lemma *insert-time-pure*[*cond-TBOUND*]:*a* < *2^n* ⟹
§*vebt-assn n S ti*§ *TBOUND* (*vebt-inserti ti a*) (*13* + *13* ∗ *nat* ⌈*log 2* (*real n*)⌉)
⟨*proof*⟩

lemma *member-time-pure*[*cond-TBOUND*]:§*vebt-assn n S ti*§ *TBOUND* (*vebt-memberi ti a*) (*5* + *5* ∗ *nat* ⌈*log 2* (*real n*)⌉)
⟨*proof*⟩

lemma *pred-time-pure*[*cond-TBOUND*]:§*vebt-assn n S ti*§ *TBOUND* (*vebt-predi ti a*) (*7* + *7* ∗ *nat* ⌈*log 2* (*real n*)⌉)
⟨*proof*⟩

lemma *TBOUND-mfold*[*cond-TBOUND*]:
(⋀ *x*. *x* ∈ *set xs* ⟹ *x* < *2^n*) ⟹
§ *vebt-assn n S ti* § *TBOUND* (*mfold* (λ*x s*. *vebt-inserti s x*) *xs ti*) (*length xs* ∗ (*13* + *13* ∗ *nat* ⌈*log 2 n* ⌉) + *1*)
⟨*proof*⟩

lemma *TBOUND-mmap*[*cond-TBOUND*]:
defines *b-def*: *b ys n* ≡ *1* + *length ys* ∗ (*5* + *5* ∗ *nat* ⌈*log 2* (*real n*)⌉ + *9* + *7* ∗ *nat* ⌈*log 2* (*real n*)⌉)
shows § *vebt-assn n S ti* § *TBOUND*

(*mmap* (λ*x*. *if*$_m$ *vebt-memberi ti x then return x*
else vebt-predi ti x ⤜ (λ*x*. *return* (*the x*))) *ys*) (*b ys n*)
⟨*proof*⟩

lemma *TBOUND-test*[*cond-TBOUND*]: ⟦∀ *x*∈*set xs*. *x*<2^*n*; *n*>*0* ⟧ ⟹
§ ↑ (*n*> *0*) § *TBOUND* (*test n xs ys*) (*10* ∗ *2*^*n* + (
(*length* (*0*#*xs*) ∗ (*13* + *13* ∗ *nat* ⌈*log 2 n* ⌉) + *1*) +
(*1* + *length ys* ∗ (*5* + *5* ∗ *nat* ⌈*log 2* (*real n*)⌉ + *9* + *7* ∗ *nat* ⌈*log 2* (*real n*)⌉))))
⟨*proof*⟩

lemma *test-hoare-with-time*: ⟦∀ *x*∈*set xs*. *x*<2^*n*; *n*>*0*⟧ ⟹
<*emp*> (*test n xs ys*) <λ*r*. ↑(*r* = *map* (λ*y*. (*GREATEST y'*. *y'*∈*insert 0* (*set xs*) ∧ *y'*≤*y*)) *ys*) ∗ *true* >
T[*10* ∗ *2* ^ *n* +
(*length* (*0* # *xs*) ∗ (*13* + *13* ∗ *nat* ⌈*log 2* (*real n*)⌉) + *1* +
(*1* + *length ys* ∗ (*5* + *5* ∗ *nat* ⌈*log 2* (*real n*)⌉ + *9* + *7* ∗ *nat* ⌈*log 2* (*real n*)⌉)))]
⟨*proof*⟩

end

24 Conclusion

We have formalized van Emde Boas trees in Isabelle, proving correct a functional and an imperative version, together with space and run-time bounds. This work amends a list [4] of formally verified CLRS algorithms [3].

Closing we sketch some enhancements of van Emde Boas trees in Isabelle. An examination of the data structure points out that there is probably a *join* operation with the semantics *set-vebt* (*vebt-join s t*) = *set-vebt s* ∪ *set-vebt t*. We make the restriction of joining only valid trees with equal degree numbers. Obviously, the join of two leaves is trivial. If one tree is empty or singleton, a join is implemented by immediately returning the other tree or performing an insertion before. Otherwise, summary and subtrees are to be joined recursively and afterwards we have to determine minimum and maximum. Certainly, this last step can be complicated, because argument trees may also coincide on minima or maxima.

One may also consider the treatment of associated satellite data. Those are to be stored in ordinary subtrees, whereas the definition of summary trees does not have to be changed. We can transfer this to Isabelle by introducing another data type representing van Emde Boas trees. The adapted *naive-member* and *membermima* still refer to integer keys, but we add an auxiliary function *assoc* such that *assoc t x y* holds iff the key x is associated with the value y. A *both-member-options* is also defined and can be used for specifying a suitable validness invariant. We may show a conjecture like *both-member-options t x* ⟷ ∃ *y*. *assoc t x y*. Besides, valid trees enforce keys to be associated with at most one value. All canonical functions f are shifted to the new type and return a key-value pair (x, y) or the modified tree. Proofs for being x the desired successor etc. are obtained by reuse and adaptation of prior proofs. In addition, modified canonical functions f' may only return the associated values y.

We show the proposition $\exists\, x.\ f\ t\ i = (x,\, y) \longleftrightarrow f'\ t\ i = y$. All writing operations require a reasoning regarding the proper (non-)modification of associations. The modified functions f' are to be exposed to a user later on.

Moreover, we did not consider lazy implementation. Currently, *vebt-buildup* n generates a full van Emde Boas tree of degree n. A *lazy implementation* would construct a subtree only if needed. From this just a constant amount of additional effort per recursive step will arise. Thereby, proven running time bounds of $\mathcal{O}(\log \log u)$ will be preserved. Beside this, a lazy implementation can also be obtained by exporting verified Isabelle code to Haskell, which heavily applies the lazy evaluation technique.

Obviously, a lazy implementation would drastically reduce memory usage. Each insertion allocates $\mathcal{O}(\log \log u)$ space and hence an implementation that does not store empty subtrees gives us memory consumption in $\mathcal{O}(n \cdot \log \log u)$ where n is the number of elements currently stored. Furthermore, one may replace ordinary arrays by *dynamic perfect hashing* [9] allowing treatment of elements in (amortized) constant time and linear space. Unfortunately, a linear memory consumption in $\mathcal{O}(n)$ is achieved at cost of some worst case runtime bounds [10]. By this, $\mathcal{O}(\log \log u)$ is turned to an amortized bound for *vebt-insert* and *vebt-delete*, since the complexity of those functions is indeed affected by the amortization. An implementation of this van Emde Boas tree variant requires verified dynamic perfect hashing and amortization in Isabelle to build on.

We used Imperative HOL due to its support of arrays and type reflexive references that are necessary for setting up a recursive tree data structure. For generating verified code, however, there also exist other frameworks, e.g. Isabelle LLVM [11] [12]. It supports refinement-based verification of correctness and worst-case time complexities. Additionally, verified programs can be exported to LLVM code, which itself is compiled to executable machine code. Strikingly, code of the introsort algorithm generated by this formalization stayed competitive with the GNU C++ library [12].

References

[1] P. van Emde Boas. "Preserving order in a forest in less than logarithmic time". In: *16th Annual Symposium on Foundations of Computer Science (sfcs 1975)*. 1975, pp. 75–84. DOI: 10.1109/SFCS.1975.26.

[2] P. E. Boas, R. Kaas, and E. Zijlstra. "Design and implementation of an efficient priority queue". In: *Mathematical Systems Theory* 10.1 (1976), pp. 99–127. DOI: 10.1007/bf01683268.

[3] T. H. Cormen, C. E. Leiserson, R. L. Rivest, and C. Stein. *Introduction to Algorithms, Third Edition*. 3rd. The MIT Press, 2009. ISBN: 0262033844.

[4] T. Nipkow, M. Eberl, and M. P. L. Haslbeck. "Verified Textbook Algorithms. A Biased Survey". In: *ATVA 2020, Automated Technology for Verification and Analysis*. Ed. by D. V. Hung and O. Sokolsky. Vol. 12302. LNCS. Invited paper. Springer, 2020, pp. 25–53.

[5] Tobias Nipkow, Jasmin Blanchette, Manuel Eberl, Alejandro Gómez-Londoño, Peter Lammich, Christian Sternagel, Simon Wimmer, Bohua Zhan. *Functional Algorithms, Verified!* https://functional-algorithms-verified.org/. 2021.

[6] P. Lammich and R. Meis. "A Separation Logic Framework for Imperative HOL". In: *Archive of Formal Proofs* (Nov. 2012). https://isa-afp.org/entries/Separation_Logic_Imperative_HOL.html, Formal proof development. ISSN: 2150-914x.

[7] P. Lammich. "Refinement to Imperative HOL". In: *Journal of Automated Reasoning* 62 (Apr. 2019). DOI: 10.1007/s10817-017-9437-1.

[8] B. Zhan and M. P. L. Haslbeck. *Verifying Asymptotic Time Complexity of Imperative Programs in Isabelle*. 2018. arXiv: 1802.01336 [cs.LO].

[9] M. Dietzfelbinger, A. Karlin, K. Mehlhorn, F. Meyer auf der Heide, H. Rohnert, and R. Tarjan. "Dynamic Perfect Hashing: Upper and Lower Bounds". In: vol. 0. Jan. 1988, pp. 524–531. DOI: 10.1109/SFCS.1988.21968.

[10] M. Straka. "Functional Data Structures and Algorithms". https://ufal.mff.cuni.cz/~straka/theses/doctoral-functional_data_structures_and_algorithms.pdf. PhD thesis. Charles University in Prague, Faculty of Mathematics and Physics, 2013.

[11] P. Lammich. "Generating Veried LLVM from Isabelle/HOL". English. In: *ITP 2019: Interactive Theorem Proving*. Interactive Theorem Proving, ITP 2019 ; Conference date: 08-09-2019 Through 13-09-2019. June 2019.

[12] M. P. L. Haslbeck and P. Lammich. "For a Few Dollars More". In: *Programming Languages and Systems*. Ed. by N. Yoshida. Cham: Springer International Publishing, 2021, pp. 292–319. ISBN: 978-3-030-72019-3.